Updates to 12/22/00 Compliance Filing

New York State Virginia Carrier-to-Carrier Guidelines Performance Standards and Reports

Verizon Reports

<u>DRAFT</u>

January April 30, 2001

Category		Function	# of Metrics	Page #
Pre-Ordering	PO-1	Response Time OSS Ordering Interface	9	
i io oraoning	PO-2	OSS Interface Availability	3	
	PO-3	Contact Center Availability	4	
	PO-4	Change Management Notice	3	
	PO-5	Average Notification of Interface Outage	1	
	PO-6	Software Validation	1	
	PO-7	Software Problem Resolution and Timeliness	4	
_	PO-8	Manual Loop Qualification	2	
Ordering	OR-1	Order Confirmation Timeliness	14	
	OR-2	Reject Timeliness	12	
	OR-3	Percent Rejects	2	
	OR-4	Timeliness of Completion Notification	12	
	OR-5 OR-6	Percent Flow-Through	3 3	
	OR-6 OR-7	Order Accuracy Percent Order Confirmation Rejects sent within 3 days	1	
	OR-8	Acknowledgement Timeliness	1	
	OR-9	Order Acknowledgement Completeness	1	
Provisioning	PR-1	Average Interval Offered	10	
Flovisioning	PR-2	Average Interval Completed	11	
	PR-3	Completed within Specified Number of Days (1-5 Lines)	11	
	PR-4	Missed Appointments	8	
	PR-5	Facility Missed Orders	3	
	PR-6	Installation Quality	3	
	PR-7	Jeopardy Reports	1	
	PR-8	Open Orders in a Hold Status	2	
	PR-9	Hot Cut Performance	3	
Maintenance	MR-1	Response Time OSS Maintenance Interface	6	
& Repair	MR-2	Trouble Report Rate	5	
o. repuii	MR-3	Missed Repair Appointments	5	
	MR-4	Trouble Duration Intervals	10	
	MR-5	Repeat Trouble Reports	1	
Network	NP-1	Percent Final Trunk Group Blockage	4	
Performance	NP-2	Collocation Performance	8	
	NP-3	Switching Performance	0	
Dillin n	NP-4	Notification of Network Outage	0	
Billing	BI-1 BI-2	Timeliness of Daily Usage Feed Timeliness of Carrier Bill	4	
	BI-3	Billing Accuracy	2	
Operator	OD-1	Operator Services – Speed of Answer/Directory	2	
Operator	וייטט	Assistance	_	
Services	OD-2	LIDB, Routing and OS/DA Platforms	0	
General	GE-1	Directory Proofs	0	
Standards	GE-2	Poles, Ducts, Conduit and Rights of Way	0	
Glossary		Glossary of Terms		

Appendix	Topic
Α	Specials and Trunk Maintenance Code Descriptions
В	Provisioning Codes
С	Pre-Ordering Details
D	Bona Fide Request ProcessHoliday Schedule
E	Local Number Portability Process
F	E911 Updates
G	Repair Disposition Codes
Н	Flow-Through Order Scenarios
I	Trunk Forecasting Guide
J	Collocation Forecasting Guide
K	Statistical Methodology
L	Product Interval Summary
M	Order Accuracy Details
N	Table of Measures, Sub-Metrics and Product Disaggregation
0	Test Deck – Weighted transaction Matrix

<u>Exhibits</u>	
<u>1</u>	Additional Provisions

INTRODUCTION

This section of the New York State The Virginia Carrier-to-Carrier (C2C) Guidelines Performance Standards and Reports provides the metrics and performance standards applicable to New York Telephone Company, d/b/a Verizon Virginia Inc. New York ("Verizon VA," "Verizon" or "VZ"-NY). Comprehensive explanations of the standard's definitions, measurement methodologies, reporting levels, geography covered, and the current product intervals, are included within this document. In addition, this section document includes a glossary and appendices that provide explanatory material related to the metrics and standards. The appendices also include a description of a statistical methodology that will be applied to help assess whether there is any difference between the delivery of Verizon New York Virginia retail services and its wholesale products and services.

Verizon New York Virginia will provide Performance Reports on a monthly basis. to the A Competitive Local Exchange Carriers (CLECs) that were members of the C2C working group in Case 97-C-0139 and to any CLEC that previously requested to receive Performance Reports issued pursuant to the Interim Guidelines, adopted in Case 97-C-0139. Any other CLEC that wishesants to obtain reports produced pursuant to the Guidelines must contact the Account Manager that Verizon New York Virginia has designated for that CLEC to make the appropriate arrangements to receive the reports.

Section 1

Pre-Ordering Performance

(PO)

Function		Number of Sub-metrics	
PO-1	Response Time OSS Ordering Interface	9	
PO-2	OSS Interface Availability	3	
PO-3	Contact Center Availability	4	
PO-4	Change Management Notice	3	
PO-5	Average Notification of Interface Outage	1	
PO-6	Software Validation	1	
PO-7	Software Problem Resolution and Timeliness	4	
PO-8	Manual Loop Qualification	2	

4

PO-1 Response Time OSS Ordering Interface

Definition:

This metric measures the response time of the OSS Ordering Interface.

Response Time: For metrics PO-1-01 through 1-06_and PO-1-09, response time is the amount of time, rounded to the nearest 1/100th of a second for a Pre-Order transaction. For CLEC transactions, this is measured from receipt of the request at Verizon's interface to the time that the response is sent to the CLEC. For Verizon retail simulated transactions, performance is measured between the issuance of a Pre-Ordering guery and the successful receipt of the requested information in a specific field and screen.

For PO-1-07, response time is the amount of time, rounded to the nearest 1/100th of a second, between the issuance of a Pre-Ordering query and the receipt of an error message associated with a rejected query.

Average Response Time: Average Response Time is the sum of the response times divided by the number of Pre-Ordering queries in the report period. It is calculated separately for PO-1-01 through PO-1-07 and PO-1-09. Queries that time-out are excluded from the calculation of Average Response Time.

Rejected Query: A rejected query is a query that cannot be processed successfully due to incomplete or invalid information submitted by the sender, which results in an error message back to the sender.

Time-out: A query is considered to be a time-out when the requested information (or an error message) is not provided within 60 seconds. Time-outs are set at long intervals to ensure that average response times include long response times but do not include queries that will never complete.

Exclusions:

Normal exclusions include Saturday, Sunday, and major holidays, as well as hours outside of the normal report period.

Note: If response time aberrations occur due to EnView robot failures or network failures between EnView and the VZ Operations Support Systems (OSS), VZ notes such failure times, and reports the data without exclusion in a footnote on the report.

Performance Standard:

The Performance Standards for the PO-1 metrics are as follows:

For PO-1-01 through PO-1-03, and PO-1-05 through PO-1-07:

- _____-EDI and CORBA (application to application interfaces): _Parity with Retail plus not more than four (4) seconds. The four (4) second difference allows for variations in functionality and additional security requirements of interface.
- For WEB GUI: Parity with Retail plus not more than seven (7) seconds. The seven (7) second difference allows for variations in functionality and additional security requirements of interface.

For PO-1-04, Product & Service Availability, and PO-1-09, Parsed CSR: Parity with Retail, plus not more than 10 seconds.

For PO-1-08: Not greater than 0.33%.

Methodology:

The measurements for all PO-1 metrics (except PO-1-07) are derived from actual production transactions for CLEC transactions and from simulated Pre-Ordering queries generated by Verizon's New York's-EnView (formerly referred to as Sentinel) system for VZ retail transactions and CLEC PO-1-07 transactions.

For retail (and CLEC PO-1-07) transactions, EnView replicates the keystrokes a VZ Service

Representative would enter for a valid Pre-Ordering inquiry transaction, and measures the response time from when the *Ente*r key is hit until a response from the Pre-Ordering OSS is received back on the display screen.

At least ten VZ retail (and CLEC PO-1-07) simulated queries are generated per hour for each type of query.

Methodology – Response Time OSS (Continued):

The total number of simulated gueries depends on the average response times.

Each query has a unique name that is based on time and date. The EnView robot monitors for a matching response, and identifies successful responses by the file extension names. The file extension varies according to whether the transaction was successful or experienced an error or time-out condition. Successful response for an Address Validation request is identified by a file extension of *ada*. The file is then read to ensure it starts and ends with the appropriate indicators for a successful transaction.

EnView also generates at least ten simulated incomplete or invalid Pre-Ordering queries per hour to enable measurement of PO-1-07 Average Response Time – Rejected Query.

Data is reported based on transactions occurring between 8:00AM and 9:00PM Monday through Friday, **excluding** New Year's Day, Memorial Day, July 4th, Labor Day, Thanksgiving Day, and Christmas Day.

Formula:

 Σ Response Times for each transaction divided by the Number of Simulated-Transactions for each transaction type.

Report Dimensions:

respond Dimensioner				
Company:	Geography:			
VZ Retail ¹	New York Virginia			
CLEC Aggregate				
CLEC Specific (PO-1-09 only)				

Products

CLEC Aggregate:

- EDI
- CORBA
- WEB GUI

Sub-Metrics – PO-1 Response Time OSS Ordering Interface

PO-1-01	Average Response Time – Customer Service Record (CSR)			
Calculation	Numerator Denominator			
	Sum of all response times for CSR transactions.	Number of CSR transactions.		
PO-1-02	Average Response Time – Due Date Av	ailability		
Calculation	Numerator	Denominator		
	Sum of all response times for Due Date	Number of Ddue Date Availability		
	(DD) Availability.	transactions.		
PO-1-03	Average Response Time – Address Validation			
Calculation	Numerator	Denominator		
	Sum of all response times for Address Validation.	Number of Address Validation transactions.		
PO-1-04	Average Response Time – Product & Service Availability			
Calculation	Numerator	Denominator		
	Sum of all response times for Product and Service Availability.	Number of Product and Service availability transactions.		

¹ There is no Parsed CSR for retail, therefore basic CSR will be reported for retail performance.

Sub-Metrics – (continued) Response Time OSS Ordering Interface			
PO-1-05	Average Response Time – Telephone Number Availability & Reservation ²		
Calculation	Numerator Denominator		
	Sum of all response times for Telephone Number Availability/Reservation.	Number of Telephone Number Availability/Reservation transactions.	
PO-1-06	Average Response Time – Mechanized	Loop Qualification – DSL	
Calculation	Numerator	Denominator	
	Sum of all response times for Mechanized Loop Qualification.	Number of Mechanized Loop Qualification transactions.	
PO-1-07	Average Response Time – Rejected Query		
Calculation	Numerator	Denominator	
	Sum of all response times for a rejected query.	Number of rejected query transactions.	
PO-1-08	% Timeouts		
Calculation	Numerator Denominator		
	Number of transactions that timeout.	Total number of transactions.	
PO-1-09	Parsed CSR		
Calculation	Numerator	Denominator	
	Sum of all response times for Parsed CSR transactions.	Number of Parsed CSR transactions.	

² While Address Validation can be completed on a stand-alone basis, Telephone Number reservation is always combined with Address Validation. For VZ retail representatives this is a required two step process requiring two separate transactions.

PO-2 OSS Interface Availability

Definition:

This metric measures the OSS Interface Availability. The OSS Interface Availability metric is a measurement of the time during which the electronic OSS Interface is actually available as a percentage of scheduled availability. Verizon Service Representatives and CLEC Service Representatives obtain Pre-Ordering information from the same underlying OSS. Thus, if a particular OSS is down, it is equally unavailable to both Verizon employees and CLEC employees. Any difference in availability, therefore, is caused by unavailability of the OSS interface.

Scheduled Availability is as follows:

- Prime Time: 6:00AM to 12:00AM EST Monday through Saturday, excluding Holidays
- Non-Prime Time: 12:01AM to 5:59AM EST Monday through Saturday, including and all day Sundays and Holidays.

Note: The number of downtime hours is noted in the Carrier to Carrier (C2C) reports under the *Observations* column heading.

Separate measurements are performed for each of the following: Pre-Ordering/Ordering EDI, Pre-Ordering/Ordering/Maintenance Web GUI. CORBA, and Maintenance-Electronic Bonding. The EnView process will be expanded/updated to monitor and report on future OSS processes.

Exclusions:

The following exclusions apply:

- Troubles reported but not found in VZ's systems.
- Troubles reported by a CLEC that were not reported to VZ's designated trouble reporting center.
- Scheduled interface outages for major system releases where CLECs were provided with advanced notification of the downtime in compliance with VZ Change Management Guidelines.

Performance Standard:

Metrics PO-2-01 and 03: No standard.

Metric PO-2-02: _≥ 99.5%

Methodology – PO-2 OSS Availability

Verizon uses EnView as one means of monitoring all VZ systems, including Retail OSS. VZ measures reported outages, based on actual reported time frames as well as any outages captured by EnView and not reported by CLECs. EnView is used as an alarm for system availability and to supplement CLEC reported outages. If no CLEC reported an outage, but EnView detected an outage, the EnView outage is included as if the entire CLEC population experienced the outage.

EnView measurement of the EDI, Web GUI, and CORBA interface availability is as follows: The mechanized OSS interface availability process is based on the transactions created by the EnView Robots. The program determines whether the Enview transactions were successful or unsuccessful, or if no transactions were issued (not polled). Transactions are processed by transaction type separately for each interface type and OSS. The hours of the day are divided into six (6) minute measurement periods.

If EDIan interface, for any Pre-Order transaction type, in a six (6) minute measurement period has at least one successful transaction, then EDIthat interface is considered available. EDI-Interface unavailability is calculated only when all-EDI interface transactions are unsuccessful and at least one of the corresponding OSS transactions is successful. This indicates that EDIthe interface was not available while at least one OSS was available. In this case, the six (6) minute measurement period is counted as unavailable. If it is determined that no Enview transactions were issued, then the six minute measurement period is excluded from all calculations since this is an indication of an EnView problem and not an EDIInterface problem.

Methodology –OSS Availability (Continued):

plus scheduled downtime.

Availability is calculated by dividing the total number of six (6) minute measurement periods in a 24-hour day (excluding unmeasured six (6) minute measurement periods) into the number of periods with no successful transactions for the day and subtracting this from 1 and multiplying by 100.

For example, there are potentially 160 six (6) minute measurement periods in a 16-hour period. If two six (6) minute measurement periods lack successful transactions, then availability equals (1-(2/160)) x 100 = 98.75% Availability.

Trouble Logs: Verizon will make Verizon's trouble logs (which contain CLEC reports that the interface is not available) available to the CLECs for inspection.

Formula:

-(Number of hours scheduled minus the number of scheduled hours not available) divided by (Number of hours scheduled) multiplied by 100.

Report Dime	ensions:			
Company:		Geography	y:	
CLEC Aggregate		 New York District of Columbia, Maryland, 		
		<u>Vi</u>	irginia, and West Virginia (combined data)	
Products	Maintenance Web GUI (I	RETAS) / I	Pre-Ordering/Ordering Web GUI	
	• EDI			
	• CORBA			
	Maintenance – Electroni	c Bonding		
Sub-Metrics	 OSS Interface Availability 	/		
PO-2-01	OSS Interface Availability – To	tal		
Calculation	Numerator		Denominator	
	Number of hours in month minus the		Number of Hours in Month.	
	Number of hours interface is not a	vailable		
	during month plus scheduled dow	ntime.		
PO-2-02	OSS Interface Availability – Pr	ime-Time		
Calculation	Numerator		Denominator	
	Number of prime-time hours in mo	onth	Number of Prime-Time Hours in Month.	
	minus the Number of prime-time h	nours in		
	month interface is not available plus			
	scheduled downtime.			
PO-2-03	OSS Interface Availability – Non-Prime-Time			
Calculation	Numerator		Denominator	
	Number of non-prime-time hours i		Number of Non-Prime-Time Hours in Month.	
	minus the Number of non-prime-time			
	hours in month interface is not ava	ailable		

PO-3 Contact Center Availability

Definition:

This metric measures the Contact Center Availability. Contact Center Availability is the hours of operation for the Centers that support CLECs for Ordering, Provisioning, Maintenance and Billing issues. Contact with CLECs is designed to take place via direct access systems. Carrier Support Centers are designed to handle fall-out and not large call volumes.

This metric also includes **Speed of Answer – CLEC** centers. Speed of Answer is measured for Ordering and Repair queues. This measure is reported out of the Automated Call Distributor (ACD). The Speed of Answer measure includes calls that go to the main number in the center, either directly or from overflow (CLECs choosing the option of the main number).

Note: Consistent with proposed end-user standard, % within 30 seconds includes 15% of Abandons and 10% of Busies in the denominator.

Speed of Answer is measured in seconds from the time a call enters the VZ ACD, following selection of a menu option, until a representative answers the call. CLECs have the choice of calling the order processing 800 number, in which case the call is directed to the next available representative through the ACD, or CLECs can call their dedicated representatives on the representative's direct line. Calls placed to the representative's direct line, if unanswered, will be forwarded to the ACD, following selection of a menu option. If the representative is not available, the CLEC can leave a voice mail or press 0 and be transferred to a pool of representatives. VZ measures speed of answer for calls to the 800 number and for calls where the CLEC presses 0 to speak to the next available representative and for calls forwarded to the ACD.

Speed of Answer measurements begin as follows: For calls to the 800 number, the measurement begins when the call enters VZ's ACD, following selection of a menu option. For calls to a dedicated representative that are forwarded to the ACD, the measurement begins when the forwarded call enters VZ's ACD, following selection of a menu option. The CLEC presses 0. In each case, the measurement ends when a representative answers the call.

Exclusions:

Calls directed to and answered by dedicated representatives.

Performance Standard:

Center Hours of Operation:

Repair Help Desk: 24 hours/day – seven (7) days a week

Order Entry Assistance: 7:00AM to 12:00AM Monday through Friday, and 8:00AM to 6:00PM Saturday.

Order Processing Assistance: 7:00AM to 6:00PM Monday through Friday. National Market Center (Ordering): 8 AM to 6 PM, Monday through Friday

Billing & Collections: 7:00AM to 6:00PM Monday through Friday.

System Administration 8:00AM to 6:00PM Monday through Friday.

To match proposed End User Standard: Metrics PO-3-02 and 04, Speed of Answer: _80% within 30 seconds.

Metrics PO-3-01 and 03: No standard.

Products	Resale	•	UNE
Sub-Metrics			
PO-3-01	Average Speed of Answering – Ordering	9	
Calculation	Numerator		Denominator

Sum of time from call initiated to call	Total Calls Answered by Ordering Center.
answered for calls placed to main number	
through the ACD.	

Sub-Metrics (continued) Contact Center Availability			
PO-3-02	% Answered within 30 Seconds – Ordering		
Calculation	Numerator Denominator		
	Number of calls to main number answered within 30 seconds after the call was received by the ACD.	Total calls answered by Ordering Center plus 15% of abandoned calls plus 10% of busy calls.	
PO-3-03	Average Speed of Answering – Repair		
Calculation	Numerator	Denominator	
	Sum of time from call initiated to call answered for calls placed to the main repair number through the ACD.	Total calls answered by Repair Center.	
PO-3-04	% Answered within 30 Seconds – Repair	•	
Calculation	Numerator Denominator		
	Number of calls to main number answered within 30 seconds after the call was received by the ACD.	Total calls answered by Repair Center plus 15% of abandoned calls plus 10% of busy calls.	

PO-4 Timeliness of Change Management Notice

Definition:

This metric measures the percent of Change Management Notices and associated documentation availability sent before implementation according to prescribed timeliness standards within prescribed timeframes.

Documentation is not considered available until all material changes are made.

Exclusions:

None.

Performance Standard:

Performance standards are set forth in the Change Management Processes and Procedures. VZ will comply with applicable Change Management Processes and Procedures.

The performance standard for <u>Metric PO-4-01</u>, % Change Management Notices sent on time is 95% or greater, and, for <u>Metric PO-4-03</u>, no delayed notices and documentation over eight (8) <u>or more</u> days <u>late</u>.

For Metric PO-4-02: No standard.

Timeliness Standards:

* Regulatory changes will vary based on applicable tion law/regulatory rules.

Tillelliess Stalidards.				
Change type		Change Notification: Interval between	Change Confirmation: Final Documentation	
		notification and implementation	Availability before implementation ³	
Type 5 – CLEC originated		≥ 73 days for business rules, ≥ 66 days	>= 45 days	
		for technical specifications)		
Type 4 – Verizon		≥ 73 days for business rules, ≥ 66 days	>= 45 days	
originated		for technical specifications)		
Type 3 – Industry		≥ 73 days for business rules, ≥ 66 days	>= 45 days	
Standard		for technical specifications)		
Type 2 – Regulatory	/	Time periods established in Regulatory	Time periods established in Regulatory Order. If no	
		Order. If no time periods set, default to	time periods set, default to above time period.	
		above time period.		
Type 1 – Emergency	у	Notification before implementation	N/A	
Maintenance	1			
Products	Chan	ge Notification:	Change Confirmation	
	Type 1 – Emergency Maintenance		 Type 2 – Regulatory 	
	• T	ype 2 Regulatory	 Type 3 – Industry Standard 	
	• T	ype 3 – Industry Standard	 Type 4 – VZ originated 	
	• T	ype 4 – VZ originated	 Type 5 – CLEC originated 	
	• T	ype 5 – CLEC originated		
Sub-Metrics				
PO-4-01	% Change Management Notices sent on Time			
Calculation	Numerator		Denominator	
	Chan	ge Management Notifications sent	Total number of Change Management	
	within required time frames.		Notices sent.	
PO-4-02	Change Management Notice – Delay one (1) to seven (7) days		e (1) to seven (7) days	
Calculation			a Value	

PO-4-03

Calculation

Data Value

Cumulative delay days for all notices sent one (1) to seven (7) days late.

Change Management Notice - Delay eight (8) plus days

³ Type one (1) change confirmation is not applicable.

Cumulative delay days for all notices sent eight (8) or more days late.

PO-5 Average Notification of Interface Outage

Definition:

This metric measures the average amount of time that elapses between VZ identification of an interface outage and VZ notification to CLECs that an outage exists. Notification is provided by electronic mail.

Note: Notification of Network Outages (different than Interface Outages) are covered in the Network Performance section. Detailed information on network outages can also be found in the CLEC Handbook.

Exclusions:

None.

Performance Standard:

Not more than: 20 minutes.

Report Dimensions

Company:

• CLEC Aggregate

Geography:

 VZ North States Notification of interface outages for OSS interfaces serving Virginia (combined data). (Note, an OSS interface may handle CLEC transactions not only for Virginia but also for other jurisdictions.)

Sub-Metrics

PO-5-01	Average Notice of Interface Outage			
Calculation	Numerator Denominator			
	Date and time of outage notification to CLECs minus date and time the interface	Total number of interface outages for which notice was given.		
	outage was identified by VZ.	notice was given.		

PO-6 Software Validation

Definition:

This metric measures software validation. Verizon maintains a test deck of transactions that are used to validate that functionality in a software release works as designed. Each transaction in the test deck is assigned a weight factor, which is based on the weights that have been assigned to the metrics in any Performance Assurance Plan (PAP) that the Commission may adopt in relationship to Verizon New York's application to provide interLATA services in New York. Within the software validation metric, weight factors will be allocated among transaction types (e.g., Pre-Order, Resale-Order, UNE-Order, Platform-Order) and then equally distributed across specific transactions within type. The initial array of weights for the transaction types are displayed in Appendix O. If test transactions are added to the test deck, the distribution of weights between transaction types will be retained, and then equally re-distributed across specific transactions within type. The allocation of weight factors among transaction types may be adjusted as part of the annual review process.

Verizon New York will execute the test deck at the start of the Quality Assurance (QA) and at the completion of QA. Within one (1) business day, following a non-emergency software release to production as communicated through Change Management, Verizon New York will begin to execute the test deck in production using training mode. Upon completion of the test, Verizon New York will report the number of test deck transactions that were rejected or otherwise failed during execution of the test. Each failed transaction will be multiplied by the transaction's weight factor.

A transaction is considered failed if the request cannot be submitted or processed, or results in incorrect or improperly formatted data.

This software validation metric is defined as the ratio of the sum of the weights of failed transactions in production using training mode to the sum of the weights of all transactions in the test deck.

Exclusions:

None.

Performance Standard:

Metric PO-6-01: ≤ 5 %

Sub-Metrics

PO-6-01	Software Validation		
Calculation	Numerator Denominator		
	Sum of weights of failed transactions.	Sum of weights of all transactions in the test deck.	

PO-7 Software Problem Resolution Timeliness

Definition:

This metric measures Software Problem Resolution Timeliness. Each month, Verizon tracks the number of rejected Pre-Order and Order transactions reported to the Help Desk, those rejected transactions resulting from the test deck execution, and the time frame to resolve the problem. For the purposes of this metric, rejected transactions caused by Verizon code or documentation errors or omissions that result in Type 1 changes are production referrals.

PO-7-01 is defined as the ratio of production referrals resolved within target response intervals to the total number of production referrals, during the 30 calendar days following a non-emergency software release.

Exclusions:

<u>Failed Pre-orders and Orders transactions reported to the Help Desk between received after</u> 6:00PM on Friday and before 9:00AM on Monday will be treated as though they were received at 9:00 AM Monday.

Performance Standard:

Metric PO-7-01: ≥ 95% according to schedule below:

Change type

Metrics PO-7-02 through 04: No standard.

Problem Resolution Timeliness Standard measured from time the trouble was reported to the Help Desk (see Appendix O).

Timeliness standard:

Shange type			rinicinicos standara.	
Orders rejected, with no workaround 48 hours				
Orders rejected, with workaround 10 days				
Sub-Metrics				
PO-7-01	% Software Problem Resolution Timeliness			
Calculation	Numerator	Denominator		
	Number of production referrals resolved within timeliness standard.	Total nu	mber production referrals.	
PO-7-02	Delay Hours – Software Resolution – Change – Transactions failed, no workaround			
Calculation	Data Value			
	Number of cumulative delay hours (beyond the 48-hour standard) for identified software resolution changes associated with order rejects with no workaround.			
PO-7-03	Delay Days – Software Resolution – Change – Transactions failed with workaround			
Calculation	Data Value			
	Number of cumulative delay days (beyond the 10-day standard) for identified softward resolution changes associated with order rejects with a workaround.			
PO-7-04	Delay Hours - Failed/Rejected Test Deck Transactions – Transactions failed, no workaround ⁴			
Calculation	Data	a Value		
Number of cumulative delay hours (beyond the 48-hour standard) for software changes associated with order rejects with no workaround for Test Deck Tran			· · · · · · · · · · · · · · · · · · ·	

Verizon 12/22/00 Compliance Filing VA Draft 4/30/01

⁴ This performance measure addresses the resolution timeliness for failed or rejected test deck transactions that are executed in production using training mode.

PO-8 Manual Loop Qualification

Definition:

The PO-8 Manual Loop Qualification metric measures the response time for the provision of Loop Qualification information required to provision more complex services (e.g. 2W-xDSL), when such information is not available through an electronic database.

Exclusions:

None. Weekend and Holiday Hours – Weekend Hours are from 5:00 pm Friday to 8:00 am Monday. Holiday Hours are from 5:00 pm of the business day preceding the holiday to 8:00 am of the first business day following the holiday. These hours are excluded from the elapsed time.

Performance Standard:

Metric PO-8-01: 95% within 48 Hours Metric PO-8-02: 95% within 72 Hours

Sub-Metrics

PO-8-01	Average Response Time / On-Time - Manual Loop Qualification			
Calculation	Numerator	Denominator		
	Count of manual loop qualification	Number of Manual Loop Qualification		
	requests where the time from receipt of	transactions.		
	requestSum of all response times from			
	receipt of request for Manual Loop			
	Qualification to distribution of Loop			
	Qualification information is less than or			
	equal to 48 hours.			
PO-8-02	Average Response Time			
Calculation	Numerator	Denominator		
	Count of Engineering Record Requests	Number of Engineering Record Request		
	where the timeSum of all response times	transactions.		
	from receipt of request for Engineering			
	Record Request to distribution of			
	Engineering Record is less than or equal			
	to 72 hours.			

Note:

Metric PO-8-01 is intended to measure the timeliness of provision of manual loop qualification information where such information is provided on a stand-alone basis separate from the LSR process. The metric will be implemented when Verizon Virginia, after completion of the applicable change management notice processes, begins to provide manual loop qualification information on a stand-alone basis separate from the LSR process.

Section 2

Ordering Performance

(OR)

	Function	Number of Sub-metrics
OR-1	Order Confirmation Timeliness	14
OR-2	Reject Timeliness	12
OR-3	Percent Rejects	2
OR-4	Timeliness of Completion Notification	12
OR-5	Percent Flow-Through	3
OR-6	Order Accuracy	3
OR-7	Order Confirmation/Rejects sent within	1
	three (3) business days	
OR-8	Acknowledgement Timeliness	1
OR-9	Order Acknowledgement Completeness	1

OR-1 Order Confirmation Timeliness

Definition:

This metric measures Order Confirmation Timeliness.

Resale and UNE:

Order Confirmation Response Time: The amount of elapsed time (in hours and minutes) between receipt of a valid order request (VZ Ordering Interface) (or fax date and time stamp) and distribution of a Service Order confirmation. Rejected orders will have the clock re-started upon receipt of a valid order. Partial migrations for less than six (6) lines – with accounts that include more than six (6) or more lines, that must be rearranged, will be treated as six (6) lines or greater.

Average Confirmation Response Time: The mean of all confirmation response times associated with a product group.

Percent of Orders Confirmed On Time: The percentage of orders confirmed within the agreed upon timeframes as specified in the Performance Standards.

Facility Checks – are completed on orders with more than five (5) lines.

Trunks:

The amount of time in business days between receipt of a clean Access Service Request (ASR) and distribution of a Firm Order Confirmation (FOC). Measures Service Orders completed between the measured dates. **Note:** The received date is restarted for each <u>SUPPsupplemental order</u>.

Inbound Augment Trunks: For CLECs e-mailing a Trunk Group Service Request (TGSR), VZ will respond with an ASR, or provide a negative response requesting additional data if it believes traffic does not support the request. Orders for inbound trunks that are for a new trunk group, are in excess of 192 trunks or that require T-3 construction, performance will be captured in the > 192 category.

Notes:

(1) Rejected Orders (orders that fail basic front-end edits) are not placed in the PON Master File.

- (2) Verizon-New York includes CLEC requests for resent confirmations that are submitted electronically as well as resent confirmations due to Verizon-New York's error in initial confirmation⁵ in the Order Confirmation Timeliness measurement. The measurements are based on confirmed orders. Cancelled orders are also included.
- (3) If no order confirmation time exists due to a missing order confirmation, Verizon-New York will use the completion notification time.
- (4) The Ordering sub-metrics data reported in the monthly C2C reports only include orders confirmed in the calendar month.
- (5) The Pre-Qualified Complex category includes 2Wire Digital, 2Wire xDSL Loop, and 2Wire xDSL Line Sharing orders that were pre-qualified.

⁵ Resent confirmations due to CLEC error – such as duplicate PON numbers, or confirmations resent to reschedule a missed provisioning appointment – either due to CLEC, End User or Verizon New York Virginia reasons are not counted as resent confirmations.

Exclusions:

Resale and UNE:

- VZ Test Orders ⁶
- Weekend and holiday hours (other than flow-through):
 - Weekend hours are from 5:00PM Friday to 8:00AM Monday.
 - Holiday hours are from 5:00PM of the business day preceding the holiday to 8:00AM of the first business day following the holiday. These hours are excluded from the elapsed time when calculating the response times for non-flow-through requests.
- For OR-1-19 Inbound Augment trunks not requested via e-mail TGSR
- For OR-1-01 and OR-1-02: SOP scheduled downtime hours (flow-through): SOACs-12 Midnight to 6
 AM, Monday through Friday, and 12 Midnight to 7 AM, Saturday and Sunday; ExpressTRAK-11 PM to 6 AM, Monday through Friday, and 11 PM to 7 AM, Saturday and Sunday.

New York - SOP scheduled hours are as follows:

Monday through Friday 12:30AM to 11:30PM Saturday 12:30AM to 7:30PM Sunday 7:30 AM to 11:30PM.

Exception: The 3rd Saturday of each month is a scheduled release. SOP will have a late start the following Sunday at 9:00AM. Additionally, SOP downtime may be extended for significant SOP releases, (e.g. NPA splits). All downtime extensions will be communicated to CLECs in advance of the release through VZ Change Management Guidelines.

_

⁶ VZ-Test Orders – see Glossary.

	•				
Report Dime	nsions				
Company:			Geography		
CLEC Aggre			• New Yo	ork <u>Virginia</u>	ļ
CLEC Speci		1010			
	Standard: OR				
Metrics OR-1-02	<u>2, 04, 06, 08, 10, 12</u>	2, 13, and 19:	_95% On Tin	ne accordi	ng to the schedule below:
Mark to a OD 4 or	4 00 05 07 00	. 1 4 4 1 1			
	<u>1, 03, 05, 07, 09, aı</u>		<u>ndard.</u>		Intercorporation Trumbo.
Resale:	Dudamaitta d	UNE:	Use Cook maisse	الم	Interconnection Trunks:
Electronically \$	Submitted	Electronical	ily Submitte	ea	Electronically Submitted
Orders: POTS/Pre-Qualit	fied Compley:	Orders: POTS/Pre-Q	ualified Com	nlov:	Orders: Firm Order Confirmation:
	orders: two (2) hours		uaimed Com ugh Orders: tw	•	
-	ofacility check: 24	hours	agii Oideis. W	70 (Z)	≤ 192 Trunks: 10 Business Days > 192 Trunks: Negotiated Process
hours			h no facility ch	eck: 24	 > 192 Trunks: Negotiated Process Design Layout Record
	acility check: 72	hours	•		
hours			h facility check		> 192 Trunks: Negotiated Process
Complex Service		Complex Ser			Inbound Augment Trunks:
Manual ILoop qC		Manual Loop			≤ 192 Trunks: 10 Business Days
Special Services	Services: 72 hours		ital Services: 7		> 192 Trunks: Negotiated Process
	o facility check : 48	2-Wire xDSL Loops: 72 hours2-Wire xDSL Line Sharing: 72 hours			The state of the s
hours	racility criccit : 40	3 11 1		y	Faxed/Mailed Orders: Add 24
 Orders with fa 	cility check: 72	Special Services:			hours to intervals above
hours ⁸	•	Orders with no facility check: 48		eck: 48	
Faxed/Mailed (Orders:	hours			
	<u>ured</u> available f or	Orders with facility check: 72 hours			
Resale		Faxed/Mailed Orders: Add 24			
		hours to intervals above. Not measured available for UNE POTS		measured	
Sub-Metrics		a ranable for biv	2.010		
OR-1-01	Average Local S	ervice Pegus	et Confirma	ation /I SE	RC) Time (Flow-Through) 9
Products	Resale:	ei vice neque	or Committe	UNE:	(C) Time (Flow-Tillough)
1 10000015		alified Compley	,	Loop/Pre-Qualified Complex/LNP	
	·				
Calculation	Numerator			Denominator	
	Sum of confirmation	of confirmation date and time minus		Total number of flow-through LSRs	
	order submission date and time for		for all		d for specified product.
	orders that flow-through to Service		ce Order		
Processor (SOP) (e.g. no manua					
	intervention required) for specified product.				
	•	•			

⁷ Excludes Verizon Advanced Data Incorporated

^{0&}lt;sup>8</sup> Also includes orders requiring facility verification as listed on the Verizon web-site documented in Appendix L (Product Interval Summary).

9 VZ will add complex and specials if this type of order is ever eligible for flow-through. However, manual

⁹ VZ will add complex and specials if this type of order is ever eligible for flow-through. However, manual intervention is currently required for both retail and wholesale services for loop qualification or design.

Sub-Metrics	OR-1 Order Confirmation Timelines	ss (continued)		
OR-1-02	% On Time LSRC – Flow-through			
Products	Resale: • POTS/Pre-qualified Complex	UNE:Loop/Pre-Qualified Complex/LNPPlatform		
Calculation	Numerator	Denominator		
	Number of electronic LSRCs sent where the confirmation date and time minus the submission date and time is less than two (2) hours for specified product.	Total number of flow-through LSRs confirmed for specified product.		
OR-1-03	Average LSRC/ASRC Time - No Facility (through)	Check (Electronic Submission – No Flow-		
Products	Resale: POTS/Pre-qualified Complex 2-Wire Digital Services Specials (Non DS0, DS1 & DS3) Specials DS0 Specials DS1 Specials DS3	UNE: Loop/Pre-Qualified Complex/LNP Platform 2-Wire Digital Services 2-Wire xDSL - Loops 2-Wire xDSL - Line Sharing Specials (Non DS0, DS1 & DS3) Specials DS0 Specials DS1 Specials DS3		
Calculation	Numerator	Denominator		
	Sum of confirmation date and time minus the order submission date and time for all electronically submitted LSRCs/ASRCs, not requiring a facility check, by product group.	Total number of electronically submitted LSRs/ASRs not requiring a facility check confirmed for specified product.		
OR-1-04	% On Time LSRC/ASRC - No Facility Che	ck (Electronic – No Flow-through)		
Products	Resale: POTS/Pre-qualified Complex 2-Wire Digital Services Specials (Non DS0, DS1 & DS3) Specials DS0 Specials DS1	UNE: Loop/Pre-Qualified Complex/LNP Platform 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing		
	Specials DS3	 Specials (Non DS0, DS1 & DS3) Specials DS0 Specials DS1 Specials DS3 		
Calculation	Specials DS3 Numerator	Specials DS0Specials DS1		

Sub-Metrics OR-1 Order Confirmation Timeliness (continued)				
OR-1-05	Average LSRC/ASRC Time - Facility Che	,		
Products	Resale: POTS/Pre-qualified Complex 2-Wire Digital Services Specials (Non DS0, DS1 & DS3) Specials DS0 Specials DS1 Specials DS1	UNE: Loop/Pre-Qualified Complex/LNP Platform 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials (Non DS0, DS1 & DS3) Specials DS0 Specials DS1 Specials DS3		
Calculation	Numerator	Denominator		
	Sum of confirmation date and time minus the order submission date and time for all electronically submitted orders, requiring a facility check, by product group.	Total number of electronically submitted LSRs/ASRs requiring a facility check, confirmed for specified product.		
OR-1-06	% On Time LSRC/ASRC - Facility Check	(Electronic – No Flow-through)		
Products	Resale: POTS/Pre-qualified Complex 2-Wire Digital Services Specials (Non DS0, DS1 & DS3) Specials DS0 Specials DS1 Specials DS3	UNE: Loop/Pre-Qualified Complex/LNP Platform 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials (Non DS0, DS1 & DS3) Specials DS0 Specials DS1 Specials DS3		
Calculation	Numerator	Denominator		
	Number of electronic LSRCs/ASRCs requiring a facility check, sent where confirmation date and time minus submission date and time is less than standard for specified product.	Total number of electronic LSRs/ASRs requiring a facility check, confirmed for specified product.		
OR-1-07	Average ASRC Time - No Facility Check	(Fax/Mail)		
Products	UNE:			
Calculation	Numerator	Denominator		
	Sum of confirmation date and time minus order submission date and time for all orders submitted by fax or mail, not requiring a facility check, by product group.	Total number of faxed or mailed ASRs not requiring a facility check confirmed for specified product.		

Sub-Metrics OR-1 Order Confirmation Timeliness (continued)			
OR-1-08	% On Time ASRC - No Facility Check (F.	` '	
Products	UNE:		
Calculation	Numerator	Denominator	
	Number of faxed or mailed ASRCs, not requiring a facility check, sent where the confirmation date and time minus the submission date and time is less than the standard for the specified product.	Total number of faxed or mailed ASRs, not requiring a facility check, confirmed for specified product.	
OR-1-09	Average ASRC Time - Facility Check (I	Fax/Mail)	
Products	UNE:		
Calculation	Numerator	Denominator	
	Sum of confirmation date and time minus the order submission date and time for all orders requiring a facility check submitted by fax or mail, by product group.	Total number of faxed or mailed ASRs requiring a facility check confirmed for specified product.	
OR-1-10	% On Time ASRC - Facility Check (Fax/I	Mail)	
Products	UNE:		
Calculation	Numerator	Denominator	
	Number of faxed or mailed ASRCs requiring a facility check sent where the confirmation date and time minus the submission date and time is less than the standard for the specified product.	Total number of faxed or mailed ASRs requiring a facility check confirmed for specified product.	
OR-1-11	Average Firm Order Confirmation (FOC)	Time	
Products	Trunks: CLEC Trunks (≤ 192 Forecasted Trunks) CLEC Trunks (> 192 and Unforecasted Trunks)		
Calculation	Numerator	Denominator	
	Sum of order confirmation date and time minus submission date and time for trunk orders.	Number of orders confirmed (faxed orders) with 192 or less trunks that are not designated projects.	

27

Sub-Metrics OR-1 Order Confirmation Timeliness (continued)				
OR-1-12	% On Time FOC			
Products	Trunks: CLEC Trunks (≤ 192 Forecasted Trunks) CLEC Trunks (> 192 and Unforecasted Trunks)			
Calculation	Numerator Denominator			
	Number of orders confirmed within 40 days.specified interval.	Number of orders confirmed-(faxed orders).		
OR-1-13	% On Time Design Layout Record (DLR)			
Products	Trunks: CLEC Trunks			
Calculation Numerator Denominator				
	Number of DLRs completed on or before DLRD date in TIRKS.	Number of DLRs completed.		
OR-1-14 through OR-1- 18	Metrics not in use in New York Virginia.			
OR-1-19	% On Time Response - Request for Inbound Augment Trunks			
Products	 VZ Trunks (≤ 192 Trunks) VZ Trunks (>192 Trunks) 			
Calculation	Numerator Denominator			
	Number of requests for Inbound Augment Trunks with responses sent within 40 daysspecified interval.	Number of requests for Inbound Augment Trunks requested on a TGSR received via e- mail.		

OR-2 Reject Timeliness

Definition:

This metric measures Reject Timeliness.

Reject Response Time: The amount of elapsed time (in hours and minutes) between receipt of an order request and distribution of a Service Order reject, both based on Ordering Interface System DCAS or Request ManagerEDI or Web GUI) or Fax date and time stamp.

Average Reject Response Time: The mean of all reject response times associated with a product group.

Percent of Orders Rejected On Time:

The percentage of orders rejected within the agreed-upon timeframes as specified in the Performance Standards.

Notes:

- (1) Rejected Orders (Orders failing basic front-end edits) are not placed in the PON Master File.
- (2) Measurements are based on rejected orders.
- (3) VZ-NY does not include cancelled orders in the measurements.
- (4) The Ordering sub-metrics data reported in the monthly C2C reports only include confirmed rejects in the calendar month.
- (5) The Pre-Qualified Complex category includes 2Wire Digital, 2Wire xDSL Loop, and 2Wire xDSL Line Sharing orders that were pre-qualified.

Exclusions:

- VZ Test Orders
- Duplicate Rejects Rejects issued against a unique PON (PON + Version Number + CLEC Id), identical and subsequent to the first reject.
- Weekend and Holiday Hours (other than flow-through):
 - Weekend Hours are from 5:00PM Friday to 8:00AM Monday.
 - Holiday Hours are from 5:00PM of the business day preceding the holiday to 8:00AM of the first business day following the holiday. These hours are excluded from the elapsed time when calculating the response times for non flow-through requests.
- For OR-2-01 and OR-2-02: SOP scheduled downtime hours (Flow-through). SOACs-12 Midnight to 6

 AM, Monday through Friday, and 12 Midnight to 7 AM, Saturday and Sunday; ExpressTRAK-11 PM to
 6 AM, Monday through Friday, and 11 PM to 7 AM, Saturday and Sunday.

New York SOP Scheduled hours are as follows:

Monday through Friday 12:30AM to 11:30PM Saturday 12:30AM to 7:30PM Sunday 7:30 AM to 11:30PM

Exception: The 3rd-Saturday of each month is a scheduled release. SOP will have a late start the following Sunday at 9:00AM. Additionally, SOP downtime may be extended for significant SOP releases, (e.g. NPA splits). All extensions will be communicated to CLECs in advance of the release through VZ Change Management Guidelines.

Report Dimensions :	
Company: CLEC Aggregate 10 CLEC Specific	Geography: New York Virginia

 $^{^{\}rm 10}$ Excludes Verizon Advanced Data Incorporated

Performance Standard – Re	eject Timeliness	
Metrics OR-2-02, 04, 06, 08, 10, a	nd 12: 95% On Time According to so	chedule below .
Metrics OR-2-01, 03, 05, 07, 09, a	nd 11: No standard.	
Resale:	UNE:	Interconnection Trunks:
Electronically Submitted	Electronically Submitted	Electronically Submitted
Orders:	Orders:	Orders:
POTS/Pre-Qualified Complex:	POTS/Pre-Qualified Complex:	
Flow-Through Orders: two (2) hours	Flow-Through Orders: two (2) hours	≤ 192 Trunks: 10 Business Days> 192 Trunks: Negotiated Process
Orders with no facility check: 24 hours	Orders with no facility check: 24 hours	Faxed/Mailed Orders: Add 24 hours to intervals above
 Orders with facility check: 72 hours Complex Services (2- Wire 	Orders with facility check: 72 hours Complex Services (requiring	
Digital Services ISDN) (requiring Manual Loop Qualification):	Manual Loop Qualification) : • 2Wire Digital Services 72 hours	
Orders: 72 hours	2Wire xDSL Loop: 72 hours	
Special Services: 11	2Wire xDSL Line Sharing: 72 hours	
 Orders with no facility check: 48 	Special Services: 12	
hours	Orders with no facility check: 48 hours	
Orders with facility check: 72 hours	 Orders with ≥ facility check: 72 	
Faxed/Mailed Orders:	hours	
Not <u>measured</u> available for Resale	Faxed/Mailed Orders: Add 24 hours to intervals above. Not measured	
Sub-Metrics – OR-2 Reject	hours to intervals above. Not <u>measured</u> available for UNE POTS	

Sub-Metrics – OR-2 Reject Timeliness		
OR-2-01	Average Local Service Request (LSR) Reject - Time (Flow-Through)	
Products	Resale: POTS/Pre-qualified Complex	UNE: Loop/Pre-Qualified Complex/LNP
Calculation	Numerator	Platform Denominator
	Sum of reject date and time minus order submission date and time for all orders that flow-through to SOP (e.g. no manual intervention required) for specified product.	Total number of flow-through LSRs rejected for specified product.
OR-2-02	% On Time LSR Reject (Flow-through)	
Products	Resale: • POTS/Pre-qualified Complex	UNE:Loop/Pre-Qualified Complex/LNPPlatform
Calculation	Numerator	Denominator
	Number of electronic rejects sent where the reject date and time minus the submission date and time is less than two (2) hours for specified product.	Total number of flow-through LSRs rejected for specified product.

Also includes orders requiring facility verification as listed on the Verizon web-site documented in Appendix L (Product Interval Summary)
 Also includes orders requiring facility verification as listed on the Verizon web-site documented in Appendix L

¹² Also includes orders requiring facility verification as listed on the Verizon web-site documented in Appendix L (Product Interval Summary)

Sub-Metrics	OR-2 Reject Timeliness (continued)
OR-2-03	Average LSR/ASR Reject Time - No Facil	ity Check (Electronic – No Flow-through)
Products	Resale: POTS/Pre-qualified Complex 2-Wire Digital Services Specials	UNE: Loop/Pre-Qualified Complex/LNP Platform 2- Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials
Calculation	Numerator	Denominator
	Sum of reject date and time minus the order submission date and time for all electronically submitted LSRs/ASRs, not requiring a facility check, that were rejected for specified product.	Total number of LSRs/ASRs electronically submitted not requiring a facility check rejected for specified product.
OR-2-04	% On Time LSR/ASR Reject - No Facility Check (Electronic – No Flow-through)	
Products	Resale: POTS/Pre-qualified Complex 2-Wire Digital Services Specials	UNE: Loop/Pre-Qualified Complex/LNP Platform 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials
Calculation	Numerator	Denominator
	Number of electronic rejects sent where the reject date and time minus the submission date and time is within the standard for orders not requiring a facility check for the specified product.	Total number of electronically submitted LSRs/ASRs, not requiring a facility check rejected for specified product.
OR-2-05	Average LSR/ASR Reject Time - Facility	
Products	Resale: POTS/Pre-qualified Complex 2-Wire Digital Services Specials	UNE: Loop/Pre-Qualified Complex/LNP Platform 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials
Calculation	Numerator	Denominator
	Sum of reject date and time minus order submission date and time for all electronically submitted LSRs/ASRs, requiring a facility check rejected for specified product.	Total number of LSRs/ASRs electronically submitted requiring a facility check rejected for specified product.

Sub-Metrics	OR-2 Reject Timeliness (continued	
OR-2-06	% On Time LSR/ASR Reject - Facility Ch	·
Products	Resale: POTS/Pre-qualified Complex 2-Wire Digital Services Specials	UNE: Loop/Pre-Qualified Complex/LNP Platform 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials
Calculation	Numerator	Denominator
	Number of electronic rejects sent where reject date and time minus the submission date and time is within the standard for orders requiring a facility check for the specified product.	Total number of LSRs/ASRs electronically submitted requiring a facility check rejected for specified product.
OR-2-07	Average Reject Time - No Facility Chec	k (Fax)
Products	UNE: • Specials	
Calculation	Numerator	Denominator
	Sum of reject date and time minus order submission date and time for all orders not requiring a facility check submitted by fax, by product group.	Total number of faxed rejects not requiring a facility check confirmed for specified product.
OR-2-08	% On Time Reject - No Facility Check (F	ax)
Products	UNE: • Specials	
Calculation	Numerator	Denominator
	Number of faxed rejects not requiring a facility check, sent where reject date and time minus submission date and time is less than standard for specified product.	Total number of faxed rejects not requiring a facility check confirmed for specified product.
OR-2-09	Average Reject Time - Facility Check (Fax)	
Products	UNE: Specials	
Calculation	Numerator	Denominator
	Sum of reject date and time minus order submission date and time for all orders requiring a facility check submitted by fax, by product group.	Total number of faxed rejects requiring a facility check rejected for specified product.
OR-2-10	% On Time Reject - Facility Check (Fax)	
Products	UNE: • Specials	
Calculation	Numerator	Denominator
	Number of faxed rejects requiring a facility check, sent where confirmationreject date and time minus submission date and time is less than standard for specified product.	Total number of faxed rejects requiring a facility check rejected for specified product.

Sub-Metrics OR-2 Reject Timeliness (continued)		
OR-2-11	Average Trunk ASR Reject Time	
Products	Trunks:	
	CLEC Trunks	
Calculation	Numerator	Denominator
	Sum of reject date minus submission date for rejected ASRs for trunk orders with	Number of rejected trunk orders for less than 192 trunks.
	less than 192 trunks.	
OR-2-12	% On Time Trunk ASR Reject	
Products	Trunks:	
	CLEC Trunks	
Calculation	Numerator	Denominator
	Number of rejected trunk orders that meet	Number of rejected trunk orders for less than
	reject trunk standard (10 days).	192 trunks.

OR-3 Percent Rejects

Definition:

This metric measures the percent of orders received (including supplements and re-submissions) by Verizon that are rejected or queried. Orders are rejected due to omission or error of required order information. Orders that are queried are considered rejected.

The percent reject measure is reported against all submitted order transactions processed in the Ordering Interface (DCAS or Request ManagerEDI, Web GUI), not just those with associated CRISbill completions.

Note: Edit Rejects (orders failing basic front-end edits) are not placed in the PON Master File.

Exclusions:

VZ Test Orders

Performance Standard:

Metric OR-3-01: No standard. Metric OR-3-02: _95%

Report Dimensions

Company:

Geography: CLEC Aggregate 13 New York Virginia

CLEC Specific

Sub-Metrics

OR-3-01	% Rejects	
Products	Resale	UNE
Calculation	Numerator	Denominator
	Sum of all rejected LSR/ASR transactions for specified product.	Total number of LSR/ASR records with unique PONs for specified product.
OR-3-02	% Resubmission Not Rejectioned	
Calculation	Numerator	Denominator
	Total PONs resubmitted at Verizon's request that are not rejected by Verizon's systems as duplicative of PONs already in Verizon's systems.	Total PONs resubmitted at Verizon's request

¹³ Excludes Verizon Advanced Data Incorporated

OR-4 Timeliness of Completion Notification

Definition:

This metric measures the timeliness of completion notification.

Resale and UNE:

Completion Notification Response Time:

The elapsed time between the actual order completion in the billing system or Service Order Processor (SOP) and the distribution of the order completion notification. If multiple orders were generated from a single CLEC/Reseller request, the measure is taken between the completion of the last order associated with the request and the distribution of the completion notification.

Completion notifications for Resale and UNE orders received via, EDI or WEB/GUI are delivered mechanically via the same interface.

Average Completion Notification Response Time For Resale and UNE:

The mean of all completion notification response times associated with a product group.

Percent On Time:

The percentage of completion notifications sent within the agreed upon timeframes as specified in the Performance Standards.

Note: Rejected Orders (orders failing basic front-end edits) are not placed in the PON Master File.

Exclusions:

Verizon Test Orders

Performance Standard:

Metrics OR-4-01 and 04: No standard.

Metrics OR-4-02 and 05, % On Time:

All products other than coordinated conversions and trunks: 95% by next business day at noon.

- Coordinated Conversions & Trunks: Acceptance at turn-up via CLEC-provided serial number.

Metrics OR-4-06, and OR-4- 07, and 08: Parity with Retail.

Metric OR-4-11: Not more than 5%. Metrics OR-4-12 and OR-4-14: 95%. Metrics OR-4-13 and OR-4-15: 99%.

Report Dimensions

Treport Differsions		
Company:	Geography:	
VZ Retail (where applicable)	New York Virginia	
CLEC Aggregate ¹⁴		
CLEC Specific		

¹⁴ Excludes Verizon Advanced Data Incorporated

Sub-Metrics Timeliness of Completion Notification				
OR-4-01	Completion Notice – Average Response			
Products	Resale	UNE		
Calculation	Numerator	Denominator		
	Sum of the notification date and time minus the CRIS bill completion date and time for specified product. (NOTFCTN-RESPONSE-TIME of ORDERING-MASTER-REC for specified product.)	Total number of completion notices for specified product.		
OR-4-02	Completion Notice – % On Time			
Products	Resale	UNE		
Calculation	Numerator	Denominator		
	Number of completion notices where the notice occurs aton or before noon the next business day after bill completion [records for specified product with ON-TIME-NOTFCTN of ORDERING-MASTER-RECORD = 'Y'].	Number of PONs for specified product with ON-TIME-NOTFCTN of ORDERING-MASTER-RECORD = 'Y' or 'N'.		
OR-4-03	Metric not in use in New York Virginia.			
OR-4-04	Work Completion Notice – Average Res	ponse Time		
Products	Resale	UNE		
Calculation	Numerator	Denominator		
	Sum of <u>SOP</u> notification date and time less SOP completion date and time for specified product.	Total number of SOP completion notices for specified product.		
OR-4-05	Work Completion Notice - % On Time			
Products	Resale	UNE		
Calculation	Numerator	Denominator		
	Number of SOP completion notices where notice occurs on or before noon the next business day after SOP completion for specified product.	Number of PONs for specified product with ON-TIME-NOTFCTN of ORDERING-MASTER-RECORD = 'Y' or 'N'.		
OR-4-06	Average Duration – Work Completion (S	Ī		
Products	Retail Resale	UNE		
Calculation	Numerator	Denominator		
	Sum of date and time for Bill completion less date and time for SOP completion.	Number of orders with SOP and Bill completions.		
OR-4-07	% SOP to Bill Completion >= five (5) Business Days			
Products	Retail Resale	UNE		
Calculation	Numerator	Denominator		
	Number of orders where date and time for Bill completion minus date and time for SOP completion is greater than or equal to five (5) business days.	Number of orders with SOP and Bill completions.		

Sub-Metrics Timeliness of Completion Notification, continued				
OR-4-08	% SOP to Bill Completion > one (1) But	siness Day		
Products	Retail Resale	UNE		
Calculation	Numerator	Denominator		
	Number of orders where date and time for Bill completion minus date and time for SOP completion is greater than one (1) business day.	Number of orders with SOP and Bill completions.		
OR-4-11	Resale	UNE		
through OR— 4-15 Products				
OR-4-09	Not included in NY Virginia C2C guide	lines		
OR-4-10	Metric not in use in NyVirginia			
OR-4-11	% Completed orders without either a P	CN or BCN		
Calculation	Numerator	Denominator		
	Total number of orders in the denominator for which neither a PCN nor a BCN exists with a time-stamp in DCASRequest Manager within three (3) business days of SOP completion.	report period.		
OR-4-12	% Due Date to PCN within two (2) Busin	ness Days		
Calculation	Numerator	Denominator		
	Number of PCNs sent within two (2) business days of due date.	Number of orders with due dates in the calendar month.		
OR-4-13	% Due Date to PCN within five (5) Busin	ness Days		
Calculation	Numerator	Denominator		
	Number of PCNs sent within five (5) business days of due date.	Number of orders with due dates in the calendar month.		
OR-4-14	% Due Date to BCN within four (4) Busi	ness Days		
Calculation	Numerator	Denominator		
Number of BCN sent within four (4) business days of due date. Number of orders with due of month.		1 111011111		
OR-4-15	% Due Date to BCN within seven (7) Business Days			
Calculation	Numerator	Denominator		
	Number of BCNs sent within seven (7) business days of due date.	Number of orders with due dates in calendar month.		

OR-5 Percent Flow-Through

Definition:

This metric measures the percent of valid orders received through the electronic ordering interface (DCAS or Request ManagerEDI, Web GUI) that processed directly to the legacy Service Order Processor system (SOP) without manual intervention. These Service Orders require no action by a VZ service representative to input an order into SOP. This is also known as Ordering flow-through.

Simple Flow-through: Percent of Basic POTS Services *(excluding Centrex)* that actually flow-through from DCASEDI or Web GUI to SOP.

% Flow-through Achieved: Percent of valid orders received through the electronic ordering interface (DCAS or Request ManagerEDI or Web GUI) that are designed to flow-through and actually flow-through, but excluding those orders that do not flow-through due to CLEC errors-or a pending order status.

Appendix H contains a summary of order types that flow-through for VZ and CLECs. Orders designed to flow-through may also fall-out for both VZ and CLECs. Non-flow-throughs include orders where there are other pending orders on the same line and those that require manual intervention to ensure that the correct action is taken.

Note: Rejected Orders (orders failing basic front-end edits) are not placed in the PON Master File.

Exclusions:

- VZ Test Orders
- Verizon Advanced Data Incorporated (VADI)

From Achieved Flow-through:

- Orders not eligible to flow-through
 - **Note:** Order types that are designed to flow-through are specified in the scenarios documented in Appendix H.
- Orders with CLEC input errors in violation of published business rules

Performance Standard:

Metrics OR-5-01 and 02: No standard developed for total flow-through or simple flow-through. Metric OR-5-03: 95% for % flow-through achieved

Report Dimensions

Company:	Geography:
CLEC Aggregate	New York Virginia

OR-5-01	% Flow-through – Total		
Products	Resale	UNE	
Calculation	Numerator	Denominator	
	Sum of all orders that flow-through (FLWTHRU-CAND-IND = '1') for specified product.	Total number of LSR/ASR records (orders) for specified product.	

Sub-Metrics – OR-5 % Flow-through (continued)			
OR-5-02	% Flow-through – Simple		
Products	Resale UNE		
Calculation	Numerator Denominator		
	Sum of all orders that flow-through for specified product minus CENTREX and Specials. Total number of LSR/ASR records (orders) specified product minus CENTREX and Specials.		
OR-5-03	% Flow-through Achieved		
Products	Resale UNE		
Calculation	Numerator Denominator		
	Number of <u>flow-through eligible</u> orders that flow-through for specified product.	Number of flow-through eligible orders.	

OR-6 Order Accuracy

Definition:

This metric measures the percent of orders completed as ordered by the CLEC. Two (2) dimensions are measured. The first is a measure of orders with error. The second measure is focused on the percent of fields populated correctly.

Methodology:

VZ uses a manual audit process of sampled orders. A statistically valid random sample of approximately 400 orders for Resale and 400 orders for UNE each month, (20 orders randomly sampled each business day for Resale and UNE respectively) are pulled from DCAS/Request Manager (for Order Accuracy). VZ compares required fields on the latest version of the LSR to the completed Verizon Service Order(s).

Exclusions:

- Orders entered by the CLEC that flow-through.
- Verizon Advanced Data Incorporated (VADI) Orders.

Performance Standard:

Metric OR-6-01: 95% orders without Verizon errors.

Metric OR-6-02: No standard.

Metric OR-6-03: Not more than 5% of LSRCs resent due to Verizon error.

Report Dimensions

Company: Geogra		Geography	hy:	
CLEC Aggr	regate • New Y		York Virginia	
Sub-Metrics				
Products	Resale		UNE:	
			 Loop/Complex/LNP 	
			Platform	
OR-6-01	% Accuracy - Orders			
Calculation	Numerator Number of orders sampled minus orders with Verizon errors for specified product.		Denominator	
			Number of orders sampled for specified product.	
OR-6-02	% Accuracy – Opportunities			
Calculation	Numerator		Denominator	
Number of fields sampled minus fields with Verizon errors for specified product		fiolds	Number of fields sampled for specified product.	
	· ·		·	
OR-6-03	· ·	oroduct.	·	
OR-6-03 Calculation	with Verizon errors for specified p	oroduct.	·	
	with <u>Verizon</u> errors for specified p % Accuracy – LSRC (Interim M	oroduct. leasure)	product.	
	with <u>Verizon</u> errors for specified p % Accuracy – LSRC (Interim M Numerator	oroduct. leasure)	product. Denominator	
	with <u>Verizon</u> errors for specified p **Accuracy - LSRC (Interim M Numerator Number of LSRCs sampled minu	es LSRCs	Denominator Number of LSRCs sampled.	
Calculation	with Verizon errors for specified p % Accuracy – LSRC (Interim M Numerator Number of LSRCs sampled minuwith errors for specified product.	es LSRCs	Denominator Number of LSRCs sampled.	

OR-7 % Order Confirmation/Rejects Sent Within Three (3) Business Days

Definition:

The percent of Resale, -and-UNE Platform, and UNE Loop LSRs confirmed or rejected by VZ within three (3) business days of receipt as a percent of total LSRs received.

Note: This is a measure of completeness not timeliness.

Source: Master PON File.

Exclusions:

- Cancelled orders.
- LSRs that were supplemented prior to confirmation or rejection.
- Edit Rejects (negative 99s) that are not eligible for confirmation or rejection.

Report Dimensions

Company:	Geography:
CLEC Aggregate— ¹⁵	New York Virginia
CLEC Specific	

Performance Standard

Metric OR-7-01: 95%.

Sub-inetrics				
OR-7-01	% Order Confirmations/Rejects Sent Within 3 Business Days			
Products	Resale UNE Platform			
	UNE Loop			
		Denominator		
Calculation	Numerator	Denominator		

¹⁵ Excludes Verizon Advanced Data Incorporated

OR-8 Acknowledgement Timeliness

Definition:

Percent of LSRs Acknowledged On Time: The percentage of LSR acknowledgements within the timeframe specified in the Performance Standard. Time starts with receipt of LSR and ends when an acknowledgement is sent. An electronic acknowledgement indicates that the file met basic edits with valid and complete data and will be processed by VZ. Applies to orders submitted via EDI.

Exclusions

- Orders submitted by Web GUI Interface.
- Orders not submitted electronically.

Report Dimensions

Company:

CLEC Aggregate 16

CLEC Specific

Geography:

New York Virginia

Performance Standard

Metric OR-8-01: 95% within two (2) hours.

OR-8-01	% Acknowledgements on Time		
Products	Resale UNE		
Calculation	Numerator	Denominator	
	Number of LSR acknowledgements sent within two (2) hours of LSR receipt.	Total number of LSR acknowledgements.	

¹⁶ Excludes Verizon Advanced Data Incorporated

OR-9 Order Acknowledgement Completeness

Definition:

This metric measures order acknowledgement completeness. The number of LSR acknowledgments sent the same day the LSR is received as a percent of total LSRs received. Orders with invalid or incomplete data are not acknowledged. Orders failing basic front-end edits are included in the denominator.

This metric applies to orders submitted via EDI. LSRs received after 10:00PM Eastern Time are considered received the next day.

Exclusions:

- Orders submitted by Web GUI Interface.
- Orders not submitted electronically.
- Orders in unreadable files.

Report Dimensions

Со	mpany:	Geog	raphy:
•	CLEC Aggregate ¹⁷	4 •	l ew York Virginia
•	CLEC Specific		

Performance Standard

Metric OR-9-01: 99%.

OR-9-01	% Acknowledgement Completeness		
Products	Resale UNE		
Calculation	Numerator	Denominator	
	Number of acknowledgements sent the same day the LSR was received.	Total number of LSRs received.	

¹⁷ Excludes Verizon Advanced Data Incorporated

Section 3

Provisioning Performance

(PR)

	Function	Number of Sub-metrics
		-
PR-1	Average Interval Offered	10
PR-2	Average Interval Completed	11
PR-3	Completed within Specified Number of Days (1-5 Lines)	11
PR-4	Missed Appointments	8
PR-5	Facility Missed Orders	3
PR-6	Installation Quality	3
PR-7	Jeopardy Reports	1
PR-8	Open Orders in a Hold Status	2
PR-9	Hot Cut Performance	3

PR-1 Average Interval Offered

Definition:

This metric measures the average interval offered for completed and cancelled orders. For **POTS and Specials**, the Average Interval Offered is also known as the Average Appointed Interval. The average number of business days between order application date and committed Dedue date (appointment date). The application date is the date that a valid service request is received. **Note:** Orders received after 5:00PM are counted as received the next business day.

Complex Orders include: 2-Wire Digital Services (ISDN) and 2-Wire xDSL Loops and line sharing.

Specials Orders include: All Designed circuits, 4-Wire circuits (including Primary rate ISDN and 4-Wire xDSL services), all DS0, DS1, and DS3 circuits. EEL and IOF are reported separately.

Trunks: The amount of time in business days between receipt of a clean ASR (received date restarted for each SUPPupplemental order) and Dddue date committed to from FOC. Measures service orders completed between the measured dates.

Notes:

- (1) The offered intervals for cancelled orders are counted in the month during which the cancellation occurs.
- (2) Sub-metrics reported according to line size groupings will be based on the total lines in the orders.

Exclusions:

- VZ Test Orders.
- Orders where customers request a due date (DD) that is beyond the standard available appointment interval. (X Appointment Code¹⁸).
- Verizon Administrative orders.
- Orders with invalid intervals (e.g. Negative intervals or intervals over 200 business days indicative of typographical error).
- Additional segments (pages or sections on individual orders) on orders (parts of a whole order are included in the whole).
- Retail-Suspend for non-payment and associated restore orders.
- Orders that have neither completed nor been cancelled.
- Orders requiring manual loop qualification.

Note: 2-wire xDSL orders that require manual loop qualification have an **R** populated in the **Required** field of the LR (indicating that a manual loop qualification is required).

 Disconnects are excluded from all sub-metrics except sub-metric PR-1-12 which measures disconnects.

Performance Standard:

Metrics PR-1-01 through 09 and PR-1-12 (except PR-1-01 and 02, UNE 2 Wire xDSL Loops): Parity with VZ Retail.

<u>Except for xDSL Loops and xDSL Line sharingMetrics PR-1-01 and 02, UNE 2 Wire xDSL Loops:</u> – No standard.

The published interval for one (1) to five (5) <u>2 Wire xDSL ILoops</u> is six (6) business days (pre-qualified). Refer to the Verizon web-site documented in Appendix L for the specific intervals offered for products and services.

¹⁸ Orders that are or should be X appointment coded. Effective 2/00, VZ will automate appointment coding when orders are received via LSOG4. CLECs that are not using LSOG4 are responsible to perform the X coding.

NY PSC Case 97-C-0139

Report Dimensions	
Company: VZ Retail VADI 19 CLEC Aggregate 20 CLEC Specific	Geography: — POTS and Complex: Manhattan, Greater Metro, Suburban and North-State NOVA, Central (Richmond), Eastern, Western • Specials & Trunks: New York State (LATA 132 and Remaining State – as identified) Virginia

¹⁹ Reported for DSL metrics only ²⁰ Excludes Verizon Advanced Data Incorporated

Sub-Metrics	– PR-1 Average Interva	al Offered			
PR-1-01	Average Interval Offered – Total No Dispatch				
Products	Retail/VADI: ²¹ • POTS: Residence • POTS: Business • 2-Wire Digital Services • 2-Wire xDSL Loops • 2-Wire xDSL - Line Sharing • Specials	Resale: POTS: Residence POTS: Business 2-Wire Digital Services Specials		UNE: POTS – Hot Cut Loop POTS – Platform POTS – Other (UNE Switch & INP) 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials	
Calculation	Numerator			Denominator	
	Sum of committed Dddue danglication date for orders we outside dispatch in product	ithout an	Number of orde in product group	rs without an outside dispatch os.	
PR-1-02	Average Interval Offered	- Total Dispat	ch		
Products	Retail/VADI: 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials	Resale: 2-Wire Digital Services Specials		UNE: 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials	
Calculation	Numerator			Denominator	
	Sum of committed Dddue danglication date for orders was dispatch in product groups.		Number of orde product groups.	rs with an outside dispatch in	
PR-1-03	Average Interval Offered -	- Dispatch one	e (1) to five (5) Li	ines	
Products	Retail: POTS: Residence POTS: Business	Resale: • POTS: Re • POTS: Bu		UNE:POTS – PlatformPOTS – Loop	
Calculation	Numerator			Denominator	
	Sum of committed Dddue date minus application date for POTS orders with an outside dispatch in product groups for orders with one (1) to five (5) lines.		Number of POTS orders with an outside dispatch in product groups for orders with one (1) to five (5) lines.		
PR-1-04	Average Interval Offered -	,	(6) to nine (9) Li	nes	
Products	Retail: Resale: POTS – Total POTS – Total			UNE: • POTS – Platform • POTS – Loop	
Calculation	Numerator			Denominator	
	Sum of committed Dddue date minus application date for POTS orders with an outside dispatch in product groups for orders with six (6) to nine (9) lines.		Number of POTS orders with an outside dispatch in product groups for orders with six (6) to nine (9) lines.		

²¹ "Retail/VADI" – see Glossary.

Sub-Metrics	– PR-1 Average Interv	al Offered (c	ontinued)		
PR-1-05	Average Interval Offered – Dispatch (3 10 Lines)				
Products	Retail: • POTS - Total	Resale: • POTS – T	otal	UNE:POTS – PlatformPOTS – Loop	
Calculation	Numerator		ı	Denominator	
	Sum of committed Dddue d application date for POTS o outside dispatch in product orders with 10 or more lines	rders with an groups for		S orders with an outside uct groups for orders with 10	
PR-1-06	Average Interval Offered	– DS0			
Products	Retail: • Specials	Resale: • Specials		UNE: • Specials	
Calculation	Numerator		1	Denominator	
	Sum of committed Dedue d application date for Special orders for DS0 services.		Number of Spec services.	cial Services orders for DS0	
PR-1-07	Average Interval Offered	– DS1	<u> </u>		
Products	Retail: • Specials	Resale: • Specials		UNE: • Specials	
Calculation	Numerator		Denominator		
	Sum of committed Dedue d application date for Special orders for DS1 services.		Number of Special Services orders for DS1 services.		
PR-1-08	Average Interval Offered	– DS3			
Products	Retail: • Specials	Resale: • Specials		UNE: • Specials	
Calculation	Numerator			Denominator	
	Sum of committed Dedue d application date for Special orders for DS3 services.		Number of Special Services orders for DS3 services.		
PR-1-09	Average Interval Offered	– Total			
Products	Retail: IXC FGD Trunks	UNE: IOF EEL – Bac EEL – Loc		CLEC Trunks: Interconnection Trunks (≤ 192 Trunks) CLEC Trunks (> 192 and Unforecasted Trunks)	
Calculation	Numerator		I	Denominator	
	Sum of committed Dddue d application date for product	group orders.	Number of orders for product group.		
PR-1-10 & 11	Metric not in use in NyVir	<u>gınia</u>			

Sub-Metrics – PR-1 Average Interval Offered (continued)				
PR-1-12	Average Interval Offered -	- Disconnects		
Products	Retail: POTS (including Complex) Specials	Resale: POTS (including Complex) Specials UNE: POTS (including Complex) Complex) Specials		
Calculation	Numerator		Denominator	
	Sum of committed DDdue date minus application date for product group disconnect (D & F) orders.		Number of orders	s for product group.

PR-2 Average Interval Completed

Definition:

This metric measures the average interval completed. The Average Interval completed for POTS and Specials is the average number of business days between order application date and actual work completion date. The application date is the date that a valid service request is received. **Note:** Orders received after 5:00PM are counted as received the next business day.

Coordinated Cut-over (Hot Cut) Loop orders are considered complete according to definition documented in the PR-9 Hot Cut metric section of this document.

DSL Loops are considered complete according to definition documented in the PR-4 metric section of this document.

Average Interval Completed Trunks: The Average Interval Completed for Trunks is the amount of time in business days between receipt of a clean ASR (received date restarted for each <u>SUPPsupplemental order</u>) and the date the order is completed and the customer is notified. Measures service orders **completed** between the measured dates.

Note:

(1) Sub-metrics reported according to line size groupings are based on the total lines in the orders.

Exclusions:

- VZ Test Orders
- Orders where customers request a DDdue date that is beyond the standard available appointment interval. (X Appointment Code).
- Verizon Administrative orders
- Orders with invalid intervals (e.g. Negative Intervals or intervals over 200 business days indicative of typographical error).
- Additional Segments on orders (parts of a whole order are included in the whole).
- Orders that are not complete. (Orders are included in the month they are completed).
- Suspend for non-payment and associated restore orders.
- Orders completed late due to any end-user or CLEC caused delay.
- Orders requiring manual loop qualification

Note: 2-wire xDSL orders that require manual loop qualification have an **R** populated in the **Required** field of the LR (indicating that a manual loop qualification is required).

- For 2 Wire Digital Services, 2 Wire xDSL Loops and 2 Wire xDSL Line Sharing, orders missed due to facility reasons.
- Trunks orders where the customer desired due dates are > 18 days.
- Disconnects are excluded from all sub-metrics except sub-metric PR-2-18, which measures
 disconnects.

Performance Standard:

Metrics PR-2-01 through 09 and PR-2-18 (except PR-2-01 and 02, UNE 2 Wire xDSL Loops): Parity with VZ Retail.

Except for Metrics PR-2-01 and 02, UNE 2 Wire xDSL Loops and xDSL Line sharing: - No standard.

The published interval for one (1) to five (5) <u>2 Wire xDSL ILoops</u> is six (6) business days (pre-qualified). Refer to the Verizon web-site documented in Appendix L for intervals on specific products and services.

Company:	Geography:
VZ Retail	 POTS and Complex: Manhattan, Greater Metro,
CLEC Aggregate	Suburban and North-State: NOVA, Central
CLEC Specific	(Richmond), Eastern, Western

NY PSC Case 97-C-0139

 Specials & Trunks: New York State (LATA 132 and Remaining State – as identified) Virginia

Sub-Metrics – PR-2 Average Interval Completed					
PR-2-01	Average Interval Completed – Total No Dispatch				
Products	Retail: POTS: Residence POTS: Business 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials	Resale: POTS: RePOTS: Burner: Potential Superior		UNE: POTS – Hot Cut Loop POTS – Platform POTS – Other (UNE Switch & INP) 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials	
Calculation	Numerator			Denominator	
	Sum of the completion date application date for orders woutside dispatch in product	ithout an	Number of orde in product group	rs without an outside dispatch os.	
PR-2-02	Average Interval Complet		spatch		
Products	Retail/VADI 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials	Resale: • 2-Wire Dig • Specials	gital Services	 UNE: 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials 	
Calculation	Numerator			Denominator	
	Sum of completion date mir application date for orders w dispatch in product groups.		Number of orders for orders with an outside dispatch in product groups.		
PR-2-03	Average Interval Complet	ed - Dispatch	one (1) to five (5) Lines	
Products	Retail: POTS: Residence POTS: Business	Resale: POTS: Re POTS: Bu		UNE:POTS – PlatformPOTS – Loop	
Calculation	Numerator			Denominator	
	Sum of completion date minus the application date for POTS orders with one (1) to five (5) lines with an outside dispatch in product groups.		Number of orders for POTS orders with one (1) to five (5) lines with an outside dispatch in product groups.		
PR-2-04	Average Interval Completed – Dispatch six (6) to nine (9) Lines				
Products	Retail: • POTS – Total	Resale: • POTS – T	otal	UNE: POTS – Platform POTS – Loop	
Calculation	Numerator			Denominator	
	application date for POTS o	of completion date minus the ation date for POTS orders with six nine (9) lines with an outside		Number of orders for POTS orders with six (6) to nine (9) lines with an outside dispatch in product groups.	

Sub-Metrics – PR-2 Average Interval Completed(continued)				
PR-2-05	Average Interval Complete		<u> </u>	
Products	Retail:	Resale:	Resale: UNE:	
	POTS – Total	 POTS – T 	otal	POTS – Platform
				POTS – Loop
Calculation	Numerator		I	Denominator
	Sum of completion date min			s for POTS orders with 10 or
	application date for POTS or			an outside dispatch in
	or more lines with an outside	e dispatch in	product groups.	
PR-2-06	product groups. Average Interval Complete	od D60		
Products	Retail:	Resale:		UNE:
Froducts	Specials	Specials		Specials
Calculation	Numerator	- Openiale		Denominator
Calculation		amplianting		
	Sum of completion date mine date for Special Services DS		orders.	rs for Special Services DS0
PR-2-07	Average Interval Complete		oruers.	
Products	Retail:	Resale:		UNE:
1 Todaoto	Specials	 Specials 		Specials
Calculation	Numerator	•		Denominator
	Sum of completion date mine	us application		rs for Special Services DS1
	date for Special Services DS		orders.	3 for opecial oct vices bot
PR-2-08	Average Interval Complete			
Products	Retail:	Resale:		UNE:
	Specials	 Specials 		Specials
Calculation	Numerator		ı	Denominator
	Sum of completion date mine	us application	Number of order	rs for Special Services DS3
	date for Special Services DS		orders.	•
PR-2-09	Average Interval Complete			
Products	Retail:	UNE:		CLEC Trunks:
	IXC FGD Trunks (≤	• IOF		Interconnection Trunks
	192 Trunks)	• EEL – Bac		(≤ 192 Trunks)
	IXC FGD Trunks (> 192 & Unforecasted	• EEL – Loc	рþ	CLEC Trunks (> 192 and Unforecasted
	Trunks)			Trunks)
Calculation	Numerator			Denominator
	Sum of completion date mine	us the	Number of order	s for orders within product
	application date for orders wi		groups.	o for oracle warm product
	groups.	•	3 1	
PR-2-10 to 17	Metrics not in use in NyVirginia			
PR-2-18	Average Interval Complete		cts	
Products	Retail:	Resale: UNE:		
	POTS (including	POTS (in	•	POTS (including
	Complex)	Complex)	Complex)
	Specials	Specials		Specials
Calculation	Numerator			Denominator
	Sum of due date minus the c	•		onnect orders for product
	date minus application date		group.	
	(D&F) orders within product group.			

PR-3 Completed within Specified Number of Days (1-5 Lines)

Definition:

This metric measures the percent of POTS-orders with five (5) or fewer lines completed in specified number (by metric) of business days, between application and work completion dates. The application date is the date (day zero (0)) that a valid service request is received. **Note:** Orders received after 5:00PM are counted as received the next business day.

Exclusions:

- VZ Test Orders.
- Disconnect Orders.
- Orders where customers request a DDdue date beyond the standard available appointment interval. (X
 Appointment Code).
- Verizon Administrative orders.
- Orders with invalid intervals (e.g. Negative Intervals or intervals over 200 business days indicative of typographical error).
- Additional Segments on orders (parts of a whole order are included in the whole).
- Orders that are not complete. (Orders are included in the month that they are complete).
- Suspend for non-payment and associated restore orders.
- Orders completed late due to any end-user or CLEC caused delay.
- Coordinated cut-over Unbundled Network Elements such as loops or number portability orders.
- Except for Metric PR-3-11, orders for 2 Wire Digital Services and 2 wWire xDSL orders Services that require a manual loop qualification.

Note: 2-wWire xDSL orders that require manual loop qualification have an **R** populated in the **Required** field of the LSR (indicating that a manual loop qualification is required).

 Orders for 2 Wire Digital Service, 2 Wire xDSL Loops and 2 Wire xDSL Line Sharing missed due to facility reasons.

Performance Standard:

Metrics PR-3-01 through 10 (except PR-3-03, UNE 2 Wire xDSL Line Sharing, and PR-3-10, UNE 2 Wire xDSL Loops): Parity with VZ Retail.

Metrics PR-3-03 and 11, UNE 2 Wire xDSL Line Sharing: Parity with VADI.

Metrics PR-3-10 and 11, UNE 2 Wire xDSL Loops: 95%.

Refer to the Verizon web-site documented in Appendix L for information on specific products and services. PR-3-10 (xDSL Loops) – 95%

PR-3-03 (xDSL Line sharing) Parity with VADI

Со	mpany:	Ge	ography:
•	VZ Retail	•	POTS: Manhattan, Greater Metro, Suburban and
•	CLEC Aggregate		North-State NOVA, Central (Richmond),
•	CLEC Specific		Eastern, Western

Sub-Metrics					
PR-3-01					
Products	Retail:	Resale: UNE:			
	POTS – Total	• POTS – T	otal	POTS – Platform & Other (UNE Switch & INP)	
Calculation	Numerator			Denominator	
	Number of No Dispatch POone (1) to five (5) lines wher date minus application date fewer days.	e completion is one (1) or	one (1) to five (5		
PR-3-02	% Completed in two (2) Da	ays one (1) to	five (5) Lines – N	lo Dispatch	
Products	Retail: • POTS – Total			UNE: POTS – Platform & Other (UNE Switch & INP)	
Calculation	Numerator		[Denominator	
	Number of No Dispatch POTS orders with one (1) to five (5) lines where completion date minus application date is two (2) or fewer days. Number of No Dispatch one (1) to five (5) lines.				
PR-3-03	% Completed in three (3) I	Days one (1) to	o five (5) Lines –	No Dispatch	
Products	Retail/VADI: POTS – Total Wire XDSL Line SSharing 22	Resale: • POTS – T	otal	 UNE: POTS – Platform & Other (UNE Switch & INP) 2 Wire XDSL Line \$\sum_{1}\$ haring \$\frac{23}{2}\$ 	
Calculation	Numerator			Denominator	
	Number of No Dispatch POone (1) to five (5) lines wher date minus application date fewer days.	e completion	Number of No D one (1) to five (5	ispatch POTS orders with) lines.	
PR-3-04	% Completed in one (1) Da	ay one (1) to f	ive (5) Lines – Di	spatch	
Products	Retail: • POTS – Total	Resale: • POTS – T	otal	UNE: • POTS – Platform & Other (UNE Switch & INP)	
Calculation	Numerator			Denominator	
	Number of Dispatch POTS of one (1) to five (5) lines wher date minus application date fewer days.	e completion	Number of Dispa (1) to five (5) line	atch POTS orders with one es.	

-

²² Line sharing intervals are 4 days until 02/28/01 and performance will be measured according to PR-3-07. As of the performance month 03/01/01, Verizon will report line sharing according to the 3 day standard in PR-3-03.

²³ Line sharing intervals are 4 days until 02/28/01 and performance will be measured according to PR-3-07. As of the performance month 03/01/01, Verizon will report line sharing according to the 3 day standard in PR-3-03.

Cub Matrica	DD 2 % Completed wit	thin Ensoific	d Number of	Days (1 Flines)
	PR-3 % Completed with	min Specifie	ea Number of	Days (1-5 Lines)
(continued) PR-3-05	0/ Completed in two (2) De	nua ena (4) ta	five (E) Lines - F	Nonetak
Products	Retail: POTS – Total	Resale: POTS – Total		UNE: POTS – Platform & Other (UNE Switch & INP)
Calculation	Numerator		ı	Denominator
	Number of Dispatch POTS one (1) to five (5) lines wher date minus application date fewer days.	e completion	Number of Dispa (1) to five (5) line	atch POTS orders with one es.
PR-3-06	% Completed in three (3) I	Days one (1) to	o five (5) Lines –	Dispatch
Products	Retail: • POTS – Total	Resale: • POTS – T	otal	UNE: • POTS – Platform & Other (UNE Switch & INP)
Calculation	Numerator		ı	Denominator
	Number of Dispatch POTS one (1) to five (5) lines wher date minus application date fewer days.	nere completion (1) to five (5) lines.		
PR-3-07	% Completed in four (4) D	ays one (1) to	five (5) Lines -	Total
Products	Retail/VADI: POTS – Total Wire xDSL line sharing 24	Resale: • POTS – Total		 UNE: POTS – Platform & Other (UNE Switch & INP) 2 Wire xDSL line sharing 25
Calculation	Numerator		ı	Denominator
	Number of POTS orders wit five (5) lines where completi application date is four (4) o	ith one (1) to Number of Dispatch POTS or tion date minus (1) to five (5) lines.		
PR-3-08	% Completed in five (5) da	ys one (1) to	five (5) Lines – N	No Dispatch
Products (also apply to PR-3-09)	Retail: • POTS – Total			POTS – Platform & Other (UNE Switch &
Calculation	Numerator	tor Denominator		Denominator
	Number of No Dispatch POone (1) to five (5) lines wher date minus application date fewer days.	e completion	Number of No Dispatch POTS orders with one (1) to five (5) lines.	

_

²⁴ Line sharing intervals are 4 days until 02/28/01 and performance will be measured according to PR-3-07. As of the performance month 03/01/01, Verizon will report line sharing according to the 3 day standard in PR-3-03.

²⁵ Line sharing intervals are 4 days until 02/28/01 and performance will be measured according to PR-3-07. As of the performance month 03/01/01, Verizon will report line sharing according to the 3 day standard in PR-3-03.

Sub-Metrics	Sub-Metrics PR-3 % Completed within Specified Number of Days (1-5 Lines)				
(continued)	,				
PR-3-09	% Completed in five (5) Da	ays one (1) to	five (5) Lines – Dis	spatch	
Calculation	Numerator		De	enominator	
			Number of Dispatch POTS orders with one (1) to five (5) lines.		
PR-3-10	% Completed in six (6) Da	ys one (1) to f	ive (5) Lines – Tot	al	
Products	Retail/VADI: POTS – Total ISDN (2 wire digital) 2 wire xDSL - Loops 2-Wire xDSL - Line Sharing	Resale: • POTS - Total • POTS - Platform & Other (UNE Switch INP) • 2-Wire Digital Serven & 2-Wire xDSL Loop • 2-Wire xDSL - Loop		 POTS – Platform & Other (UNE Switch & INP) 2-Wire Digital Services. 	
Calculation	Numerator		De	enominator	
	Number of orders (by specified product) with one (1) to five (5) lines where completion date minus application date is six (6) or fewer days.		Number of orders one (1) to five (5)	(by specified product) with lines.	
PR-3-11	% Completed in nine (9) D	ays one (1) to	five (5) Lines - To	otal ²⁶	
Products	Retail/VADI: • 2 wire xDSL Loops • 2-Wire xDSL - Line Sharing		UNE:2-Wire xDSL Loops2-Wire xDSL - Line Sharing		
Calculation	Numerator		Denominator		
	Number of orders (by specification with one (1) to five (5) lines of completion date minus application ine (9) or fewer days.	where	Number of orders one (1) to five (5)	(by specified product) with lines.	

_

 $^{^{\}rm 26}$ Interim performance measure. This metric will be removed upon completion of PO-8 metric.

PR-4 Missed Appointments

Definition:

This metric measures the Percent of Orders completed after the commitment date.

For LNP: The percent of orders completed on time (not early). **DSL Loops** are considered complete if completed on time on the due date. VZ utilizes serial numbers where CLECs provide them to support ontime performance measures. The use of a DDdue date-2 test or a CLECs 800 # has no impact in the determination of a completed DSL loop.

Trunks: Includes reciprocal trunks from VZ to CLEC. The percentage of trunks completed for which there was a missed appointment.

Exclusions:

- VZ Test Orders
- Disconnect Orders
- Verizon Administrative orders
- Additional Segments on orders (parts of a whole order are included in the whole)
- Orders that are not complete. (Orders are included in the month that they are completed)
- Suspend for non-payment and associated restore orders.
- LNP orders without office equipment which do not have a trigger order.
- For PR-4-04, and PR-4-14, 2 Wire Digital Services and 2 Wire xDSL Services, only exclude-orders missed for facility reasons.

Performance Standard:

Metrics PR-4-01, 02, 04, and 05 (except PR-4-04, UNE 2 Wire xDSL Loops): Parity with VZ Retail. Retail Comparison for UNE IOF is rRetail DS3 and for UNE EEL is rRetail DS1.

Retail Comparison for Metric PR-4-02, UNE 2 Wire xDSL Loops, is Retail Specials DS0.

Metric PR-4-07 LNP: 95% on Time

PR-4-02 xDSL Loop - parity with retail specials DS0

Metric PR-4-04, UNE 2 Wire xDSL Loops Dispatch xDSL: Not more than 5%.

Metric PR-4-14, UNE 2 Wire xDSL Loops-: 95% on Time.

Metrics PR-4-03 and 08: No standard. 27

Report Dimensions

respond Billionologic	
Company:	Geography:
VZ Retail	 POTS and Complex: Manhattan, Greater Metro,
CLEC Aggregate	Suburban and North-State NOVA, Central
CLEC Specific	(Richmond), Eastern, Western
	Specials & Trunks: New York State (LATA 132 and)
	Remaining State - as identified)Virginia

Verizon 12/22/00 Compliance Filing VA Draft 4/30/01

²⁷ % Missed Appointment Customer – No Standard – Not in Control of Verizon

Sub-Metrics					
PR-4-01	% Missed Appointmer	nt – Verizon – Total			
Description	The percent of orders/trunks completed after the commitment date, due to Verizon				
2000	reasons.				
Products		Resale:	UNE:	Trunks:	
	• DS0	• DS0	• EEL	CLEC Trunks	
	• DS1	• DS1	• IOF	00	
	• DS3	• DS3	• DS0		
	Specials Other	 Specials Other 	• DS1		
	IXC Feature	•	• DS3		
	Group D (FGD)		Specials Other		
	Trunks		·		
Calculation	Nume	rator	Denor	ninator	
	Number of Orders/Trunk	s where the Order	Number of orders/tru	nks completed for	
	completion date is great	ter than the order	product group.	·	
	Dddue date due to Veriz				
	product group.				
PR-4-02	Average Delay Days -	- Total			
Description	For orders/trunks misse	ed due to Verizon reas		nber of days between	
	committed Dddue date	and actual work comple	etion date.		
Products		Resale:	UNE:	Trunks:	
	• POTS	 POTS 	POTS	 CLEC Trunks 	
	2-Wire Digital	 2-Wire Digital 	 2-Wire Digital 		
	Services.	Services.	Services.		
	2-Wire xDSL	 Specials Total 	 2-Wire xDSL 		
	Loops		Loops		
	• 2-Wire xDSL -		• 2-Wire xDSL -		
	Line Sharing		Line Sharing		
	Specials – Total		 Specials Total 		
	• DS0		• EEL		
	• DS1		• IOF		
	• DS3				
	IXC FGD Trunks				
Calculation	Numei		Denominator		
	Sum of the completion of		Number of orders/tru		
	date for orders/trunks m		company reasons, by	y product group.	
	company reasons by pr	•			
PR-4-03	% Missed Appointmen				
Description	The percent of orders/tr user delay. (Refer to A			due to CLEC or end-	
Products	Retail/VADI:	Resale:	UNE:	Trunks:	
Fioducis	POTS	• POTS	POTS	CLEC Trunks	
	2-Wire Digital	• 2-Wire Digital	2-Wire Digital	• CLEO HUIKS	
	Services.	Services.	Services.		
	2-Wire xDSL	 Specials 	2-Wire xDSL		
	Loops	Opoolalo	Loops		
	• 2-Wire xDSL -		• 2-Wire xDSL -		
	Line Sharing		Line Sharing		
	-Specials		• EEL		
	• DS1		Specials		
	IXC FGD Trunks		op coldio		
Calculation	Nume	rator	Denor	ninator	
	itailie		55.101		

NY PSC Case 97-C-0139

Number of orders/trunks where the order	Number of orders/trunks completed for
completion date is greater than the order	product group.
DDdue date due to customer reasons for	
product group.	

Sub-Metrics	(continued) PR-4 Misso	ed Appointme	nts		
PR-4-04	% Missed Appointment – Verizon – Dispatch				
Description	The Percent of Dispatched Orders completed after the commitment date, due to Verizon				
	reasons.			,	
Products	Retail/VADI: POTS 2-Wire Digital Services. 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing	Resale: POTS 2-Wire Digital	l Services.	UNE: • Platform • Loop – New • Loop – Hot Cut • 2-Wire Digital Services. • 2-Wire xDSL Loops • 2-Wire xDSL - Line Sharing	
Calculation	Numerator			Denominator	
	Number of Dispatched Order order completion date is great order Deldue date due to Verproduct group.	ater than the	Number of Di for product gr	ispatched Orders completed oup.	
PR-4-05	% Missed Appointment - \	/erizon – No Disp	atch		
Description	The Percent of No-Dispatch reasons.	Orders completed	after the com	mitment date, due to Verizon	
Products	Retail/VADI: POTS 2-Wire Digital Services. 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing	Resale: POTS 2-Wire Digital	l Services.	 UNE: Platform Loop – Hot Cut POTS – Other 2 –Wire Digital Services 2-Wire xDSL - Line Sharing 	
Calculation	Numerator	•		Denominator	
	Number of No Dispatch Order Order completion date is green order Defined date due to Confor product group.	ater than the	Number of No for product gr	o Dispatch Orders Completed oup.	
PR-4-06	Metric Not in Use in New 1	/ork<u>Virginia</u>. Mea	asure moved	to PR-9 metrics.	
PR-4-07	% On Time Performance -				
Description Products	Percent of all LNP orders (including the associated retail disconnect orders) where trigger is in place before the frame Dedue date and disconnect is completed after, but on the Dedue date. For LNP only orders, the percent of LNP (retail disconnect) orders completed in translation on or after date and time on order. Reported in Aggregate. Orders disconnected early are considered not met.				
	UNE: • LNP				
Calculation	Numerator			Denominator	
	Number of LNP orders, where port trigger is completed one (1) day before frame due time (as scheduled on order) and retail disconnect is completed on or after committed time frame.		Number of LN	NP orders completed.	

Sub-Metrics (continued) PR-4 Missed Appointments					
PR-4-08	% Missed Appointment – Customer – Due to Late Order Confirmation				
Description	The percent of orders completed after the commitment date, due to CLEC or end-user delay, where the reason for customer delay is identified as a late order confirmation.				
Products	Resale: POTS 2-Wire Digital Services. Specials	e: UNE: OTS • Platform -Wire Digital Services. • Loop – Hot Cut			
Calculation	Numerator	Denominator			
	Number of orders where the order completion date is greater than the order Ddue date due to customer reasons (for late Order Confirmation [MAC = SC]) for product group	Number of orders completed for product group.			
PR-4-09 to 4- 13	Metric numbers not available in New York	Virginia.			
PR-4-14	% Completed On Time – 2-wWire xDSL_Lo	<u>ops</u>			
Description	% of 2-wWire x-DSL services Loops completed on time. Complete per VZ and CLEC. A 2Wire xDSL Loop order is considered completed on time if: For CLECs that provide serial numbers; the order is completed on the due date and a serial number is provided or: For CLECs that do <i>not</i> provide serial numbers; Verizon completed the service on the due date.				
Products	UNE • 2Wire xDSL services Loops				
Calculation	Numerator	Denominator			
	Number of all orders completed on or before the Dedue date.	Number of completed orders.			

PR-5 Facility Missed Orders

Definition:

This metric measures facility missed orders.

Facility Missed Orders: The Percent of Dispatched Orders completed after the commitment date, where the cause of the delay is lack of facilities.

Facility Missed Orders > 15 or 60 Days: The percent of Dispatched orders missed for lack of facilities where the completion date minus the appointment date is greater than 15 or 60 calendar days.

Facility Missed Orders/Trunks: The percentage of trunks completed after the commitment date, where the cause of the delay was due to lack of facilities.

Exclusions:

- VZ Test Orders
- Disconnect Orders
- Verizon Administrative orders
- Additional Segments on orders (parts of a whole order are included in the whole)
- Orders that are not complete. (Orders are included in the month that they are complete)
- Suspend for non-payment and associated restore orders.

Performance Standard:

Parity with VZ Retail.

Company:		Geography:	
•	VZ Retail	_	POTS and Complex: Manhattan, Greater Metro,
•	CLEC Aggregate		Suburban and North-State NOVA, Central
•	CLEC Specific		(Richmond), Eastern, Western
		Specials & Trunks: New York State (LATA 132)	
			Remaining State - as identified) Virginia

		Homanii	ig otato do idontino	a<u>y virgirila</u>			
Sub-Metrics							
PR-5-01	% Missed Appointment – Verizon – Facilities						
Description	· · · · · · · · · · · · · · · · · · ·	The percent of <u>Trunks/Dispatched Orders</u> completed after the commitment date, due to lack of Verizon facilities.					
Products	Retail/VADI: POTS Specials 2-Wire Digital Services. 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing IXC FGD Trunks	Resale: POTS Specials 2-Wire Digital Services.	UNE: Loop Platform Specials 2-Wire Digital Services. 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing if applicable to process)	Trunks: • CLEC Trunks			
Calculation	Nume	erator	Denoi	minator			
	Number of trunks/disparted order completion do order Dedue date due to recessor for product are	ate is greater than the to Verizon Facility	Number of trunks/discompleted for production				
	reasons for product gro	Jup.					

Sub-Metrics	(continued) Facility Missed Orders				
PR-5-02	% Orders Held for Facilities > 15 Days				
Description	The Percent of <u>Trunks/Dispatched Orders</u> completed more than 15 days after the commitment date, due to lack of Verizon facilities.				
Products	Retail/VADI: POTS 2-Wire Digital Services. 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials IXC FGD Trunks	UNE: • Loop • Platform • Specials • 2-Wire Digital Services. • 2-Wire xDSL Loops • 2-Wire xDSL - Line Sharing.			
Calculation	Numerator Number of trunks/dispatched orders where the completion date minus Dddue date is more than 15-or more days for Company Facility reasons for product group.	Number of trunks/dispatched orders completed for product group.			
PR-5-03	% Orders Held for Facilities > 60 Days	1			
Description	·	completed more than 60 days after the illities.			
Products	Retail/VADI: POTS Specials 2-Wire Digital Services. 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing IXC FGD Trunks	UNE: • Loop • Platform • 2-Wire Digital Services. • 2-Wire xDSL Loops • 2-Wire xDSL - Line Sharing • Specials			
Calculation	Numerator	Denominator			
	Number of trunks/dispatched orders where the completion date minus Dedue date is more than 60-or more days for Company Facility reasons for product group.	Number of trunks/dispatched orders completed for product group.			

PR-6 Installation Quality

Definition:

This metric measures the percent of lines/circuits/trunks installed where a reported trouble was found in the network within 30 days of order completion.

Note: For POTS services, the percent of lines/circuits/trunks installed where a reported trouble was found in the network within seven (7) days. This includes Disposition Codes 03 (Drop Wire), 04 (Cable) and 05 (Central Office). Disposition Code 05 includes translation troubles closed via STARMEMERVICE automatically by CLEC. Source: NORD

Exclusions:

- Subsequent reports (additional customer calls while the trouble is pending).
- Troubles closed due to customer action.
- Troubles reported by Verizon employees in the course of performing preventative maintenance, where no customer has reported a trouble.
- For Metric PR-6-01, 2 wire xDSL <u>Services</u> troubles reported by CLECs that do not participate in cooperative testing.

Formula:

Installation Troubles (within seven (7) or 30 days) with Disposition Codes 03, 04 and 05 divided by Lines completed multiplied by 100

Performance Standard:

<u>Metrics PR-6-01 and 02 (except PR-6-02, UNE POTS – Loop Hot Cut):</u> Parity with VZ Retail For Found Troubles (For PR-6-01, UNE 2 Wire xDSL Loops, the comparison is to Retail POTS-Dispatch.)

<u>Metric PR-6-02, UNEFor POTS – Loop</u> Hot Cut-<u>Loops</u> - % Installation Troubles Reported within seven (7) Days: _2%

Metric PR-6-03: No standard.

Company:		Geography:	
•	VZ Retail	_	POTS: Manhattan, Greater Metro, Suburban and
•	CLEC Aggregate		North-State NOVA, Central (Richmond), Eastern,
•	CLEC Specific		Western
		•	Specials & Trunks: New York State (LATA 132 and
			Remaining State - as identified) Virginia

	rice

PR-6-01	% Installation Troubles reported within 30 Days						
Description	The percent of lines/circuits/trunks installed where a reported trouble was found in Verizon's network within 30 days of order completion. Includes Disposition Codes 03						
	, , , ,) and 05 (Central Office).					
Products	Retail/VADI:	Resale:	UNE:	Trunks:			
	POTS	POTS	 POTS – Loop 	 CLEC Trunks 			
	 POTS-Dispatch 	 2 wire digital 	Platform				
	2 wire digital	services (ISDN)	 2-Wire Digital 				
	services (ISDN)		Loops.				
	 2-Wire xDSL 	 Specials 	 2-Wire xDSL 				
	Loops		Loops				
	• 2-Wire xDSL -		• 2-Wire xDSL -				
	Line Sharing		Line Sharing.				
	 Specials 		 Specials 				
	IXC FGD Trunks						

NY PSC Case 97-C-0139

Calculation	Numerator	Denominator
	Number of Central Office and outside plant loop (Disposition Codes 03, 04 and 05) troubles with installation activity within 30 days of trouble report.	Total Lines installed in calendar month.

Sub-Metrics	(continued) Installatio	n Quality			
PR-6-02	% Installation Troubles reported within seven (7) Days				
Description	The percent of lines/circuits/trunks installed where a reported trouble was found in the network within seven (7) days of order completion. Includes Disposition Codes 03 (Drop Wire), 04 (Cable) and 05 (Central Office).				
Products	Retail: • POTS	Resale: POTS POTS POTS – Loop - Total POTS – Loop Hot Cut POTS - Platform			
Calculation	Numerato	r	De	nominator	
	Number of Central Office an loop (Disposition Codes 03, troubles with installation act (7) days of trouble report.	04 and 05)	Total Lines install	led in calendar month.	
PR-6-03	% Installation Troubles reported within 30 Days – FOK/TOK/CPE				
Description	The percent of lines/circuits/trunks installed where a reported trouble was not found in the network within 30 days of order completion. Includes Disposition Codes 07, 08, and 09 (Found OK/Test OK) and Disposition Codes 12 and 13 (CPE).				
Products	Retail/VADI: Res	sale: POTS 2 wire Digital Services (ISDN) Specials	UNE: POTS – Loop POTS – Othe 2-Wire Digita Services. 2-Wire xDSL Loops 2-Wire xDSL Line Sharing Specials	er I	
Calculation	Numerato	r	Denominator		
	Number of Not Found, Test troubles with installation act days of trouble report.		Total Lines install	led in calendar month.	

PR-7 Jeopardy Reports

Definition:

This metric measures the percent of orders, completed or cancelled, identified with a jeopardy condition. CLECs are provided with jeopardy notices, unless they specifically agree or request, in writing, not to receive them. The jeopardy notifications are now available to all CLECs and Resellers in New York Virginia. These notices are posted twice daily for CLECs to retrieve on the WEB server. All CLECs and Resellers in New York Virginia currently have these posted.

Exclusions:

- VZ Test Orders
- Disconnect Orders
- Verizon Administrative orders
- Additional Segments on orders (parts of a whole order are included in the whole)
- · Orders that are not complete or cancelled.

Report Dimensions

ttoport 2 mionologic		
Company:	Geography:	
CLEC Aggregate	New York Virginia	
CLEC Specific		

Performance Standard:

Jeopardy Status Notification:

Timeliness of notice of jeopardy of Service Order request where a *miss* is known in advance of the due date (missed commitment with new date/time) ²⁸

- Resale and UNE:
- 100% at least 24 hours before due date with facilities
- 100% at least 48 hours before due date without facilities
- Interconnection Trunks: Two (2) days prior to due date.

% Orders with Jeopardy status: Assessed in conjunction with missed appointments.

Sub-Metrics (continued) Installation Quality				
PR-7-01	% Orders with Jeopardy Status			
Products	UNE:			
	• EEL			
Calculation	Numerator	Denominator		
	Number of EEL orders with jeopardy status.	Total EEL orders completed or cancelled.		

²⁸ To the extent that VZ has knowledge of a jeopardy condition, notice will be given as soon as it is known on or before committed due date.

PR-8 Open Orders in a Hold Status

Definition:

This metric measures the number of open orders that at the close of the reporting period have been in a hold status for more than 30 or 90 calendar days, as a percentage of orders completed in the reporting period.

An **open order** is a valid order that has not been completed or cancelled. Open orders in a hold status include:

- 1. open orders that have passed the originally committed completion date due to VZ reasons; and,
- 2. open orders that have not been assigned a completion date due to VZ reasons.

Measurement of the 30 and 90 day intervals for open orders that have passed the originally committed completion date due to VZ reasons will commence with such passed originally committed completion date (passed originally committed completion date = Day 0). Measurement of the 30 and 90 day intervals for open orders that have not been assigned a completion date due to VZ reasons will commence with the application date (application date = Day 0).

Exclusions:

- VZ Test Orders.
- Disconnect Orders.
- Verizon Administrative orders.
- Additional segments on orders (parts of a whole order are included in the whole).
- Orders that are complete or cancelled.
- Suspend for non-payment and associated restore orders.
- Orders that have passed the committed completion date, or whose completion has been delayed, due to CLEC or end user delay. (including VZ requests for cancellation)
- Orders that at the request of the CLEC or VZ Retail customer have not been assigned a completion date.

Performance Standard:

Parity with VZ Retail.

For UNE 2W xDSL Loops, the rRetail compare is Specials DS0.

Report Dimensions				
Company • VZ Retail	Geography:			
VZ RetailCLEC Aggregate	 POTS: Manhattan, Greater Metro, Suburban and North-State NOVA, Central (Richmond), Eastern, 			
CLEC Specific	 Western Specials & Trunks: New York State (LATA 132) 			
	and Remaining State – as identified) Virginia			

Sub-Metrics				
PR-8-01	Open Orders in a Hold Status > 30 Days			
Products	Retail/ VADI: POTS 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials DS0 Specials IXC FGD Trunks	Resale: POTS 2-Wire Digital Services Specials	UNE: POTS 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials EEL IOF	Trunks: • CLEC Trunks
Calculation	Numerator		Denominator	
PR-8-02	Number of open orders that at the close of the reporting period have been in a hold status for more than 30 days. Open Orders in a Hold Status > 90 Days		Total number of orders completed in the reporting period.	
Products	Retail:	Resale:	UNE:	Trunks:
	POTS 2-Wire Digital Services 2-Wire xDSL Loops Specials DS0 2-Wire xDSL - Line Sharing Specials IXC FGD Trunks	 POTS 2-Wire Digital Services Specials 	 POTS 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing Specials EEL IOF 	CLEC Trunks
Calculation	Nume	erator	Denor	minator
	Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days.		Total number of orders completed in the reporting period.	

PR-9 Hot Cut Loops

Methodology:

This metric measures the percent on-time performance for UNE Hot Cut Loops.

A Hot Cut is considered **complete** when the following situation occurs:

Work is done at the appointed Frame Due Time (FDT) as noted on the LSRC or the work is done at a time mutually agreed upon by the RCCC/CLEC. The time is either within a prescribed interval as noted in the C2C guidelines, or it is a mutually accepted interval agreed upon by Verizon and the CLEC (e.g. project completes by a certain date).

Note: If Verizon re-institutes the acceptance testing process, the percent on time measure will include the time it takes to complete acceptance testing.

A Hot Cut is considered **missed** when one of the following occurs:

- 1. Premature disconnect called in to 1-877-HotCuts (otherwise the disconnect would be captured as a Retail trouble).
- 2. Work was not done (e.g. work was not turned up to CLEC by some means (e-mail, VMS, direct phone call)) by close of intervals noted under Met Hot Cuts definition due to a Verizon reason (e.g. HFC, late turn-up, due date pushed out due to Verizon action).

Exclusions:

- VZ Test Orders
- Verizon Administrative orders
- Additional segments on orders (parts of a whole order are included in the whole)
- Orders that are not complete. (Orders are included in the month that they are complete)
- If a CLEC cancels an order before the start of a Hot Cut window and VZ performs the Hot Cut, this VZ error will result in a retail trouble report and need not be reflected elsewhere.

From PR-9-09 % Supplemented or Cancelled Orders at Verizon-New York request:

- Hot Cuts where no CLEC dial tone was found on Dddue date-2 test and the CLEC was notified of problem
- Hot Cuts where CLEC dial tone was found on DDdue date-2 test and not present on the DDdue date.

Performance Standard:

Hot Cuts:

PR-9-01: 95% completed within window

PR-9-028 through PR-9-10and 09: No Standard established

Standard for Cut-Over Window: Amount of time from start to completion of physical cut-over of lines:

one (1) to nine (9) lines: one (1) Hour

10 to 49 lines: two (2) Hours 50 to 99 lines: three (3) Hours 100 to 199 lines: four (4) Hours 200 plus lines: eight (8) Hours

If IDLC is involved – Four (4) hour window (8:00AM to 12:00PM (Noon) or 1:00PM to 5:00PM)²⁹. Four (4) hour window applies to start time.

Company:	Geography:
CLEC Aggregate	POTS: Manhattan, Greater Metro, Suburban and
CLEC Specific	North-State NOVA, Central (Richmond), Eastern,

²⁹ Only applicable if Verizon New York Virginia notified CLEC by 2:30PM Eastern Time on DD-2 that the service was on IDLC

NY PSC Case 97-C-0139

Wester

Sub-Metrics	- Hot Cut Loops			
PR-9-01	% On Time Performance – Hot Cut			
Description	Percent of all UNE Loop orders completed within the cut-over window. Start time specified on LSR. For UNE Loops, includes both Loop only and Loop & Number Portability. Orders disconnected early are considered not met. Note: Also includes lines on orders cancelled by CLEC during or after a Defective Cut.			
Products	UNE:			
	 Loop – Hot Cut (Coordinated Cut-over) 			
Calculation	Numerator Denominator			
	Number of Hot Cut (coordinated loop) orders (with or without number portability) completed within commitment window (as scheduled on order) on DDdue date.	Number of Hot Cut (coordinated loop orders) completed.		
Description	Percent of all UNE Loop orders completed within the cut-over window. Start time specified on LSR. For UNE Loops, includes both Loop only and Loop & Number Portability. Orders disconnected early are considered not met. Note: Also includes lines on orders cancelled by CLEC during or after a Defective Cut.			
PR-9-02 through PR-9- 07	Metrics not in use in New York Virginia.			

Sub-Metrics	Sub-Metrics – Hot Cut Loops (Continued)				
PR-9-08	Average Duration of Service Interruption				
Description	The average repair time (Mean Time to Repair - MTTR) for troubles called in to the 1-877-HotCuts line (Installation troubles)				
Calculation	Numerator	Denominator			
	The sum of the trouble clear date and time minus the trouble receipt date and time for Central Office and Loop troubles (disposition codes 03, 04, and 05 (Specials excludes stop time)) for Hot_Cut Installation troubles reported within seven (7) days.	Number of Central Office and Loop troubles (disposition codes 03, 04, and 05) for Hot_Cut Installation troubles reported within seven (7) days.			
PR-9-09	% Supplemented or Cancelled Orders at V	erizon New York Request			
Description	Percent of orders supplemented or cancelled by CLEC at the request of Verizon-New York as a percent of total Hot Cut orders.				
Calculation	Numerator Denominator				
	Number of Hot Cuts cancelled or supplemented at VZ Request.	Number of Hot Cut orders completed plus cancelled orders.			

Maintenance & Repair Performance

(MR)

	Function	Number of Sub-metrics
MR-1	Posnonco Timo OSS Maintonanco Interfaco	6
	Response Time OSS Maintenance Interface	6
MR-2	Trouble Report Rate	5
MR-3	Missed Repair Appointments	5
MR-4	Trouble Duration Intervals	10
MR-5	Repeat Trouble Reports	1

MR-1 Response Time OSS Maintenance Interface

Definition:

This metric measures the response time defined as the time, in seconds, that elapses from issuance of a query request to receipt of a response by the requesting carrier. For CLECs this performance is measured at the access platform.

Verizon uses two databases to collect maintenance performance data. Coding specified in this section is largely POTS services. Special Services and Trunks coding descriptions are included in the Appendix A.

Exclusions:

• CLEC Create Transactions – complex create trouble transactions not available to retail.

Methodology:

8:00AM to 5:00PM. (earlier version Monday through Friday now expanded to seven (7) days, no holiday exclusions)

For VZ retail representatives: Retail performance is reported directly from Caseworker R2.

For CLEC representatives: Actual response times reported by RETAS. For Create Trouble includes basic create function.

Performance Standard:

Parity with Retail plus not more than four (4) seconds. Four (4)-second difference allows for variations in functionality.

Report Dimensions

Roport Billio		
Company: VZ Retail		Geography:
 VZ Retail 		New York <u>Virginia</u> ³⁰
 CLEC Aggree 	egate	
Products	Retail	• CLEC

Sub-Metrics				
MR-1-01	Average Response Time – Create Trouble			
Calculation	Numerator Denominator			
	Sum of all response times from <i>Enter</i> key to reply on screen for Create Trouble transactions.	Number of Create Trouble transactions.		

77

Initially, performance will be reported for Virginia, Maryland, the District of Columbia, and West Virginia, combined. Caseworker R2 does not have the ability to identify transactions by state. Plans are underway to replace Casework R2 with CAD (Control Access Desktop), which will be able to identify transactions by state. Implementation of CAD is expected to begin by the end of 2001.

Sub-Metrics (continued) MR-1 Response Time OSS Maintenance Interface					
MR-1-02 Average Response Time – Status Trouble					
Calculation	Numerator	Denominator			
	Sum of all response times from <i>Enter</i> key to reply on screen for Status Trouble transactions.	Number of Status Trouble transactions.			
MR-1-03	Average Response Time – Modify Trouble				
Calculation	Numerator	Denominator			
	Sum of all response times from <i>Enter</i> key to reply on screen for Modify Trouble transactions	Number of Modify Trouble transactions.			
MR-1-04	Average Response Time – Request Cancel	lation of Trouble			
Calculation	Numerator	Denominator			
	Sum of all response times from <i>Enter</i> key to reply on screen for Request for Cancellation of Trouble transactions.	Number of Request for Cancellation of Trouble transactions.			
MR-1-05	Average Response Time –Trouble Report F	listory (by TN/Circuit)			
Calculation	Numerator	Denominator			
	Sum of all response times from <i>Enter</i> key to reply on screen for Trouble Report History transactions.	Number of Trouble History transactions.			
MR-1-06	Average Response Time – Test Trouble (Po	OTS Only)			
Calculation	Numerator	Denominator			
	Sum of all response times from <i>Enter</i> key to reply on screen for Trouble Test transactions.	Number of Trouble Test transactions.			

MR-2 Trouble Report Rate

Definition:

This metric measures the total initial customer direct or referred troubles reported, where the trouble disposition was found to be in the network, per 100 lines/circuits/trunks in service. Loop equals Drop Wire plus Outside Plant Loop. Network Trouble means a trouble with a Disposition Codes of 03 (Drop-wire), 04 (Outside Plant Loop), or 05 (Central Office).

UNE Loop is defined as 2-wire analog loop.

Subsequent Reports: Additional customer trouble calls while an existing trouble report is pending – typically for status or to change or update information.

The Disposition Codes set forth in the CLEC Handbook, Section 8.8 are included in Appendix G.

Exclusions:

- Report rate excludes subsequent reports (additional customer calls while the trouble is pending)
- Troubles reported on VZ official (administrative lines)
- Troubles closed due to customer action.
- Troubles reported by Verizon employees in the course of performing preventative maintenance, where no customer has reported a trouble

Excluded from Total and Loop/CO report rates:

- Customer Premises Equipment (CPE) troubles
- Troubles reported but not found (Found OK and Test OK).

Excluded from MR-2-02 and MR-2-03 for 2 wWire xDSL Loops and Line sSharing: Installation troubles

Performance Standard:

Metrics MR-2-01, 02, and 03, Report Rate:

Parity with VZ Retail.

Trunk Retail Equivalent = IXC FGD. Parity should be assessed in conjunction with MTTR

Metric MR-2-04, % Subsequent Reports:

No standard. Parity to be assessed in conjunction with missed appointments.

<u>Metric MR-2-05,</u> % CPE/TOK/FOK Reports: (Customer Premises Equipment, Test OK, Found OK):
<u>No standard.</u> To be used for root cause analysis. For CLEC troubles a not found trouble is coded as CPE.

Report Dimensions

Co	mpany:	Geography:	
•	VZ Retail	 POTS and Complex: Manhattan, Greater Metro, 	
•	CLEC Aggregate		Suburban and North-State NOVA, Central
•	CLEC Specific		(Richmond), Eastern, Western
		•	Specials & Trunks: New York State (LATA 132 and
			Remaining State - as identified)Virginia

MR-2-01	Network Trouble Report Rate				
Products	Retail:	Resale: • Specials	UNE: • Specials	Trunks: CLEC Trunks	
Calculation	Numerator		Denominator		
POTS:	Number of all trouble reports with found network troubles (trbl_cd is FAC or CO).		Number of Lines or specials or trunks in service.		

Sub-Metrics – MR-2 Network Trouble Report Rate (continued)						
MR-2-02	<u> </u>					
Products	Retail/ VADI:	Resale:		UNE:		
Froducts	 POTS 2 wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing 	 POTS 2 wire Digital Services (ISDN) 		 Platform Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL - Line Sharing 		
Calculation	Numerator	T		Denominator		
	Number of all loop trouble re (Disposition Codes of 03 and		Number of L	ines in service.		
MR-2-03	Network Trouble Report R	Rate - Central Offi	ice			
Products	Retail/ VADI: POTS 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing	Resale: POTS 2 wire Digital services (ISDN)		 UNE: Platform Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line Sharing 		
Calculation	Numerator			Denominator		
	Number of all Central Office (Disposition Code of 05).	trouble reports	Number of L	umber of Lines in service.		
MR-2-04	% Subsequent Reports					
Description	report is pending. Subseq change information.	uents are typically		eived while an existing trouble iries or customer's calling to		
Products	Retail/ VADI: POTS Variety Digital Services (ISDN) 2-Wire xDSL Loops C-Wire xDSL Line Sharing	Resale: POTS Platform Loop (ISDN) 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line Sharing		 Platform Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line 		
Calculation	Numerato	r		Denominator		
	Number of subsequent repo administrative repeaters for Codes, 03, 04 and 05).			otal Disposition Codes 03, 04, oles reported (Per MR-2-01).		

Sub-Metrics – MR-2 Network Trouble Report Rate (continued)					
MR-2-05	% CPE/TOK/FOK Trouble I	Report Rate			
Description	Troubles closed to CPE, Fou	und OK and Test C	K as a perce	nt of lines in service.	
Products	Retail/VADI: POTS 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing Specials	Resale: POTS 2 Wire Digital (ISDN) Specials	Services	UNE: Platform Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line Sharing Specials	
Calculation	Numerator			Denominator	
	Number of all CPE (Dispositi 12/13), Test OK, and Found (Disposition Codes 07, 08, a	OK troubles	Number of li	nes in service.	

MR-3 Missed Repair Appointments

Definition:

This metric measures the percent of reported Network Troubles not repaired and cleared by the date and time committed. Also referred to as percent of customer troubles not resolved within estimate. Appointment intervals vary with force availability in the POTS environment. Includes Disposition Codes 03 (Drop Wire), 04 (Cable) and 05 (Central Office).

Loop is defined as Disposition Codes 03 plus 04. These troubles are always dispatched.

Double Dispatch: A trouble that has more than one dispatch before closure. May include more than one outside dispatch or dispatches inside and outside.

Exclusions:

- Missed appointments where the CLEC or end-user causes the missed appointment or required access was not available during appointment interval
- Excludes subsequent reports (additional customer calls while the trouble is pending)
- *Customer Premises Equipment (CPE) troubles
- *Troubles reported but not found (Found OK (FOK) and Test OK (TOK)).
- Troubles closed due to customer action.
- Troubles reported by Verizon employees in the course of performing preventative maintenance, where no customer reported a trouble.

Note: The following *No Access Rule* applies to MR-3 *Missed Repair Appointments* sub-metrics: Exclude records where Verizon dispatches a technician prior to the appointment date, and encounters a *No Access* situation.

* The CPE and FOK/TOK exclusions do not apply to sub-metric MR-3-03.

Performance Standard:

<u>Metrics</u> MR-3-01 and MR-3-02 – Parity with VZ Retail. UNE Loop measurement is compared to Retail Business and Residence combined.

Metrics MR-3-03, 04, and 05: No standard.

Report Dimensions

Со	mpany:	Geography:	
•	VZ Retail	 POTS and Complex: Manhattan, Greater Metro, 	
•	CLEC Aggregate	Suburban and North-State NOVA, Central	
•	CLEC Specific	(Richmond), Eastern, Western	

MR-3-01	% Missed Repair Appointment – Loop					
Products	Retail/ VADI: POTSBusiness POTS - Residence POTS-Total 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing	Resale: POTS - Busi POTS – Resi 2 Wire Digital (ISDN)	idence	 UNE: Platform Business Platform Residence Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line Sharing 		
Calculation	Numerato	r		Denominator		

NY PSC Case 97-C-0139

Number of Loop troubles where clear time is	Number of Loop troubles (Disposition
greater than commitment time (missed	Codes 03 and 04).
appointments for (M=X) for Disposition Codes	
0300-0499).	

Sub-Metrics	- Missed Repair Appo	intment (Conti	nued)		
MR-3-02	% Missed Repair Appointment – Central Office				
Products	Retail/VADI: POTS - Business POTS- Residence POTS-Total 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing	Resale: POTS- Business POTS- Residence Wire Digital Services (ISDN)		UNE: Platform Business Platform Residence Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line Sharing	
Calculation	Numerator	r		Denominator	
	Number of Central Office tro time is greater than commits (missed appointments (M=X Code 05).	ment time (Disposition		Central Office Troubles n Code 05).	
MR-3-03	% CPE/TOK/FOK - Missed	I Appointment	I		
Products	Retail/ VADI: POTS 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing	Resale: POTS 2 Wire Digital (ISDN)	Services	UNE: • Platform • Loop • 2-Wire Digital Services • 2-Wire xDSL Loops • 2-Wire xDSL Line Sharing	
Calculation	Numerator	r		Denominator	
	Number of CPE, FOK and T where clear time is greater time for (M=X) Disposition C 12, and 13).	han appointment		CPE, FOK and TOK troubles Codes 07,08, 09, 12, and 13).	
MR-3-04	% Missed Repair Appointr	ment – No Double	Dispatch		
Products	Retail/ VADI: POTS 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing	Resale: POTS 2 Wire Digital (ISDN)	Services	 UNE: POTS – Platform POTS – Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line Sharing 	
Calculation	Numerator	r		Denominator	
	Number of network troubles where clear time is greater than commitment time (missed appointments for (M=X) for Disposition Codes 0300-0599) for troubles with a single dispatch.			network troubles (Disposition 14, and 05) for troubles with a tch.	

Sub-Metrics	Sub-Metrics – Missed Repair Appointment (Continued)				
MR-3-05	% Missed Repair Appointment –Double Dispatch ³¹				
Products	Retail/VADI: POTS 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing	Resale: POTS 2 Wire Digital Services (ISDN)		 UNE: Platform Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line Sharing 	
Calculation	Numerator			Denominator	
	Number of network troubles where clear time is greater than commitment time (missed appointments for (M=X) for Disposition Codes 0300-0599) for troubles with multiple dispatches.		Codes 03, 0 multiple disp	asured by individual	
	Retail is measured by individual dispatches on a single trouble.		dispatches of	on a single trouble.	
			UNE is based on double dispatch		
	UNE is based on double dis	patch identifier.	identifier.		

³¹ When Verizon New York Virginia opens a second trouble report, after an incorrect dispatch by a CLEC, Verizon New York Virginia will notify the CLEC by telephone of the second trouble ticket.

MR-4 Trouble Duration Intervals

Definition:

This metric measures the trouble duration intervals. Mean Time to Repair: (MTTR) For Network Trouble reports, the average duration time from trouble receipt to trouble clearance. Includes Disposition Codes 03 (Drop Wire), 04 (Cable) and 05 (Central Office).

For **POTS and Complex** type services this is measured on a *running clock* basis. Run clock includes weekends and holidays.

For **Special Services** type services and Interconnection trunks, this is measured on a *stop clock* basis (e.g., the clock is stopped when CLEC testing is occurring, VZ is awaiting carrier acceptance, or VZ is denied access).

Out of Service Intervals: The percent of Network Troubles that indicate an Out-Of-Service (OOS) condition which was repaired and cleared more than "y" hours after receipt of trouble report. OOS means that there is no dial tone, the customer cannot call out, or the customer cannot be called. The OOS period commences when the trouble is entered into VZ's designated trouble-reporting interface either directly by the CLEC or by a VZ representative upon notification. OOS intervals includes weekends and holidays. Includes Disposition Codes 03 (Drop Wire), 04 (Cable) and 05 (Central Office). **Note:** "y" equals hours OOS (2, 4, 12 or 24 hours).

For Special Services: An OOS condition is defined as follows: Troubles where, in the initial contact with the customer, it is determined that the circuit is completely OOS and not just an intermittent problem (osi = 'y'), and the trouble completion code indicated that a trouble was found within the Verizon network (trbl_cd is "FAC" or "CO").

Double Dispatch: A trouble that has more than one dispatch before closure. May include more than one outside dispatch or dispatches inside and outside.

Exclusions:

- Subsequent reports (additional customer calls while the trouble is pending)
- Customer Premises Equipment (CPE) troubles
- Troubles reported but not found (Found OK and Test OK).
- Troubles closed due to customer action.
- Troubles reported by Verizon employees in the course of performing preventative maintenance, where
 no customer reported a trouble.

Performance Standard:

Parity with VZ Retail. UNE Loop measurement will be compared to Retail Business and Residence combined.

Report Dimensions

Company: VZ Retail CLEC Aggregate CLEC Specific CLEC Specific Geography: POTS and Complex: Manhattan, Greater Metro, Suburban and North-State NOVA, Central (Richmond), Eastern, Western Specials & Trunks: New York State (LATA 132 and Remaining State – as identified) Virginia

Sub-Metrics	Sub-Metrics – Trouble Duration Intervals			
MR-4-01	Mean Time To Repair – Total			
Products		Resale: POTS 2 Wire Digital Services (ISDN) Specials	UNE: Platform Loop 2-Wire Digital Services Specials	Trunks: • CLEC Trunks
Calculation	Numei	rator	•	minator
	Sum of trouble clear dat trouble receipt date and Office and Loop troubles 03, 04 and 05 (Specials time).	time for Central (Disposition Codes	Number of Central C troubles (Disposition 05).	
MR-4-02	Mean Time To Repair	– Loop Trouble		
Products	Retail/VADI: POTS- Business POTS - Residence POTS-Total 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing	Resale: POTS- Busin POTS- Reside 2 Wire Digitale (ISDN)	dence • Platform Residence	
Calculation	Numei	rator	Denoi	minator
	Sum of the trouble clear the trouble receipt date troubles (Disposition Co	and time for Loop	Number of Loop troubles (Disposition Codes 03 and 04).	
MR-4-03	Mean Time To Repair	- Central Office Trou	uble	
Products	Retail/VADI: POTS- Business POTS- Residence POTS-Total 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing	2 Wire Digital (ISDN)	dence Bu I Services PC Re PC 2-\ 2-\ 2-\	OTS – Platform siness OTS – Platform sidence OTS - Loop Wire Digital Services Wire xDSL Loops Wire xDSL Line aring
Calculation	Numei	rator	Denoi	minator
	Sum of trouble clear dat trouble receipt date and Office troubles (Disposit	time for Central	Number of Total Central Office troubles (Disposition Codes 05).	

Sub-Metrics	MR-4 Trouble Dura	ation Intervals (co	ntinued)	
MR-4-04	% Cleared (all trouble		,	
Products	Retail/VADI: POTS 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing Specials IXC FGD Trunks	Resale: POTS 2 Wire Digital Services (ISDN) Specials	UNE: Platform Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line Sharing Specials	Trunks: • CLEC Trunks
Calculation	Nume	erator	Deno	minator
MR-4-05	Number of troubles, who date and time minus trutime is less than or equivalent with the control of the control	ouble receipt date and ual to 24 hours.	Number of Central C troubles (Disposition 05).	•
Products	Retail:	i ivui 3	Trunks:	
Flouucis	IXC FGD Trunks		CLEC Trunks	
Calculation		erator		minator
	Number of trunk troubles OOS, where the trouble clear date and time minus the trouble receipt date and time is greater than two (2) hours.		Number of Total OO and Central Office).	S trunk troubles (Loop
MR-4-06	% Out of Service > 4	Hours		
Products	Retail: POTS Specials IXC FGD Trunks	Resale: POTS Specials	UNE:PlatformSpecials	Trunks: • CLEC Trunks
Calculation	Nume	erator	Deno	minator
	Number of troubles OC clear date and time mindate and time is greated	nus trouble receipt er than four (4) hours.	Number of OOS trou Central Office).	bles (Loop and
MR-4-07	% Out of Service > 12		T	
Products	Retail/VADI: POTS Vire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing IXC FGD Trunks	Resale: POTS 2 Wire Digital Services (ISDN)	UNE: • Platform • Loop • 2-Wire Digital Services • 2-Wire xDSL Loops • 2-Wire xDSL Line Sharing	Trunks: • CLEC Trunks
Calculation	Nume		Deno	minator
	Number of troubles OC clear date and time min date and time is greater	nus trouble receipt	Number of OOS trou Central Office).	bles (Loop and

Sub-Metrics	MR-4 Trouble Duration Intervals (co	ntinued)		
MR-4-08	% Out of Service > 24 Hours			
Products	Retail/VADI: POTS- Business POTS- Residence POTS-Total 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing Specials Kesale: POTS- Business POTS- Residence 2 Wire Digital Services (ISDN) Specials	UNE: Platform Business Platform Residence Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line Sharing Specials		
Calculation	Numerator	Denominator		
	Number of troubles OOS, where the trouble clear date and time minus trouble receipt date and time is greater than 24 hours.	Number of OOS troubles (Loop and Central Office).		
MR-4-09	Mean Time To Repair - No Double Dispato	ch		
Products	Retail/VADI: POTS 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing	 UNE: Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line Sharing 		
Calculation	Numerator	Denominator		
	Sum of Trouble clear date and time minus trouble receipt date and time for Central Office and Loop troubles (Disposition Codes 03, 04 and 05) for troubles with a single dispatch.	Number of Central Office and Loop troubles (Disposition Codes 03, 04 and 05) for troubles with a single dispatch.		
MR-4-10	Mean Time To Repair -Double Dispatch			
Products	Retail/VADI: POTS 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing	UNE: Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line Sharing		
Calculation	Numerator	Denominator		
	Sum of Trouble clear date and time minus trouble receipt date and time for Central Office and Loop troubles (Disposition Codes 03, 04 and 05) for troubles with multiple dispatches. Retail is measured by the number of	Number of Central Office and Loop troubles (Disposition Codes 03, 04 and 05) for troubles with multiple dispatches. Retail is measured by the number of individual dispatches on a single trouble.		
	individual dispatches on a single trouble. UNE is based on double dispatch identifier.	UNE is based on double dispatch identifier.		

MR-5 Repeat Trouble Reports

Definition:

This metric measures the percent of troubles cleared that have an additional trouble reported/cleared within 30 days for which a network trouble (Disposition Codes 03, 04, or 05) is found. A repeat trouble report is defined as a trouble on the same line/circuit/trunk as a previous trouble report that occurred within the last 30 calendar days of the previous trouble. Any trouble, regardless of the original Disposition Code, that repeat as a Disposition Code 03, 04, or 05 will be classified as a repeat report.

The identification of a repeat report and the scoring (number of days since original report) is based on the Close Date of the original report (often referred to as the "OR") to the Close Date of the repeater.

Exclusions:

A report is not scored as a *repeat* when the original reports are:

- Troubles reported by Verizon employees in the course of performing preventative maintenance, where no customer has reported a trouble
- Excluded from the *repeat* reports are:_subsequent reports (additional customer calls while the trouble is pending)
- Customer Premises Equipment (CPE) troubles
- Troubles reported but not found upon dispatch (Found OK and Test OK).
- Troubles closed due to customer action.
- Troubles reported by Verizon employees in the course of performing preventative maintenance, where
 no customer reported a trouble.

Performance Standard:

Parity with VZ Retail.

Report Dimensions

Company: Geography:		eography:	
•	VZ Retail	_	POTS and Complex: Manhattan, Greater Metro,
•	CLEC Aggregate		Suburban and North-State NOVA, Central
•	CLEC Specific		(Richmond), Eastern, Western
		•	Specials & Trunks: New York State (LATA 132 and
			Remaining State - as identified) Virginia

	ous moures					
MR-5-01	% Repeat Reports wi	% Repeat Reports within 30 Days				
Products	Retail/VADI: POTS 2 Wire Digital Services (ISDN) 2-Wire xDSL Loops 2-Wire xDSL Line Sharing Specials IXC FGD Trunks	Resale: POTS 2 Wire Digital Services (ISDN) Specials	UNE: Platform Loop 2-Wire Digital Services 2-Wire xDSL Loops 2-Wire xDSL Line Sharing Specials	Trunks: • CLEC Trunks		
Calculation	Numerator		Denoi	minator		
	Number of Central Office and Loop troubles that had previous troubles within the last 30 days. (Disposition Codes 03, 04, and 05, that repeated from Disposition Codes < 14). (Repeat Flag is set)		Total Central Office a troubles (Disposition 05) within the calend	Codes 03, 04 and		

Network Performance

(NP)

	Function	Number of Sub-metrics
NP-1	Percent Final Trunk Group Blockage	4
NP-2	Collocation Performance	8
NP-3	Switching Performance	0
NP-4	Notification of Network Outage	0

Network Performance (NP)

Function:

NP-1 Percent Final Trunk Group Blockage

Definition:

The percent of Final Trunk Groups that exceed blocking design threshold. Monthly trunk blockage studies are based on a time consistent busy hour. The percentage of VZ trunk groups exceeding the applicable blocking design threshold will be reported. Data collected in a single study period to monitor trunk group performance is a sample and is subject to statistical variation based upon the number of trunks in the group and the number of valid measurements. With this variation, for any properly engineered trunk group, the measured blocking for a trunk group for a single study may exceed the design-blocking threshold. [Tables specify the blocking threshold (Service Threshold) under which Verizon operates, above which it is statistically probable that the design blocking standard is not being met and the trunk group requires servicing action. For B.005 design, this is trunk-groups exceeding a threshold of about 2% blocking.]
For this measure, VZ Retail Trunks are defined as Common Final Trunks carrying Local Traffic between offices. Typical common final trunks are between end-offices and access tandems.

CLEC Trunks are dedicated final trunks carrying traffic from the VZ-access tandem to the CLEC.

Exclusions:

Trunks not included:

- IXC Dedicated Trunks
- Common Trunks carrying only IXC traffic

VZ will electronically notify CLECs (operational trunk staffs), of the following situations for blocked trunks. This notification will identify that VZ has identified a blocked trunk group and that the trunk group should be excluded from VZ performance. Unless the CLEC responds back with documentation that the information on the condition is inaccurate, the trunk group will be excluded:

- Trunks blocked due to CLEC network failure
- Trunks that actually overflow to a final trunk, but are not designated as an overflow trunk
- Trunks blocked where CLEC order for augmentation is overdue
- Trunks blocked where CLEC has not responded to or has denied VZ request for augmentation
- Trunks blocked due to other CLEC trunk network rearrangements.

Performance Standard:

Metrics NP-1-01, 02, and 03: No standard (Note: Because common trunks carry both retail and CLEC traffic, there will be parity with Retail on common trunks.)

For individual trunk groups carrying traffic between VZ and CLECs, VZ will provide an explanation (and action plan if necessary) on individual trunks blocking for two months consecutively.

Metric NP-1-04: An individual trunk should not be blocked for three consecutive months.

End User Standard:

602.1(m) Final Trunk Group - The last choice group of common interoffice communications channels for the routing of local, operator and/or toll calls.

603.3(g) Percent Final Trunk Group Blockages. This metric is defined as the monthly percentage of blocked calls on any local, toll, and local operator final trunk groups and has a performance threshold of 3.0% or less for each final trunk group.

603.4(d)(3) For Percent Final Trunk Group Blockages, a Service Inquiry Report shall automatically be filed whenever performance is not at or better than 3.0 percent for three consecutive months.

Report Dimensions – NP-1 Percent Final Trunk Group Blockage			
Company:		Geography:	
VZ Retail		New York	∢ <u>Virginia</u>
 CLEC Aggre 	CLEC Aggregate		
CLEC Speci			
Products	Retail:		Trunks:
	 VZ Common Final (Local)Tree 	unks	CLEC Trunks
Sub-Metrics			
NP-1-01	% Final Trunk Groups Exceed	ling Blocking	Standard
Calculation	Numerator		Denominator
	Number of Final Trunk Groups that exceed blocking threshold for one (1) month exclusive of trunks that block due to CLEC		Total number of final trunk groups.
NP-1-02	network problems as agreed by % Final Trunk Groups Exceed		Standard (No Exceptions)
	•	ing blocking	• '
Calculation	Numerator		Denominator
	Number of Final Trunk Groups the blocking threshold.	nat exceed	Total number of final trunk groups.
NP-1-03	Number Final Trunk Groups E	xceeding Blo	ocking Standard – Two (2) Months
Calculation	Numerator		Denominator
	Number of Final Trunk Groups that exceed blocking threshold, for two (2) consecutive months, exclusive of trunks that block due to CLEC network problems as agreed by CLECs.		Not applicable.
NP-1-04	Number Final Trunk Groups E	xceeding Blo	cking Standard – Three (3) Months
Calculation	Numerator		Denominator
	Number of Final Trunk Groups that exceed blocking threshold, for three (3) consecutive months, exclusive of trunks that block due to CLEC network problems as agreed by CLECs.		Not applicable.

NP-2 Collocation Performance

Definition:

Interval: The average number of business days between order application date and completion or between order application date and response (notification of space availability) date. The application date is the date that a valid service request is received.

Refer to the web-site contained in Appendix L, Product Interval Summary, for specific collocation intervals.

Completions: VZ will not be deemed to have completed work on a collocation casge until the cage is suitable for use by the CLEC, and the cable assignment information necessary to use the facility has been provided to the CLEC.

Exclusions:

None

Formula:

Interval:∑ (Committed DD<u>Due Date</u>) minus the Application Date) divided by the Number of Cages. % On Time: Number of Cages completed on DD<u>Due Date</u> (adjusted for milestone misses) divided by Number of Cages completed multiplied by 100.

Delay Days: :∑ (Actual Completion Date minus the Committed DDDue Date (adjusted for milestone misses)) divided by the Number of Cages where DDDue Date is missed.

Performance Standard:

Refer to the web-site listed in Appendix L, Product Interval Summary for specific collocation intervals.

Metrics NP-2-01 and 05 - Physical:

95% On Time

Metrics NP-2-02 and 06 - Virtual:

95% On Time

Metrics NP-2-03, 04, 07, and 08: No standard.

Report Dimensions

Company:		Geography:
 CLEC Aggre 	egate	New York Virginia
 CLEC Speci 	fic	
Products	 New Applications 	
	 Augment Applications 	

NP-2-01	% On Time Response to Request for Physic	cal Collocation		
Calculation	Numerator	Denominator		
Number of requests for Physical Collocation		Number of requests for Physical		
	cages where response to request is	Collocation received in period.		
	answered on time.			
NP-2-02	% On Time Response to Request for Virtual Collocation			
Calculation	Numerator	Denominator		
	Number of requests for Virtual Collocation arrangements where response to request is answered on time.	Number of requests for Virtual Collocation received in period.		

Sub-Metrics NP-2 Collocation Performance (continued)			
NP-2-03	Average Interval – Physical Collocation		
Calculation	Numerator	Denominator	
	Sum of duration from application date to completion date for Physical Collocation cages completed during report period. (Excludes time for CLEC milestone misses).	Number of Physical Collocation cages completed.	
NP-2-04	Average Interval – Virtual Collocation		
Calculation	Numerator	Denominator	
	Sum of duration from application date to completion date for Virtual Collocation arrangements completed during report period. (Excludes time for CLEC milestone misses).	Number of Virtual Collocation arrangements completed.	
NP-2-05	% On Time – Physical Collocation		
Calculation	Numerator	Denominator	
	Number of Physical Collocation arrangements completed on or before DDdue date (including DDdue date extensions resulting from CLEC milestone misses).	Number of Physical Collocation cages completed.	
NP-2-06	% On Time – Virtual Collocation		
Calculation	Numerator	Denominator	
	Number of Virtual Collocation arrangements completed on or before DDdue date (including DDdue date extensions resulting from CLEC milestone misses).	Number of Virtual Collocation arrangements completed.	
NP-2-07	Average Delay Days - Physical Collocation	1	
Calculation	Numerator	Denominator	
	Sum of duration between actual Physical Collocation cage due completion date and DDdue date for missed Physical Collocation cages (including DDdue date extensions resulting from CLEC milestone misses).	Number of missed Physical Collocation cages.	
NP-2-08	Average Delay Days – Virtual Collocation		
Calculation	Numerator	Denominator	
	Sum of duration between actual Virtual Collocation arrangement due completion date and DDdue date for missed Virtual Collocation cages (including DDdue date extensions resulting from CLEC milestone misses).	Number of missed Virtual Collocation arrangements.	

NP-3 Switching Performance

Performance Standard:

Parity with Retail - by design of switch

Metrics Not Reported:

Switching performance data will be provided to the Commission in accordance with the requirements of Commission regulation, if any. No additional reporting is required by this metric.

Reported to New York PSC in Aggregate (Retail/Wholesale):	Reported to New York PSC
Switching Performance - PSC Standards	
Percent Blockages & Failures	0.0 - 1.0 (weak spot > 2.1)
Percent Incoming Matching Loss	0.0 - 2.1 (weak spot > 2.8)
 Percent Dial Tone Speed over three (3) Seconds 	0.0 - 1.5 (weak spot > 2.6)
Not Reported Switching Standards:	

Switching Index Standards by Switch Type:

The switching index takes a number of factors, weighs them, and calculates an overall score. The overall objective is 95.5 and up for each switch. Individual performances may fall below threshold, but not necessarily drop the index below. This is an overall indicator of switch performance.

Thresholds are based on industry standard guidelines and vary with switch manufacturers. The performance is grouped into two categories machine access and machine switching. Machine access measurements are designed to reflect difficulties experienced by the customer in obtaining service from the switching equipment. Machine switching measurements are designed to reflect customers' call attempts (or incoming call attempts from another switch) that failed during call processing. NOTE: There are no longer any 1AESS switches in New York, hence switching performance plan is removed.

Switching Performance - Index Plan - 5ESS	<u>Threshold</u>
a.) Machine Access	
Tone Decoder Overflow	1.00
Tone Decoder Attached Delay	0.10
— Dial Tone Speed	33.34
 SS7 Link Unavailable 	0.27
b.) Machine Switching	
Facility Cutoff Calls	2.00
Remote Module Stand Alone Time	0.50
Initializations SM/RSM	1.00
Interrupts (AM)	80.00
- Maintenance Usage	50.00
Audits	10.00
Equipment Outage	1.00
Equal Access	100.00
Switching Performance - Index Plan - DMS100	
a.) Machine Access	
— Dial Tone Speed	33.34
Receiver Queue	0.00
SS7 Link Unavailable	0.27
b.) Machine Switching	
Transmitter Time-outs	16.00
_Errors	50.00
EA Wink Equal Access	100.00
—SS7 Errors	10.00
Equipment Outage	1.00
RLCM RSC Emergency Stand Alone	5.00

NP-4 Notification of Network Outage

Performance Standard:

Parity with Retail - Same notification via e-mail distribution list

Metrics Not Reported:

Refer to the CLEC Handbook Series III, Section 8.3.7 for the Network Outage Notification processes.

Billing Performance

(BI)

	Function	Number of	
		Sub-metrics	
BI-1	Timeliness of Daily Usage Feed	4	
BI-2	Timeliness of Carrier Bill	1	
BI-3	Billing Accuracy	2	

Billing Performance (BI)

Function:

BI-1 Timeliness of Daily Usage Feed

Definition:

The number of business days from the creation of the message to the date that the usage information is made available to the CLEC on the Daily Usage Feed (DUF). Measured in percentage of usage records transmitted within three (3), four (4), five (5), and eight (8) business days. One report covers both UNE and Resale. For CLECs requesting this service, usage records will be provided to CLECs each business day. The usage process starts with collection of usage information from the switch. Most offices have this information teleprocessed to the data center. Not all offices poll usage every business day. Weekend and holiday usage is captured on the next business day. Usage for all CLECs is collected at the same time as VZ's.

Note:

- Verizon New York monitors the level of service order errors with the potential of delaying usage feeds;
- Verizon New York monitors the timeliness of the usage feed to the process on a daily basis; and
- Verizon New York offers its CLEC customers the option of receiving EMI usage feeds through the Network Data Mover (NDM) process to increase the timeliness of delivery.

Exclusions:

None

Formula:

(Total usage records in "y" business days divided by the total records on file) multiplied by 100

Note: y = 3, 4, 5 or 8

Performance Standard:

Process is Designed at parity with Retail

Metric BI-1-02: 95% in Four (4) Business Days.

Metrics BI-1-01, 03, and 04: No standard.

Report Dimensions

Report Dilliensions	
Company:	Geography:
CLEC Aggregate	New York Virginia
CLEC Specific	

BI-1-01	% DUF in three (3) Business Days		
Calculation	Numerator Denominator		
	Number of usage records on daily usage feed tapes processed during month, where the difference between current date and call date is three (3) days or less.	Number of Usage Records on DUF tapes processed during month.	
BI-1-02	% DUF in four (4) Business Days		
Calculation	Numerator	Denominator	
	Number of usage records on daily usage feed tapes processed during month, where the difference between current date and call date is four (4) days or less.	Number of Usage Records on DUF tapes processed during month.	

Sub-Metrics BI-1 Timeliness of DUF (continued)			
BI-1-03	% DUF in five (5) Business Days		
Calculation	Numerator	Denominator	
	Number of usage records on daily usage feed tapes processed during month, where the difference between current date and call date is five (5) days or less.	Number of Usage Records on DUF tapes processed during month.	
BI-1-04	% DUF in eight (8) Business Days		
Calculation	Numerator	Denominator	
	Number of usage records on daily usage feed tapes processed during month, where the difference between current date and call date is eight (8) days or less.	Number of Usage Records on DUF tapes processed during month.	

BI-2 Timeliness of Carrier Bill

Definition:

The percent of carrier bills sent to the carrier, unless the CLEC requests special treatment, within 10 business days of the bill date. The bill date is the end of the billing period for recurring, non-recurring and usage charges.

Exclusions:

None

Formula:

(Number of Bills sent within 10 business days divided by Number of Bills sent) multiplied by 100.

Performance Standard:

98% in 10 Business Days

Report Dimensions

Company:

• CLEC Aggregate

Geography:

• New York Virginia

BI-2-01	Timeliness of Carrier Bill	
Calculation	Numerator	Denominator
	Number of carrier bills sent to CLEC ³² within 10 business days of bill date.	Number of Carrier Bills distributed.

³² Sent to Carrier, unless other arrangements are made with CLEC

BI – 3 Billing Accuracy

Definition:

The percent of carrier bill charges adjusted due to billing errors.

Exclusions:

 Adjustments that are not billing errors such as: charges for directories, incentive regulation credits, performance remedies, OOS credits, special promotional credits

Performance Standard:

No Performance Standard yet developed.

Report Dimensions

Company:

VZ Retail

CLEC Aggregate

Geography:

New York Virginia

Sub-Metrics		
BI-3-01	% Billing Adjustments – Dollars Adjusted	
Calculation	Numerator	Denominator
	Number of dollars adjusted for billing errors.	Total Dollars Billed.
BI-3-02	% Billing Adjustments – Number of Adjustments	
Calculation	Numerator	Denominator
	Number of adjustments for billing errors.	Total Bills.

Operator Services & Directory Assistance

(OD)

	Function	Number of Sub-metrics
OD-1	Operator Services/Directory Assistance – Speed of	2
OD-2	Answer LIDB, Routing and OS/DA Platforms	0

Operator Services and Databases (OD)

Function:

OD-1 Operator Services/Directory Assistance – Speed of Answer

Performance Standard:

Standard: Average Speed of Answer provided at parity with Verizon retail.

Exclusions:

None

Report Dimensions

For metric OD-1-01 Operator Services – Speed of Answer Company:

- New York Virginia Retail (and Resale)
- New York Virginia CLEC (facility based and UNE-P)

For metric OD-1-02 Directory Assistance – Speed of Answer

- New York Virginia Retail (and Resale)
- New England-Virginia CLEC (facility based and UNE-P) 33

Geography:

New York Virginia

Sub-ivieti ics			
OD-1-01	Average Speed of Answer – Operator Services		
Calculation	Numerator Denominator		
	Sum of call answer time from the time the	Number of Calls Answered.	
	calls enter the queue for an operator to the		
	time the calls are answered by an operator.		
OD-1-02	Average Speed of Answer – Directory Assistance		
Calculation	Numerator	Denominator	
	Sum of call answer time from the time the calls enter the queue for an operator to the time the calls are answered by an operator.	Number of Calls Answered.	

³³ If no NY Virginia CLEC traffic is handled by these centers, the data will not be reported.

OD-2 LIDB, Routing and OS/DA Platforms

Performance Standard:

LIDB:

- LIDB reply rate to all query attempts: Bellcore produced standard
- LIDB query time out: Bellcore produced standard
- Unexpected data values in replies for all LIDB queries: 2%
- Group troubles in all LIDB queries Delivery to OS Platform: 2%

800 Database: Bellcore produced standard

AIN: Bellcore produced standard

Metrics Not Reported:

Verizon New York Virginia does not have the capability to report this performance area.

General and Miscellaneous Standards

(GE)

	Function	Number of Sub-metrics
GE-1	Directory Proofs	0
GE-2	Poles, Ducts, Conduit and Rights of Way	0

General (GE)

Function:

GE-1 Directory Proofs

Performance Standard:

VZ does not provide directory proofs to CLECs. VZ provides Listing Verifications Report 90 days before close out date and provides a Directory Listings view of Listings through the Web-GUI. All business rules are documented in the CLEC and Reseller Handbook.

Metrics Not Reported:

Verizon New York Virginia does not have the capability to report this performance area.

Function:

GE-2 Poles, Ducts, Conduit and Rights of Way

Performance Standard:

Verizon New York has specific performance guidelines contained in its pole attachment and conduit license agreements that are consistent with applicable Federal and State requirements. Verizon New York Virginia will respond to requests for its engineering records information, and requests for access to its carrying plant in accordance with Verizon's specific performance guidelines.

Metrics Not Reported:

Verizon New York Virginia does not have the capability to-report this performance area.

Glossary

Application Date	The date that a valid order is received.
ASR	Access Service Request
VZ Administrative Orders	Orders completed by VZ for administrative purposes and NOT at the request of a CLEC or end user. These also include administrative orders for VZ official lines and LIDT (Left in Dial Tone). [SWO<>"NC", "NF"] [CLS<>TOV, or CLS_2<>TOV].
Basic Edits	Front-end edits performed by DCASEDI/Web GUI prior to order submission. Basic Edits performed against DCASEDI/Web GUI provided source data include the following validations: State Code must equal NY, CT, MA, ME, NH, VT, RIDE, DC, MD, VA, NJ, PA, VA, WV; CLEC Id can-not be blank; All dates and times must be numeric; Order Type must be '1','2','3','4'; Svc Order Type must be '0', '1' '2'; Flowthru Candidate Ind and Flowthru Indicator must be 'Y' or 'N'; Lines Number must be numeric; Service Order Classification must be '0' or '1'; Confirmation Method must be 'E', 'M' 'W'; Each submission must have a unique key (PON + Ver + CLEC Id + State); Confirmation, Reject and Completion Transactions must have matching Submission record. Any changes to basic edits will be provided via VZ Change Control procedures.
BFR	Bona Fide Request Process (BFR): Refer to Appendix D for a summary of the BFR process.
Collocation Milestones	Refer to the web-site listed in Appendix L, Product Interval Summary, for specific collocation intervals. In Physical Collocation, the CLEC and VZ control various interim milestones they must meet to meet the overall intervals. The interval clock will stop, and the final due date will be adjusted accordingly, for each milestone the CLEC misses (day for day). Prior to the CLEC beginning the installation of its equipment, the CLEC must sign the VZ work completion notice, indicating acceptance of the multiplexing node construction work and providing VZ with a security fee, if required, as set forth in Section 5.5.5. Payment is due within 30 days of bill date. The CLEC may not install any equipment of facilities in the multiplexing node(s) until after the receipt by VZ of the VZ work completion notice and any applicable security fee.
	In Virtual Collocation,_VZ and the CLEC shall work cooperatively to jointly plan the implementation milestones. VZ and the CLEC shall work cooperatively in meeting those milestones and deliverables as determined during the joint planning process. A preliminary schedule will be developed outlining major milestones including anticipated delivery dates for the CLEC-provided transmission equipment and for training.

Change Management Notices	Change Management Notices are notices sent to the CLECs to notify CLECs of scheduled interface-affecting changes.
Common Final Trunk Blockage:	Common final trunks carry traffic between VZ end offices and the VZ access tandem, including local traffic to VZ customers as well as CLEC customers. (In rare circumstances, it is possible to have a common final trunk group between two end offices.) The percentage of VZ common final trunk groups carrying local traffic, exceeding the applicable blocking design standard (either B.01 or B.005) will be reported. All CLECCommon Final trunks are engineered at the B.005 level. In all but the Washington Metropolitan area, local common trunks are engineered at the B.005 level. In the Washington Metropolitan area, common trunks are engineered at the B.01 level.
Common Trunks:	High Usage Trunks carry two-way local traffic between two VZ end offices. High Usage Common Trunks are designed so that traffic will overflow to final trunk groups. Local trunks are designed such that no more than 0.5% (B.005 standard) of traffic will overflow during the busy hour in all Verizon New York geographies.
	Final Trunks: (All Verizon except New York LATA) Final Trunks carry two-way local and long distance IXC traffic between an end office and an access-tandem switch. In some geographic areas, Final Trunks are designed to carry only two-way local or only long distance IXC traffic between an end office and a tandem, which means that the local and long distance traffic are separated. Common Final Trunks are designed so that no more than 0.5% (B.005 standard) of traffic will block during the busy hour.
	Final Trunks – Local (NY LATA 132) Final Trunks carry local two-way traffic between an end office and an access tandem switch. Common Final Trunks are designed so that no more than 0.5% (B.005 standard) of traffic will block during the busy hour.
	Final Trunks – IXC (NY LATA 132 and Washington Metropolitan Calling Area) Final Trunks carry long distance IXC two-way traffic between an end office and an access tandem switch. Common Final Trunks are designed so that no more than 0.5% (B.005 standard) of traffic will block during the busy hour.
Company Initiated Orders	Provisioning orders processed for administrative purposes and not at customer request.
Company Services	Official Verizon Lines
Completion Date	The date noted on the service order as the date that all physical work is completed as ordered.
Coordinated Cut over	A coordinated cut-over is the live manual transfer of a VZ end user to a CLEC completed with manual coordination by VZ and CLEC technicians to minimize disruptions for the end user customer. Also known as a Hot Cut. These all have fixed minimum intervals.
CPE	Customer Premises Equipment.
Cut-Over Window	Amount of time from start to completion of physical cut-over of lines: One (1) to nine (9) lines: one (1) hour 10 to 49 lines: two (2) hours 50 to 99 lines: three (3) hours 100 to 199 lines: four (4) hours 200 plus lines: eight (8) hours
DCAS	Direct Customer Access System (DCAS): The system developed initially for the North States (CT, MA, ME, NH, NY, RI and VT) for a CLEC to transact with Verizon. DCAS supports GUI and EDI transactions. Request Manager will eventually replace DCAS.

Dedicated Final	A dedicated final trunk group does not overflow. Dedicated final trunk groups carry	
Trunks Blockage:	local traffic from a VZ Access Tandem to a CLEC switch. All dedicated final trunk	
	groups to the CLECs are engineered at a design-blocking threshold of B.005.	

Dedicated Trunks	High Usage Trunks – CLEC Interconnection: _carry one-way traffic from a CLEC switch end office to a Verizon switch Tandem Office or carry two-way local traffic between a Verizon switchend-office and a CLEC switchend-office. High Usage Common-Trunks are designed so that traffic will overflow to final trunk groups. Local trunks are designed such that no more than 0.5% (B.005 standard) of traffic will overflow during the busy hour in all Verizon geographies. These trunks are ordered by the CLEC.
	Final Trunks – CLEC Interconnection : _carry one-way traffic from a CLEC end-office to a Verizon Tandem Office or carry two-way traffic between an_end-office and a tandem switchCLECs order these trunks from VZ and engineer to their desired blocking design threshold.
	High Usage Trunks – VZ to CLEC Interconnection: _carry one-way local traffic from a Verizon switchend-office to a CLEC switchend-office. High Usage Common Trunks are designed so that traffic will overflow to final trunk groups. Local trunks are designed such that no more than 0.5% (B.005 standard) of traffic will overflow during the busy hour in all Verizon geographies. VZ orders these trunks from CLECs.
	Final Trunks – VZ to CLEC Interconnection: _carry one-way traffic from a VZ switchend office or a CLECtandem_switch. Final Trunks are designed using a se that no more than 0.5% (B.005 standard_) of traffic will block during the busy hour_in all Verizon geographies. VZ orders these trunks from CLECs.
	High Usage Trunks – IXC Feature Group D: _carry two-way traffic between a Verizon end-office and an IXC POP. High Usage Trunks are designed so that traffic will overflow to final trunk groups. <u>IXC trunks are designed such that no more than 0.5% (B.005 standard) of traffic will overflow during the busy hour in all Verizon geographies.</u> IXCs order these trunks from VZ.
	Final Trunks – IXC Feature Group D; _carry two-way traffic between and endoffice and a tandem switch. Common Final Trunks are designed <u>using a so that no more than 0.5% (B.005 standard) of traffic will block during the busy hour in all Verizon geographies</u> . IXCs order these trunks from VZ.
Dispatched Orders:	An order requiring dispatch of a Verizon Field technician outside of a Verizon Central Office. Intervals differ by line size. In all areas, for orders greater than or equal to 10 lines, a facility check is required and the interval negotiated. In many, but not all areas, a facility records check (in Engineering) is also performed for orders with six (6) to nine (9) lines.
Dispatched Troubles:	Loop or Drop Wire Troubles reports found to be in drop wire or outside plant. Disposition codes 03 or 04.
Disposition Codes	The code assigned by the Field Technician upon closure of trouble. This code identifies the plant type/location in the network where the trouble was found.
DUF	Daily Usage Feed:
FOC	Firm Order Confirmation.
Front End Close-Out	A trouble report closed with the customer on the line usually within 10 minutes of receiving the trouble from the customer. These include cancellations by the customer or CLEC. Disposition Codes: 0741(RE<10), 0747, 0706(CP=291).
LIDT	Left in Dial tone Orders. These are orders used after a customer has moved out of a residence dwelling and the line has been disconnected for billing – to leave in reserve Office Equipment (OE) assigned to the cable pair in the Central Office Once another customer moves into the location a second order is written to remove the LIDT status to enable the customer order to process.

These are not customer-requested orders.

Loop Qualification	Loop qualification is the manual step whereby it is determined if the loop facility
200p Qualification	meets or can be made to meet specifications necessary for ISDN or xDSL
	services. It must be provided on non-loaded facilities with less than 1300 OHMs
	of resistance and not more than 6 kft of bridge tap.
LSR	Local Service Request
LSRC	Local Service Request Confirmation
Mechanized Flow-	Orders received electronically through the ordering interface DCAS <u>EDI, Web</u>
Through:	GUI) and requiring no manual intervention to be entered into the SOP.
Missed Appointment	Verizon Missed Appointment Codes: CB = Business Office, CC = Common
Codes	Cause, CE = Equipment, CF = Facility, CL = Load (lack of work forces), CS =
	Switching/programming, CO = Company Other
	Customer Missed Appointment Codes: SA = Customer Access, SR = Customer
N. C. L. L.	Not Ready, SO = Customer Other, SL = Customer requested later due date
Negotiated Intervals	A process whereby Verizon New York and the CLEC discuss and come to a
	mutual agreement on a delivery date of requested services. This agreement should be based on customer, CLEC and Verizon—New York requirements;
	including but not limited to equipment, facility and work resources required for
	completing the requested services. Both the CLEC and Verizon—New York
	should be able to explain the requirements and positions for the discussion.
Network Troubles	Troubles with a disposition code of 03 (Drop Wire), 04 (Loop), or 05 (Central
Tretwent Treasies	Office). Excludes Subsequent reports (additional customer calls while the trouble
	is pending), Customer Premises Equipment (CPE) troubles, troubles reported
	but not found on dispatch (Found OK and Test OK), and troubles closed due to
	customer action.
Non-Mechanized:	Orders that require some manual processing. Includes orders received
	electronically that are not processed directly into the legacy provisioning
	systems, and are manually entered by a VZ representative into the VZ Service
	Order Processor (SOP) system. For orders not received electronically (such as
N D:	faxed or courier orders), 24 hours are added to all intervals.
No-Dispatch Troubles:	Troubles reports found to be in the Central Office, including frame wiring and translation troubles. Disposition Codes 05.
No-Dispatch Orders:	Orders completed without a dispatch outside a Verizon Central Office. Includes
	orders with translation changes and dispatches inside a Verizon Central Office.
Orders with ≥ 10 6 lines:	In some geographic areas, aA facility check is completed on orders greater than
	five (5) lines. In all geographic areas, orders with 10 or greater lines require a
OSS	facility check prior to order confirmation and due date commitment.
Parsed CSR	Operations Support Systems The Parsed CSR transaction returns fielded Customer Service Record data to
Parsed CSR	the customer when the PARSEIND field = Y on the inquiry. The parsed CSR
	transaction enables CLECs to populate their ordering template. This transaction
	is available on EDI and CORBA. The Verizon Parsed CRS transaction supports
	POTS accounts, it currently does not support complex accounts including ISDN
	and Centrex.
POTS Services	Plain Old Telephone Services (POTS) include all non-designed lines/circuits that
	originate at a customer's premise and terminate on an OE (switch Office
	Equipment). POTS include Centrex, basic ISDN and PBX trunks.
DOM	
PON	Purchase Order Number: Unique purchase order provided by CLEC to VZ placed

Projects	Projects are designated by CLECs. For Trunks, any request for a new trunk group, augment for more than 384 trunks, complex (E911 or DA) or request out of the ordinary requiring special coordination, such as rearrangements is considered a project.
Retail/VADI	For metrics where the standard is "Parity with Retail", (a) Verizon will use its UNE 2 Wire xDSL Loops performance for Verizon Advanced Data Inc. as the basis of comparison for its UNE 2 Wire xDSL Loops performance for CLECs, and (b) Verizon will use its UNE 2 Wire xDSL Line Sharing performance for Verizon Advanced Data Inc. as the basis of comparison for its UNE 2 Wire xDSL Line Sharing performance for CLECs.
Reject	An order is rejected when there are omissions or errors in required information. Rejects also include queries where notification is provided to a CLEC for clarification on submitted orders. The order is considered rejected and order processing is suspended while a request is returned or queried.
Run Clock	A measure of duration time where no time is excluded. Duration time is calculated comparing the date and time that a trouble is cleared to the date and time that the trouble was reported.
Segment	Segments are parts of whole orders. [NVL SEGMENT, 0=<1] A segment is used to apportion a longer order to meet limitations of record lengths. Similar to a separate page or section on the same order.
SOP	Service Order Processor
Special Services	Any service or element involving circuit design. Any service or element with four wires. Any DS0, DS1 and DS3, no access service. Excludes trunks. IOF and EEL are separately reported for provisioning.
Stop Clock	A measure of duration time where some time is excluded. The clock is stopped when testing is occurring, VZ is awaiting carrier acceptance, or VZ is denied access.
Suspend/Restore Orders	Orders completed by VZ to suspend for non-payment or restore for payment subject to New York PSC Collections guidelines. [SNPRES_IND.IS NOT NULL]Includes: (a) orders to suspend Verizon Retail customer service for non-payment and to restore service suspended for non-payment; and (b) for Resale service, CLEC orders to suspend CLEC customer service for non-payment and to restore service suspended for non-payment, provided such orders are submitted to Verizon as orders to suspend for non-payment and restore service suspended for non-payment, pursuant to Verizon's CLEC suspend for non-payment service.
Test Orders	Orders processed for "fictional" CLECs for VZ to test new services, attestation of services etc. Includes the following CLEC AECN's: 'DPC', 'DPCL','NYNX','ZKPM','ZPSC','ZTKP','ZTPS','ZJIM'.
TGSR	Trunk Group Service Request. A request that CLECs submit to Verizon to request augmentation to the Verizon network to accommodate an increase in CLEC volume.
Two wire digital ISDN Loop	2-Wire unbundled digital loop (previously called 2-Wire Digital Loop) that is compatible with ISDN basic Rate service. It is capable of supporting simultaneous transmission of two (2) B channels and One (1) D channel. It must be provided on non-loaded facilities with less than 1300 OHMs of resistance and not more than 6 kft of bridge tap. This service provides a digital 2-wire enhanced channel. It is equivalent to a 2-wire loop less than 18,000 feet from the NID at the end user's premises to the main distributing frame (which is connected to the CLEC's collocation arrangement), in Verizon's Central Office where the end user is served. The 2-wire digital – ISDN BRI loop, currently offered by Verizon, is designed to support the Integrated Services Digital Network (ISDN) Basic Rate Service which operates digital signals at 160 kilobytes per second (kbps). The 2-wire digital – ISDN BRI loop is only available to the CLEC for use in

conjunction with the provision of local exchange service and exchange access to
its end-users.

Product identification descriptions:

Retail	Major Customer Name/Number entered on Provisioning order first four (4)
	characters does not contain the values "RSID" which indicates resold or
	"AECN" which indicates unbundled.
Resale	Major Customer Name/Number entered on Provisioning order-first four (4)
11000.10	characters does contain the value "RSID" the 6th through 10th indicate
	reseller id. RSID except test and training RSID orders
	Ordering: ORDER-TYPE of ORDERING-MASTER-REC = '1'
UNE	Major Customer Name/Number entered on provisioning order- first four (4)
	characters contains the values "AECN" which indicates unbundled.
	Characters 6 through 10 indicate the Telecommunications carrier id.
	Ordering: ORDER-TYPE of ORDERING-MASTER-REC = '2' or '3'
POTS - Total	Two-wire analog service with a telephone number and POTS class of service.
	Includes analog loop-(SVGAL).
	Ordering:
	 Service order classification of ordering master rec = 0
	Provisioning:
	 Pots Orders are defined as not having a circuit layout (CL_FID IS NULL)
	or are not for ISDN service (SCM_2 IS NULL)
	Maintenance:
	• Class Service = 04/05/06/07/08/09/10/13/19/20/21
Complex:	Provisioning:
	• ISDN Basic Rate: Secondary Service Code Modifier (SCM_2) is not
	blank
	 ISDN Primary: Service Code Modifier (SCM) begins with "IB"
	2-Wire Digital Services
	2-Wire xDSL Services (for UNE, 2 Wire xDSL Loops and 2 Wire xDSL)
	Line Sharing)

Special Services

Special Services are services that require engineering design intervention. These include such services as: high capacity services (DS1 or DS3), Primary rate ISDN, 4 wire xDSL Services, digital services and private lines or foreign served services (a line physically in one exchange, served by another through a circuit).

Ordering:

- Service order classification of ordering master rec = 1 Provisioning:
- CL_FID is not NULL

Maintenance:

• Criteria for inclusion is Circuit format (cfmt) is 's','t','2','3' as defined by Bellcore standard, report category (rpt_cat) is "CR" indicating a Customer Reported trouble, circuit format does not indicate (fourth character of circuit id for a length of 2) "TK","IB","DI","DO" because these are considered POTS, 7th character of circuit id does not indicate official Verizon line as defined by Bellcore standard practice, trouble code (trbl_cd) is either "FAC" or "CO" indicating the trouble was found in the Facility-cable (from Central Office to customers location), or in the Central Office (the trouble was found within the Verizon Central Office), Maintenance center (MCTR) is not training or blank which excludes troubles entered for employee training purposes, Subsequent calls on the same trouble are not included in these metrics, Troubles are excluded where circuit id (cktid character 4 for a length of 2) indicates access tariff filing.

For Trunks:

For Maintenance: Criteria for inclusion is Circuit format (cfmt) is 'M' as defined by Bellcore standard, report category (rpt_cat) is "CR" indicating a Customer Reported trouble, trouble code (trbl_cd) is either "FAC" or "CO" indicating the trouble was found in the Facility-cable (from Central Office to customers location) or in the Central Office (the trouble was found within the Verizon Central Office), Maintenance Center (MCTR) is not training or blank which excludes troubles entered for employee training purposes, Subsequent calls on the same trouble are not included in these metrics.

Specials and Trunk Maintenance Code Descriptions

Trunk Maintenance:

Included are all Message Trunk troubles reported by the customer that were caused by a problem within the Verizon network. This does not include troubles for (Special Access) circuits under the Access tariff.

Criteria for inclusion is Circuit format (cfmt) is 'M' as defined by Bellcore standard, report category (rpt_cat) is "CR" indicating a Customer Reported trouble, trouble code (trbl_cd) is either "FAC" or "CO" indicating the trouble was found in the Facility-cable (from Central Office to customers location) or in the Central Office (the trouble was found within the Verizon central office), Maintenance center (MCTR) is not training or blank which excludes troubles entered for employee training purposes, Subsequent calls on the same trouble are not included in these metrics.

Measure Trunks:	criteria
total lines	Count of all Message Trunks that are currently workingl.e. provisioning work is complete.
total network troubles	trouble close out code indicates the trouble was found in the facility or central office part of the Verizon Network - trbl_cd is "FAC" or "CO" .
Network trouble report rate	total network troubles divided by total working lines then multiply by 100
mean time to repair	average (mean) of all duration times for receipt of the trouble within the Verizon Operating Support System to the time the circuit was restored to service to the customeravg_(actual_dur)the actual_dur field does not contain any time where the Verizon technician could not gain access to the customer location.
out of service	This is used as the divisor for all of the out of service metricsupon initial contact with the customer it is determined that the circuit is completely out of service and not just intermittent problem (osi = 'y') and that the trouble completion code indicated that a trouble was found within the Verizon network (trbl_cd is "FAC" or "CO")
out of service over 24	The trouble report entry indicated that the circuit was out of service (osi is 'y') to the customer and that the trouble was reported more than 24hours before it was resolved (actual_dur is > 1440 minutes or 24 hrs) and that the trouble close out code indicates that a trouble was found within the Verizon Facility or Central office network (trbl_cd is "FAC" or "CO").
% out of service over 24	total troubles out of service more than 24 hours divided by total troubles that were out of service to the customer then multiply by 100

repeats	Total troubles entered - where a previous trouble report on the same circuit occurred within the previous 30 days. Trouble is scored as a "repeat". Count of all repeats (rpr_flag is 'y') where trouble close out code indicates trouble was found within the Verizon Network.
% repeats	Total repeated troubles divided by total troublesthen multiply by 100.

Trunks:

trouble code	the code that identifies the type of trouble found
Repeat	The flag indicates that this trouble report was received within 30 days of the restoral date of the last trouble reported on the circuit.
out of service indicator	The flag is set to 'y' if the circuit was out of service when the report was taken, or was scored as out of service during the life of the trouble. For designed circuits the flag is always set to y

Specials Services Maintenance:

Included are all special service troubles reported by the customer that were caused by a problem within the Verizon network. This does not include troubles for special access circuits under the Access tariff.

Criteria for inclusion is Circuit format (cfmt) is 's','t','2','3' as defined by Bellcore standard, report category (rpt_cat) is "CR" indicating a Customer Reported trouble, circuit format does not indicate (fourth character of circuit id for a length of 2) "TK","IB","DI","DO" because these are considered POTS, 7th character of circuit id does not indicate official Verizon line as defined by Bellcore standard practice, trouble code (trbl_cd) is either "FAC" or "CO" indicating the trouble was found in the Facility-cable (from Central Office to customers location) or in the Central Office (the trouble was found within the Verizon central office), Maintenance center (MCTR) is not training or blank which excludes troubles entered for employee training purposes, Subsequent calls on the same trouble are not included in these metrics, Troubles are excluded where circuit id (cktid character 4 for a length of 2) indicates access tariff filing. table will be provided.

Measure	Criteria
Special Services:	
total lines	count circuits where center (MCTR) is not blank, not an official service (cktid 8,1) is not z (lines are in a different data base than specials and the circuit id field has a different layout), and only count 1 end of a point to point circuit (CKLEND='z') z indicates customer location.
total network troubles	trouble close out code indicates the trouble was found in the facility or central office piece of the special services circuit - trbl_cd is "FAC" or "CO".
Network trouble report rate	total network troubles divided by total working lines then multiply by 100.
total troubles loop	trouble close out code indicates the trouble was found in the facility portion of the Verizon Network - (trbl_cd is "FAC")

network trouble report rate- loop	total troubles loop divided by total lines multiply by 100
total troubles "CO"	trouble close out code indicates the trouble was found in the central office portion of the Verizon Network - (trbl_cd is "CO").
network trouble report rate - co	total troubles central office divided by total lines then multiply by 100.
mean time to repair	Average (mean) of all duration times for receipt of the trouble within the Verizon Operating Support System to the time the circuit was restored to service to the customeravg(actual_dur)the actual_dur field does not contain any time where the Verizon technician could not gain access to the customer location.

Special Services:

opeolal oct vioco.	
mean time to repair loop	average (mean) of all duration times for receipt of the loop trouble within the Verizon Operating Support System to the time the circuit was restored to service to the customeravg(actual_dur) and trbl_cd is "FAC"the actual_dur field does not contain any time where the Verizon technician could not gain access to customer location
mean time to repair co	average (mean) of all duration times from receipt of the CO trouble within the Verizon Operating Support System to the time the circuit was restored to service to the customeravg(actual_dur) and trbl_cd is "CO"the actual_dur field does not contain any time where the Verizon Technician could not gain access to the customer location or the customer was verifying the status of the circuit.
out of service	This is used as the divisor for all of the out of service metricsupon initial contact with the customer it is determined that the circuit is completely out of service and not just intermittent problem (osi = 'y') and that the trouble completion code indicated that a trouble was found within the Verizon network (trbl_cd is "FAC" or "CO").
out of service loop	This is used as the divisor for all of the loop out of service metricsupon initial contact with the customer it is determined that the circuit is completely out of service and not just intermittent problem (osi = 'y') and that the trouble completion code indicated a trouble was found within the LOOP piece of the Verizon network (trbl_cd is "FAC").
out of service co	This is used as the divisor for all of the CO out of service metricsupon initial contact with the customer it is determined that the circuit is completely out of service and not just intermittent problem (osi = 'y') and that the trouble completion code indicated that a trouble was found within the CO piece of the Verizon network (trbl_cd is "CO").

out of service over 24	The trouble report entry indicated that the circuit was out of service (osi is 'y') to the customer and that the trouble was reported more than 24hours before it was resolved (actual_dur is > 1440 minutes or 24 hrs) and that the trouble close out code indicates that a trouble was found within the Verizon Facility or Central office network (trbl_cd is "FAC" or "CO").
% out of service over 24	total troubles out of service more than 24 hours divided by total troubles that were out of service to the customer then multiply by 100.
out of service over 24- loop	The trouble report entry indicated that the circuit was out of service (osi is 'y') to the customer and that the trouble was reported more than 24hours before it was resolved (actual_dur is > 1440 minutes or 24 hrs) and that the trouble close out code indicates that a trouble was found within the Verizon Facility network (trbl_cd is "FAC").
% out of service over 24 loop	total troubles out of service more than 24 hours loop divided by total troubles that were out of service - loop to the customer then multiply by 100.
out of service over 24- CO	The trouble report entry indicated that the circuit was out of service (osi is 'y') to the customer and that the trouble was reported more than 24hours before it was resolved (actual_dur is > 1440 minutes or 24 hrs) and that the trouble close out code indicates that a trouble was found within the Verizon Central Office network (trbl_cd is "CO").
% out of service over 24 CO	total troubles out of service more than 24 hours CO divided by total troubles that were out of service - CO to the customer then multiply by 100.
repeats	total troubles entered - where a previous trouble report on the same circuit occurred within the previous 30 days. Trouble is scored as a "repeat". Count of all repeats (rpr_flag is 'y') where trouble close out code indicates trouble was found within the Verizon Network.
% repeats	Total repeated troubles divided by total troublesthen multiply by 100.
trouble code	the code that identifies the type of trouble found
Repeat	The flag indicates that this trouble report was received within 30 days of the restoral date of the last trouble reported on the circuit.
out of service indicator	The flag is set to 'y' if the circuit was out of service when the report was taken, or was scored as out of service during the life of the trouble. For designed circuits the flag is always set to y

Example of Actual coding for Out of Service Specials:

stop oos le 3 (5)	actual_dur is le 003:00 (hrs/min) and osi is y and trbl_cd is co
% stop oos le3(5)	stop oos le 3(5) / total oos 5 * 100
stop oos le 4(5)	actual_dur is le 004:00 (hrs/min) and osi is y and trbl_cd is co
% stop oos le 4(5)	stop oos le 4(5) / total oos 5 * 100
stop oos le 4 (3,4)	actual_dur is le 004:00 (hrs/min) and osi is y and trbl_cd is fac
% stop oos le4(3,4)	stop oos le 4(3,4) / total oos 3/4 * 100
stop oos le 16(3,4)	actual_dur is le 016:00 (hrs/min) and osi is y and trbl_cd is fac
% stop oos le 16(3,4)	stop oos le 16(3,4) / total oos 3/4 * 100

SORD Code Tables: (Service Order Database Codes)

ORDER TYPE:

Defines what type of service is requested

- N New Service
- The "To" portion when a customer moves From one address To another address
- C Change request to existing service (add or remove features/services)

Appointment Type Code (ATC):

This code identifies how the appointment date was derived

- W The customer accepted the company's offered due date
- X The customer requested a due date that was greater than the company's offered

Due date

S The customer requested a due date that was earlier than the companies offered

due date

- C The customer requested a special due date to coordinate a hot cut.
- R A due date could not be applied due to company or customer reasons.

Missed Appointment Code (MAC):

When the original scheduled due date is missed a code is applied to the order to identify the reason for the miss

Customer Missed Appointment:

- SA Access could not be obtained to the customers premises(customer not at home)
- SR Customer was not ready to receive the new service
- SO Any other customer caused reason for the delay (e.g., unsafe working conditions

at the customer site)

- SL Customer requested a later appointment date prior to the due date
- SP Customer requested an earlier appointment date prior to the due date
- __ Under Development: CLEC Not Ready
- Under Development: CLEC Not Ready due to late FOC

Company (VZ) Missed Appointment:

CA The cable pair from the VZ central office to the customer premises could not be

Assigned by the due date due to any reason, including assignment load. If after the due date it is determined that no facilities were available, a CF miss is applied.

- CB The VZ business office taking the request caused the delay (misplaced the order)
- CC A Common Cause that affected a large area caused the delay (Hurricanes/work

stoppages)

- CF The assigned cable facility was bad
- CL Not enough VZ technicians to complete the work on a given day
- CO Any other delay caused by the Company not listed here (e.g., Technicians truck

broke down)

CS The VZ Central office work was not complete (line not programmed)

<u>SWO:</u>

A code applied when the order is completed to identify the service grouping

NR Residence service

NL Small business (2 lines or less) NV Large business (3 lines or more)

NF & NC Internal VZ service
NS Special services
NP VZ Coin services

SELLER TYPE

A code used to identify orders for Wholesale/Resale/UNE

1 VZ Retail
 R Resale
 A or C UNE
 P COIN

CL FID:

Circuit Layout identifies the type of circuit

* any code in this field identifies the service as a special service

Service Code Modifier (SCM):

Identifies the service grouping of a special service circuit .

ITEM	SERVICE ORDER	SORD FILED	VALUE
Dispatch	OCB in STAT section	OCB_COC	='O'
No Dispatch	N0 OCB in STAT section	OCB_COC	<>'0'
Offered Interval	Elapsed business days between the application date and due date in Header Section	APPINTV	INTERGER
Completion Interval	Elapsed business days between the application date and completion date in header section	CMPINTV	INTERGER
Status complete		STATUS	='55B'
Company services	SWO = is NF or NC in STAT section	SWO_CODE	<>'NC', 'NF'
Seller	RSID or AECN in ID CCAR section	SELLER_NAME	
ATC	Appointment type code after due date in header section	ATC	W' OR 'X'
Service Code Modifier	Position 3-4 of circuit ID in S&E section	SCM	SEE DS TABLE
Customer Missed Appointment	Follows "SD/" after due date in Header Section	CISR_MAC Company	COMPANY BEGINS WITH 'C'. CUSTOMER = SA, SR,SO, SL

Appendix B Provisioning Codes (continued)

SERVICE CODE MODIFIER (SCM) TABLE FOR DS LEVEL REPORTING

DERVICE CODE	MODIFIER (SCM) TABLE FOR DS	LEVEL KEI OKI	1110	
SCM - FIRST	Report Level	SCM - FIRST 2	Report Level	SCM - FIRST 2	Report Level
2 Characters		Characters		Characters	·
AB	DS0	QY	DS0	ED	DS3
CC	DS0	RC	DS0	EH	DS3
DA	DS0	ST	DS0	EJ	DS3
DC	DS0	US	DS0	EK	DS3
DM	DS0	WB	DS0	FI	DS3
DP	DS0	WC	DS0	GW	DS3
DQ	DS0	WD	DS0	HD	DS3
DR	DS0	WE	DS0	HE	DS3
DS	DS0	WF	DS0	HF	DS3
DW	DS0	XA	DS0	HG	DS3
DX	DS0	XB	DS0	HH	DS3
DY	DS0	XC	DS0	Н	DS3
DZ	DS0	XD	DS0	HT	DS3
FE	DS0	XE	DS0	HZ	DS3
FF	DS0	XF	DS0	JI	DS3
GA	DS0	XG	DS0	JJ	DS3
GB	DS0	XH	DS0	JK	DS3
GC	DS0	XI	DS0	LI	DS3
GD	DS0	XJ	DS0	LM	DS3
GE	DS0	XR	DS0	LO	DS3
GF	DS0	YG	DS0	LW	DS3
GG	DS0	YN	DS0	LX	DS3
GH	DS0			LY	DS3
GI	DS0			MB	DS3
GJ	DS0	AC	DS1	MD	DS3
GK	DS0	АН	DS1	ME	DS3
GL	DS0	AQ	DS1	MF	DS3
GM	DS0	AR	DS1	MG	DS3
GN	DS0	AS	DS1	MH	DS3
GO	DS0	CH	DS1	MI	DS3
GP	DS0	DB	DS1	MJ	DS3
GQ	DS0	DF	DS1	MK	DS3
GR	DS0	DG	DS1	MM	DS3
GS	DS0	DH	DS1	MP	DS3
GT	DS0	FL	DS1	OA	DS3
GU	DS0	HC	DS1	OB	DS3
GV	DS0	HJ	DS1	OD	DS3
GZ	DS0	HK	DS1	OE	DS3
HA	DS0	HL	DS1	OF	DS3
HB	DS0	HN	DS1	OG	DS3
HP	DS0	HU	DS1	QC	DS3
HQ	DS0	HX	DS1	QH	DS3
HR	DS0	IP	DS1	QI	DS3
HS	DS0	JE	DS1	TV	DS3
HW	DS0	QA	DS1	TZ	DS3
HY	DS0	QG	DS1	VR	DS3
IA	DS0	SY	DS1	ΥH	DS3
ΙΒ	DS0	UF	DS1	ΥI	DS3
ID	DS0	UH	DS1		
PC	DS0	UM	DS1		
QB	DS0	VS	DS1		
QD	DS0	VW	DS1		
QE	DS0	VX	DS1		

QJ	DS0	VY	DS1	
QK	DS0	YB	DS1	
QL	DS0			
QR	DS0			
QS	DS0			

Log files – the daily files produced by the robots that include the records for all of the requests issued during the report period and the resulting dispositions and response times.

There are three types of log files that are used to create the text files are:

```
rr_xxx.log*
rrr_xxx.dlg
rrr_xxx.dtm
```

*rr and rrr = the robot designation and xxx = the cycle date

The EnView application creates the log files for the OSS. A REXX program creates the log files on the DCAS side. Currently the log files are stored on the robots for five days; however, they are FTP'd (File Transfer Protocol) daily to multiple locations including the EnView server for the North where they remain until written to compact disk. Once written to compact disk, copies are maintained by EnView and Wholesale Metrics personnel. The log files are automatically FTP'd to the EnView reports server & Wholesale metrics server each morning.

Text files — Text files are produced from the log files that are FTP'd daily from the EnView server to the Metrics PC for analysis and reporting. Daily average response times are calculated by the EnView program and are included in the text files. The following text files are FTP'd daily:

```
N_xxx.rec* All of the requests issued during the report period.

N_xxx.rep Average response times by hour and day for the report period.

N_xxx.sum Hourly counts by transaction type for the 24-hour period

N_xxx.all All of the requests issued during the 24-hour period including response times.

*xxx=the cycle date
```

Excel workbook – the format for VZ internal daily distribution and reporting of the official response time results.
Monthly average response times are calculated in the Excel workbook Production by State STATE Master.xls.
The following Excel workbook is updated and distributed internally each business day:
Sentl-no.xls

Transactions included in the EnView text_files:

BOSS1_T_BCO OSS -	 BOSS Product and Services Availability Simple Business
BOSS1_T_CCO OSS -	BOSS Product and Services Availability Complex Business
BOSS1_T_CSR OSS =	- BOSS Customer Service Record
BOSS1_T_RCO OSS -	- BOSS Product and Services Availability Residence
BOSS2_T_CSR OSS =	- BOSS Customer Service Record
DCAS68_ADR	DCAS - Address Validation
DCAS68_ADRTNR	DCAS - Telephone Number Restore
DCAS68_ADRTNS	DCAS - Telephone Number Select
DCAS68_CSR	DCAS - Customer Service Record
DCAS68_DDA	DCAS - Due Data Availability
DCAS68_PSA	DCAS - Product and Services Availability
PREMIS_NE_T_REQPREM	OSS - PREMIS Address Validation
PREMIS_NE_REQTNR	OSS - PREMIS Telephone Number Restore
PREMIS_NE_REQTNS	OSS - PREMIS Telephone Number Select
SOP_T_WLU	OSS - SOP Due Date Availability

NAK - No Acknowledgement - the request file contains an error (bad transmission) as received by the DCAS host (DCAS only)

SEM – System Error Message – the request file contains a syntax mistake or OSS is unavailable (DCAS only) ACK – Acknowledgement – the request file is accepted by the DCAS host (DCAS only)

TIMEOUT – neither a SEM (DCAS) nor an indication of a successful response is received by the robot within a predetermined amount of time. (DCAS and OSS)

Appendix C Pre-Ordering EnView Additional Details (continued)

Timeouts for the DCAS transactions are set at 60 330 seconds.

The following transactions and response time differences are measured and reported for PreOrder response times:

Customer Service Record

DCAS68_CSR_region specific wholesale CSR BOSS1_T_CSR region specific retail CSR Difference

Address Validation

DCAS68_ADR region specific wholesale ADV
PREMIS_NE_T_REQPREM region specific retail ADV
Difference

Due Date Availability

DCAS68_DDA region specific wholesale DDA SOP_T_WLU region specific retail DDA Difference

Telephone Number Select

DCAS68_ADRTNS region specific wholesale TNS PREMIS_NE_REQTNS region specific retail TNS Difference

Product and Services Availability

DCAS68_PSA region specific wholesale PSABOSS1_T_BCO region specific retail PSADifference

Basic Loop Qualification

Region specific wholesale LXR Region specific retail LXR

ENVIEW PROCESS - NOTES:

There are currently two robots that log into applications and execute transactions for the PreOrder response time measurement process. The EnView process and the resulting response times are common to the VZ North South footprint due to the commonality of the interface. Transactions are executed through customizable scripts created for each application based on replications of actual transactions of a Verizon service representative using the OSS and of a CLEC representative accessing the OSS through the Wholesale interfaces. The ROBOT creates log records that show whether the transaction was successful or failed, and records transaction response times.

The robot sends the wholesale transactions to the same wholesale interfaces that the customers use. There is no difference between the processing of the EnView transactions and those submitted by the CLECs through the interface and back-end applications. Corresponding transactions are sent directly by EnView to the OSS as well.

The process is active on a 7 day by 24-hour basis. However, only those transactions included in the report period as defined above are recorded and documented as PreOrder response times.

Data from the EnView robot log files is processed daily and average response times by hour and by day for each of the above transactions is calculated and included in the text files that are used for input to the Excel workbooks. These daily response times are subsequently averaged by month in the Excel workbook.

Appendix C Pre-Ordering EnView Additional Details (continued)

The resulting averages and the differences between the corresponding retail and wholesale average response times are reported and distributed daily.

Errors and Timeouts are not included in these calculations. They are removed from the queue and reported separately in the text files. ACKs, by themselves, are also not included in the calculations but the acknowledgement process is part of the overall process for a successful transaction.

Daily average response times as received in the EnView log files are reported "as is" in the Excel workbook with the exception of Telephone Number Select for OSS. It is not possible to do a Telephone Number Select transaction in DCAS Request Manager without including an Address Validation. However, in the OSS these transactions are separate and manual effort is required to update the service rep's screen in between actions.

In order to make a like for like comparison between DCAS Request Manager and the OSS an adjustment is made to the response times prior to calculating the DCAS Request Manager and OSS response time differences. The daily average response time for the PREMIS_Live Wire Telephone Number Select transaction. Monthly average response times and differences are calculated and reported at the close of each month. The monthly average is calculated for each transaction type by averaging all of the daily average response times. Monthly results include response times for each of the PreOrder transaction types, and a Non-CSR Combined average response time for the non-CSR transactions. This is calculated by averaging each of the monthly averages for the non-CSR transactions. Transaction count weighting factors are not included in the averaging process.

2001 Holiday Schedule - Verizon East

(No staffing or limited staffing of work units.)

<u>The Verizon holiday schedule is located on the Verizon Wholesale Web Site:</u> URL- www.bell-atl.com/wholesale/html/resources.htm

Note: Holidays may vary based on collective bargaining agreements. Holidays apply to work unit based on the state in which it is located.

Summary of Bona Fide Request Process (BFR)

The following is the Bona Fid Request (BFR) Process that Verizon (VZ) utilizes to consider requests for interconnections, access to new unbundled network elements, or new services for resale. The following is Verizon's BFR Process.

- 1. VZ shall promptly consider and analyze requests for interconnection, access to UNEs or new services for resale through the submission of a BFR.
- 2. A BFR shall be submitted in writing and shall include a technical description.
- 3. The requesting CLEC may cancel a BFR at any time with no charge for the Preliminary Report. However, the requesting party shall pay VZ reasonable and demonstrable costs of processing and/or implementing the BFR up to the date of the cancellation.
- 4. Within 10 Business Days of its receipt, VZ shall acknowledge receipt of the BFR
- 5. Except under extraordinary circumstances, within 30 days of its receipt of a BFR, VZ shall provide to the requesting CLEC a Preliminary Report including analysis of such BFR. The preliminary analysis shall confirm that VZ will offer the arrangement, service or element or will provide a detailed explanation that it is not technically feasible and/or that the request does not qualify to be provided under the Act. If the request is found to be valid, the Preliminary report shall include a time and cost estimate for completion of any Detailed Report.
- 6. If VZ determines that the BFR is technically feasible and otherwise qualifies under the Act, it shall promptly proceed with developing the BFR upon receipt of written authorization, together with the payment of the cost estimate for completion of the BFR, from the requesting CLEC. When it receives such authorization, VZ shall promptly develop the requested service, element or interconnection arrangement, determine its availability, calculate the applicable prices and establish installation intervals.
- 7. Unless the Parties otherwise agree, the Requested service, element or interconnection arrangement must be priced in accordance with Section 252(d)(1) of the Act.
- 8. As soon as feasible, but no later than 90 days after its receipt of authorization to proceed with developing the BFR, VZ shall provide to the Requesting CLEC a Detailed Report containing the complete BFR request quote which will include, at a minimum, a description of each request, the availability, the applicable rates and the installation intervals.
- 9. Within 90 days of receipt of the Detailed Report, the Requesting CLEC must either confirm its order for the BFR pursuant to the BFR quote or seek arbitration by the Commission pursuant to Section 252 of the Act.
- 10. If a Party to a BFR believes that the other Party is not requesting, negotiating or processing the BFR in good faith, or disputes a determination, or price or cost quote, or is failing to act in accordance with Section 251 of the Act, such Party may seek mediation or arbitration by the Commission pursuant to Section 252 of the Act.

LOCAL NUMBER PORTABILITY/HOT-CUT

LNP/Hot-Cut Process

The CLEC sends an LSR to VZ for a loop hot-cut with LNP. VZ returns a FOC to the CLEC with the date and time for the cutover. VZ also sends a message via the SOA (service order activation system) to NPAC indicating that the affected telephone number will be made available for LNP activation. This message creates a subscription version in the NPAC. VZ sends the message to NPAC at the same time that the service order is issued. This is mechanized for all orders except DID/CTX. If the CLEC uses DCAS Request Manager or other mechanized interface for LSR, the FOC, (or more correctly the LSC), will be returned to the CLEC the same time the service order is issued and the message goes to the NPAC. If a paper LSR is used, VZ NY will send the LSC back to the CLEC after VZ NY issues the order.

The first company that sends the subscription version to NPAC starts the NPAC concurrence timers. Since VZ's internal service order generates the FOC and NPAC create message at the same time, VZ's activity starts the NPAC timers. This process is outlined in the industry agreed upon NANC LNP Process Flows. The CLEC/new service provider has 18 hours to enter their subscription from the time the VZ NY subscription version is sent to the NPAC. NPAC hours are from 7 am to 7 pm Central Time excluding weekends and holidays. If the CLEC does not enter a subscription within the 18 hours, then their subscription will be canceled. This timing issue and NPAC subscription version cancellation was a problem for many CLECS when they first started porting with the LNP process.

Upon receipt of the FOC, the CLEC sends a message to NPAC specifying the date and time for the activation of LNP. Alternatively, the CLEC may specify only the date initially and, when they are ready to port, a second message to NPAC to activate LNP in real time. VZ has observed that most CLECs' initial subscription entered into NPAC via SOA contains the date due only. On the date due the CLEC will send an ACTIVATE message via SOA to NPAC when they are ready to port the Verizon number. Two basic scenarios may occur.

Scenario 1 - PORT OUT of the Verizon number associated with an Unbundled Loop HOT CUT conversion: Prior to the due date, the VZ Regional CLEC Co-ordination Center (RCCC) will arrange with internal VZ personnel to have the cable pairs moved on the agreed upon due date at specific time known as the frame due time (FDT). In addition, at least one day prior to the due date VZ will install a 10 digit unconditional trigger on the VZ line (during the porting process, it is VZ's policy to place the 10 digit trigger on all non-Centrex/DID numbers to direct all calls to the number being ported to be queried at the LNP data base before any call termination is attempted). For all HOT CUTS (with or without LNP or INP) of unbundled loops, the CLEC is required to have dial tone at their collocation 48 hours before the DD. The RCCC will verify dialtone 24 hours before the cutover and notify the CLEC of any problems found. On the due date, the RCCC will call the CLEC 1 hour before the scheduled cutover time to ensure that both parties are ready. If the CLEC indicates that the port should proceed, VZ will cut the loop at the scheduled time and report the completion to the CLEC within 60 minutes. Upon notification of the completion, the CLEC would send a notice to NPAC to activate LNP in real time, if the time was not initially specified. As long as a trigger has been placed on the Verizon line, this PORT OUT is under the total control of the CLEC. However, the line should be ported at the FDT (Frame Due Time) of the Unbundled Loop conversion to prevent any service interruptions.

Scenario 2 - PORT OUT of the Verizon number NOT associated with an Unbundled Loop HOT CUT: VZ will issue service orders to place the 10-digit trigger on the line at least one day prior to the date due and to remove the end user telephone number translation from the VZ switch at 11:59 pm using the FDT. For informational purposes the CLEC requested work completion time will be carried on the VZ service order. At the same time the service orders are issued, VZ will send the FOC to the CLEC and the create subscription version to the NPAC. The NPAC 18-hour timers will start at this point. Since no hotcut is involved, once the 10 digit trigger is added to the VZ telephone number, the CLEC has control of the porting activity and there should be no customer service interruption if the CLEC completes their work by 11:59pm on the confirmed due date. If the

10 digit trigger is not applied because the VZ account is Centrex or DID, then the FDT would govern the porting out activity and VZ will handle in the same manner as a hotcut.

Appendix E LNP Process

Note that triggers can be placed on all lines with OE (Office equipment). Centrex and DID service requires coordination between the CLEC and the RCCC at the FDT. VZ places the 10-digit trigger on all non-Centrex/DID porting orders. The 10-digit trigger enables intraswitch call origination and donor switch query calls to be routed to the CLEC's switch even if the line is not disconnected from the switch. This will happen only if the CLEC has updated the LNP database via an NPAC activation message. Basically the 10 digit trigger mitigates the need to closely co-ordinate the disconnect of the line with the CLEC. VZ activates the 10 digit trigger at least 1 day prior to the porting due date; it is de-activated when the TN translations are removed from the switch. The 10-digit trigger has no other network purpose.

On all ports without a loop and with a trigger, the VZ service order will carry

a FDT of 11:59 PM. The trigger will not be deactivated until that time. Therefore, the CLEC is able to use the full day of the due date to complete their work activities (switch translations, loop installs, NPAC activate, etc.) before the VZ line is disconnected from the switch.

ENHANCED 911 DATABASE UPDATES

Background:

The E911 database identifies the street address associated with each telephone number, thus enabling PSAPs to automatically identify an emergency caller's location, if the emergency caller is unable to communicate this information verbally.

The E911 database is owned and maintained by VZ in those counties where VZ is the incumbent telephone company or has been contracted by the municipality or state to be the lead telephone company or database administrator. However, the company that provides dial tone to a telephone number is responsible for updating the E911 database when there is service order activity. VZ is responsible for updating the E911 database for their own customers, for customers of CLECs served by resale of VZ's local service or by VZ's UNEs. CLECs are responsible for updating the E911 database for customers that receive dial tone via CLECs' switching equipment.

The E911 database is updated by means of an electronic interface. VZ updates the E911 database once each evening from the VZ service order systems through a file transfer protocol. Facilities based CLECs use PS/ALI and have the opportunity to upload their records 10 times per day. VZ developed this interface for PBX's and subsequently it is available for use by CLECs so that they can update the E911 database when they provide the dial tone.

When VZ or a CLEC attempts to update the E911 database, the address is compared against a range of permissible street addresses contained in the Master Street Address Guide (MSAG). The MSAG is compiled by the E911 municipalities and consists of address information provided by each of the E911 municipalities. Thus, the MSAG is only as accurate as the information supplied by the municipalities.

If the E911 database cannot accept the update, either because of a discrepancy with MSAG or for some other reason, the E911 database generates an error message that identifies the nature of the problem. The Telephone Company attempting to update the database must then correct the problem and resubmit the information.

Local Number Portability (LNP) requires additional steps pursuant to procedures developed by the National Emergency Number Association called "NENA Recommended Standards for Service Provider Local Number Portability." The donor company must issue an "unlock" order to the E911 database to make the telephone number available to the recipient company, and the recipient company must issue a "migrate" order to the E911 database to identify the new dial tone provider. The E911 database does not have the updated customer's carrier identification code until both orders are issued in the proper sequence. Nevertheless, the customer's E911 record is present in the database and the customer's access to E911 service is unaffected. The responsibilities and procedures for updating the E911 database are described in VZ's CLEC Handbook and E911 PS/ALI Guide. Both documents are available to the public at VZ's website.

8.8 (Repair) Disposition Codes

Disposition Codes exist to identify defects in equipment or facilities and customer error or misuse of Telephone Company (TELCO) and Customer Equipment.

8.8.1 DISPOSITION CODES NORTH

Disposition Code Table		
Disposition Code	Trouble was found in:	
03xx	Verizon Wire	
0371	Protector	
0372	Ground Wire	
0373	Radio Suppressor	
0381/0382	Aerial Drop Wire	
0383/0384	Buried Drop Wire	
0385	Block/Bridle Wire	
0391-97	Network Interface Device	
04xx	Verizon Cable Plant	
040x	Pair Transferred	
041x	Sheath, Case, End Cap, etc.	
042x	Closure/Splice Case	
043x	Terminal	
044x	Fiber Optic Cable	
045x	Fiber Termination	
046x	Fiber Splice	
047x	Pair Gain Analog	
048x	Pair Gain Digital	
049x	Cable Misc. (Pole, Guy, Trench, etc.)	
05xx	Verizon Central Office	
051x	Switch	
052x	Translations (Software)	
053/054x	Frame (Hardware)	
055x	Power Equipment	
056x	Central Office Misc. Equipment	

Disposition Code Table			
Disposition Code Trouble was found in:			
057x	Central Office Special Services Equipment		
058x	Central Office Voice Mail Service Equipment		
12xx	CPE (Customer Premises Equipment)		
1220	Dispatched Out on a demand dispatch/trouble proven		
	into CPE/IDC applies.		
1232	Dispatched In/trouble proven in CLEC portion of		
	circuit/IDC applies.		
1235	Demand dispatch for cooperative test IDC applies.		
1239	Dispatch Out on a demand dispatch/proven into CLEC		
	portion of circuit/IDC applies.		
1239	Dispatch Out on a demand dispatch/no access to		
	premises/CNR applies.		
1296	Dispatched In/trouble not found within Verizon's		
	Central Office/IDC applies.		

8.9.1 CAUSE CODE TABLE - NORTH

The Cause Code describes the trouble's cause.

Cause Code Table		
Cause Code	Trouble was caused by	
1XX	Employee	
2XX	Non-employee	
3XX	Plant Equipment	
4XX	Weather	
5XX	Other	
6XX	Miscellaneous	
600	Unknown	
610	Came Clear	
698	CPE Trouble – IDC Incurred	
699	CPE Trouble – Auto Generated IDC Incurred	

A list of orders that flow-through is set out on Verizon's website at http://www.verizon.com/wholesale/html/cd_supp_document.htm. The list of orders that flow-through is subject to change from time-to-time in accordance with applicable change control processes.

VERIZON PRODUCT	ORDERING SCENARIO	NORTH FLOWTHROUGH
Resale		
	New Connect: business or residence, straight line main listing	Level 5
	New Connect with hunting	Level 5, Series & circular only
	As Specified, Add or Drop Line with hunting changes	Level 5
	As-Is Residence and Business	Level 5
	As-Is w/Changes: involving Freeze PIC, PIC/ LPIC Change, Customized Routing, & Blocking	Level 5
	As Specified Full Migration	Level 5
	As Specified Partial Migration	Level 5
	As Specified drop a line, not the main	Level 5
	Post Migration Delete Account (disconnect of account)	Level 5
	Post Migration Change – Add or Drop Features (no change feature detail) This includes ADD of features on inscope list and DROP of any feature with the exception of Distinctive Ringing	Level 5
	Post Migration New/Add Lines	Level 5
	Post Migration Disconnect Lines	Level 5
	Post Migration PIC Change	Level 5
	Outside Moves (includes same or different TNs, same or different due dates, and dual service)	Level 5

Appendix H
Flow Through Ordering Scenarios

PRODUCT UNE Platform		
CT (ET MATOTIA		
	New Connect: business or residence, straight line main listing	Level 5
	As Specified, Add or Drop Line without hunting changes	Level 5
	As-Is Residence or Business	Level 5
1	As Is w/Changes: involving Freeze PIC, PIC/LPIC Change, Customized	Level 5
	Routing, & Blocking	
	As Specified (no disconnect of lines)	Level 5
	As Specified Full Migration	Level 5
	As Specified drop a line, not the main	Level 5
	Post Migration Delete Account (disconnect of account)	Level 5
	Post Migration Change - Add or Drop Features (no change feature detail) This includes ADD of features on inscope list and DROP of any feature with the exception of Distinctive Ringing	Level 5
	Post Migration New/Add Lines	Level 5
-	Post Migration Disconnect Lines	Level 5
1	Post Migration PIC Change	Level 5
	Post Migration SNP Deny (one-way & two-way)	Level 5
	Post Migration SNP Restore (one-way & two-way)	Level 5
	Post Migration Seasonal Suspend	Level 5
	Post Migration Seasonal Restore	Level 5
	Post Migration Short-Term	Level 5
	Post Migration TN Change (Non-BTN)	Level 5
	Resale to Platform Full Migration	Level 5
	Resale to Flationin Full Migration	Level 3
Basic 2 Wire Loop	N. C 101	T 15
	New Connect: 1-9 loops	Level 5
	Full Migration	Level 5
	Partial Migration (taking BTN = Level 2)	Level 5
	Post Migration New/Add Loops: 1-9 loops	Level 5
	Post Migration Delete Loops	Level 5
Premium 2 Wire Loop		
	New Connect: 1-9 loops	Level 5
	Post Migration New/Add Loops: 1-9 loops	Level 5
	Post Migration Delete Loops	Level 5
CSS 2 Wire Loop	D. M. C. D.L. I.	T 15
	Post Migration Delete Loops	Level 5
Basic 2 Wire M Loop		
	Post Migration Delete Loops	Level 5

Appendix H
Flow Through Ordering Scenarios

		Flow Through Ordening Scenarios
VERIZON PRODUCT	ORDERING SCENARIO	NORTH FLOWTHROUGH
INP		
	Delete INP Arrangement Only	Level 5
	Dorote II ii Timingomoni Omj	Bevere
Loop w/NP - No		
listing (LNP)		
	Full Migration	Level 5
	Partial Migration (taking BTN = Level 2)	Level 5
Standalone Number		
Portability (LNP)		
	Full Migration	Level 5
	Partial Migration (taking BTN = Level 2)	Level 5
Loop w/New /Change	e Main Straight Line Listing	
	New Connect: 1-9 loops	Level 5
	Full Migration	Level 5
	Partial Migration (taking BTN = Level 2)	Level 5
Platform combined v	 v / New Main Straight Line Listing	
	New Connect	Level 5
	Post Migration (additional listings only)	Level 5
Loop w/LNP combin	ed w/Main Straight Line Listing Change	
	Full Migration	Level 5
	Partial Migration (taking BTN = Level 2)	Level 5
Platform combined v	//Wain Straight Line Listing Change	
	As Specified (Full Migration)	Level 5
	Post Migration	Level 5

Appendix H
Flow Through Ordering Scenarios

VERIZON PRODUCT	ORDERING SCENARIO	NORTH FLOWTHROUGH
Loop w/LNP combin	ned w/Listing As Is (No Change)	
	Full Migration	Level 5
	Partial Migration (taking BTN = Level 2)	Level 5
Platform combined w/Listing As Is		
	As-Is	Level 5
	As-Is w/Changes	Level 5
	As Specified (Full Migration)	Level 5
	Full Migration (No DL Form is required) Partial Migration (relian PTN Level 2)	Level 5
	Partial Migration (taking BTN = Level 2)	Level 5
Platform combin	red w/Delete Additional Listing	
	Post Migration	Level 5
Standalone Director Listing	У	
	UNE New Straight Line Listing, main listing	Level 5
	<u> </u>	Ec (Cl S
	UNE New Straight Line Listing, additional listing	Level 5
	UNE New Straight Line Listing, additional listing UNE Change Straight Line Listing, main listing	



Telecom Industry Services

CLEC Interconnection Trunking Forecast Guide

September 2000

Introduction

Introduction	The purpose of this CLEC Interconnection Trunking Forecast Guide and attached documents is to provide guidelines for the formats and language to be used in exchanges of forecast information between CLECs and Verizon. These guidelines in no way supersede any established or future Interconnection Agreements between Verizon and individual CLECs. The Verizon CLEC Interconnection Trunking Forecast Process is an interactive planning process between the CLECs and Verizon. This recommended process represents a work in progress and may be modified as appropriate.
Initial Implementation	The Trunk Forecasting Process was implemented to meet the requirements of Verizon's forecasting and capital budget process.
Evaluation	The Trunk Forecasting Process will be monitored by Verizon with input from all CLECs to evaluate the success of the forecast process.

CLEC Interconnection Trunking Forecast Process

Why Do We Need	1. To ensure that trunk groups do not exceed their design blocking thresholds.
Forecasts? 2. To ensure adequate infrastructure planning to meet customer service requiremen standard intervals. 3. CLECs and Verizon analyze forecast information in order to: • Design optimum network infrastructure. • Prioritize and allocate limited capital funds for next year's switching, transport projects. • Allocate expense budgets and human resources.	
Impact of	Unforecasted Demand Forces:
Unforecasted	 Blockage that exceeds design blocking thresholds.
Demand	 Redesign of infrastructure network in various areas.
	Sub-optimization of planned aggregate infrastructure.
	 Reallocation of funds for infrastructure.
	 Reprioritizing, rescheduling, or cancellation of planned projects.
	Reallocation of human resources.

APPENDIX I Part I Trunk Forecasting Guide

When Will This Trunk Forecast be Provided?	On a semiannual basis, CLECs will be requested to provide Verizon with at least a two year detailed forecast of its traffic and volume requirements for all CLEC Interconnection Trunking. This should include requirements for both new growth and change in volumes.				
	This forecast must be provided on February 1 st and August 1 st each year.				
	To facilitate the forecast, Verizon's TIS Account Team will send out a letter with a 3.5Mb diskette (with an attached VZ Excel forecast spreadsheet) to each CLEC				
How will feedback be provided on the	Verizon will review the forecast and provide feedback to individual CLECs as appropriate.				
process?	A CLEC or Verizon can also request a meeting to discuss the forecast process.				
Degree of Confidence	The CLEC should strive to provide Verizon with a high degree of accuracy. The remarks section of forecast template should be used to identify high priority requirements and indicate special considerations. Verizon may use the remarks as a guide for discussions at joint meetings.				
Distribution of the Official Forecast	Forecasts will only be made available to those parties within Verizon with a need to know and will be in compliance with the appropriate Interconnection Agreements. For example, Verizon-Telecom Industry Services, Verizon - Network Forecasting and Network Provisioning groups.				
	Individual CLEC forecasts will not be shared with other CLECs or Verizon Retail.				
How should each party provide	Each party will notify the other when they project a significant short term spike in demand which has the potential to impact infrastructure and/or workforce balance.				
feedback to the other of a spike in demand/project that	This notification will be done via letter to the other party (ex. CLEC obtains a new ISP) via the respective account managers. A copy may be sent to the appropriate provisioning group in Verizon.				
is Unforecasted for the current year?	For example, significant changes can include : • A new CLEC POI				
·	 Advancing or delaying significant trunk requirements from one year to another Unforecasted trunking requirements New Switch 				
Joint Network	May be called by either party as required. These meetings will include engineering representatives				
Planning Reviews	from each party. May include discussions on changes in POI, additional transport requirements, additional trunking requirements, significant advances or delays in requirements from one year to another.				

CLEC Interconnection Trunking Forecast Guide

Forecast Template Field Definitions

Header Section

1. CLEC Name:

DEFINITION: This field identifies the Telecommunications Carrier issuing the trunk forecast.

EXAMPLE: ABC Telecom

2. Forecast Issue Date:

DEFINITION: This field identifies the date the trunk forecast is issued by the Telecommunications Carrier.

EXAMPLE: 2/1/98

3. **Issued By:**

DEFINITION: This field identifies the name and the title of the person issuing the Forecast for the CLEC.

USAGE: This information will be used by Verizon to contact the CLEC if additional information concerning the forecast is required.

EXAMPLE: Jane Doe, Network Manager

4. Reach Number:

DEFINITION: This field identifies the Telephone Reach Number of the CLEC employee who originated this trunk forecast. The field should contain a three-digit area code, three-digit exchange, and a four-digit line number.

USAGE: This information will be used by Verizon to contact the CLEC if additional information concerning the forecast is required.

EXAMPLE: 1-800-555-1212

5. **LATA:**

DEFINITION: This field indicates the LATA which the trunk group(s) forecast will serve. A separate forecast template should be prepared for each LATA for which the CLEC is providing trunk forecasts.

USAGE: This information will be used to distribute the forecasts to appropriate personnel within Verizon.

EXAMPLE: 132

Trunk Group Specific Section

6. ACTL (Access Customer Terminal Location / POI (Point of Interface):

DEFINITION: This field identifies the CLLI Code of the Terminal Location / POI of the CLEC providing the IntraLata Service. If the CLEC does not have a CLLI Code for a particular ACTL / POI, the CLEC should contact their Verizon account manager to obtain a code prior to the submission of the trunk forecast.

USAGE: This field identifies the physical drop-off point of traffic to the CLEC.

EXAMPLE: GRCYNYAANMD

7. TSC (Two Six Code) / NEW:

DEFINITION: This field identifies the unique number assigned to the Trunk Group by Verizon. **For new trunk groups, indicate "New" in the field.**

USAGE: This field assures that Verizon and the CLEC are referencing the appropriate trunk group.

EXAMPLE: AQ123456

8. Verizon CLLI:

DEFINITION: This field is the eleven (11) character CLLI (Common Language Location Identification) Code of the Verizon switch.

USAGE: The CLLI identifies the Verizon switch in unique terms.

EXAMPLE: GRCYNYCG02T

9A. TO (Traffic Origination)

DEFINITION: This field is used to identify the direction of traffic for each trunk group between Verizon and the CLEC.

USAGE: The following codes should be used. VZ= Traffic originates with Verizon, CL= Traffic originates with CLEC, 2W = Two Way Traffic

EXAMPLE: VZ, CL, 2W

9. **DS** (Direction and Type of Signaling)

DEFINITION: This field is a two character code which identifies the direction of traffic movement for trunk groups and the type of pulsing signals between the Verizon and CLEC location. Refer to Bellcore standard BR756-350-522 Issue3, Section 2, January 1989 for a complete list of definitions. The following table represents the most common selections:

DS	Description
MM	Two way MF pulsing
-M	MF pulsing from CLEC to Bell Atlantic
M-	MF pulsing from Bell Atlantic to CLEC
77	Two way SS#7 pulsing
-7	SS#7 pulsing from CLEC to Bell Atlantic
7-	SS#7 pulsing from Bell Atlantic to CLEC

USAGE: This field is required to help identify the components necessary to build the trunk group.

EXAMPLE: MM

10. CLEC SWITCH CLLI:

DEFINITION: This field is the eleven (11) character CLLI code of the CLEC Switch.

USAGE: The CLLI identifies the CLEC switch in unique terms.

EXAMPLE: GRCYNYAADS0

11. INTERFACE TYPE (Point of Interconnection)

DEFINITION: This element describes the Interface Group desired for this traffic. These Groups relate to the CLEC POI Interface Groups for Switched Access Service.

Interface	CLEC/Verizon Point of		
Type	Interconnection		
DS1	DS1 Level High Speed Digital (1.544		
	MBPS)		
DS3	DS3 Level High Speed Digital (44.73)		
	MBPS)		

USAGE: This field is required on all documents.

EXAMPLE: DS1

12. 56 KB or 64 Clear Channel:

DEFINITION: This field defines the requirement for either 56KB or 64 clear channel on this trunk group.

USAGE: This field is required to help identify the components necessary to build the trunk group.

EXAMPLE: 56 or 64

Current Year Trunk Requirements

13. Trunks In-Service As Of Forecast Issue Date:

DEFINITION: This field identifies the number of **DS0** trunks In Service for this trunk group as of the date of the forecast.

USAGE: This information gives Verizon evaluates the starting point for this forecast.

EXAMPLE: 192

14. 1Q FCST, 2Q FCST, 3Q FCST, 4Q FCST:

DEFINITION: These fields indicate the cumulative trunk quantity forecasted for each quarter of the current year. Quantities indicate end of quarter requirements. As quarterly updates are provided, fields for past quarters should be used to indicate actual in-service amounts.

USAGE: This information will identify any changes in requirements for the current year.

EXAMPLE: 192 Trunks (Only the number of DS0 trunks required)

Trunk Forecast Requirements - Current Year + 1

15. **1Q**, **2Q**, **3Q**, **4Q**:

DEFINITION: These fields indicate the cumulative trunk quantities forecasted to be required for the First Future Year (Current Year +1) by quarter for that year. Quantities indicate end of quarter requirements.

USAGE: This information provides and indication of timing as well as volumes for the forecast year.

EXAMPLE: 216 Trunks (Only the number of DS0 trunks required)

16. Trunk Forecast Requirements - Current Year + 2:

DEFINITION: This field indicates the cumulative trunk quantities forecasted to be required for the second future Year (Current Year +2) as of the end of the year.

USAGE: This information provides volumes for the forecast year.

EXAMPLE: 216 Trunks (Only the number of DS0 trunks required)

Other

17. **REMARKS**:

DEFINITION: This field is used to expand upon/clarify-forecast data for each trunk group. It should be used to identify the sizing and timing of major projects, major shifts in demand, new switches etc.

USAGE: This field should be used to identify high priority requirements and other forecast items to be included in correspondence and discussions with Verizon.

EXAMPLE: Will be establishing new POI in late in year 2000.



CLECs shall comply with this Guide.



Collocation Forecast Guide

September 2000

Appendix J Part I

Collocation Forecasting Guide

Introduction

	iiiti oaaotioi	•
Introduction		The purpose of this CLEC Collocation Forecast Guide and attached exhibits is to provide guidelines for the formats and language to be used in exchanges of collocation forecast information between CLECs and Verizon. These guidelines in no way supersede any established or future Interconnection Agreements between Verizon and individual CLECs. These guidelines in no way supercede any regulatory orders or tariff provisions related to collocation.
		The development of the CLEC Collocation Forecast process is a collaborative initiative between CLECs and Verizon. It is being developed in an effort to improve the network planning process for CLECs and Verizon. In addition to network planning, another goal of the process is to improve the quality and timeliness of industry information regarding space availability in particular Verizon Central Office locations. The design of the Guide is based on the successful New York CLEC Interconnection Trunk

Forecast Guide. This recommended process may be modified as appropriate.

CLEC Collocation Forecast Process

Why are forecasts required?	To ensure adequate infrastructure planning to meet customer service requirements within standard intervals.
	CLECs and Verizon analyze forecast information in order to:
	Design optimum network infrastructure.
	 Prioritize and allocate limited capital funds for future projects.
	Allocate expense budgets and human resources.
Impact of	Unforecasted collocation demand causes:
unforecasted	• Delays in cage construction.
demand	 Delays in meeting power requirements.
	Delays in conditioning space in Central Offices.
	Reallocation of capital funding for buildings work.
	• Excessive expense for unplanned construction.
	Reprioritizing, rescheduling, or cancellation of planned projects.
	Reallocation of human resources.
When will this	On a semi-annual basis, CLECs will be requested to provide Verizon with a two year detailed
collocation forecast	forecast of its physical and virtual collocation requirements. This should include
be provided to	requirements for new growth, changes from previously provided forecasts and deletions from
Verizon?	previously provided forecasts.
	This forecast must be provided no later than February 1 st and August 1 st of each year in
	accordance with the Verizon Telecom Industry Services semi-annual forecast cycle. To the

How information will be provided?	extent that a CLEC has significant modifications to a previously provided forecast, or is a new entrant, out-of-cycle forecasts will always be accepted by Verizon and will be used for planning purposes. To facilitate CLEC collocation forecasts, Verizon's TIS Account Team will send CLECs a forecast request letter along with a floppy diskette which will contain a collocation template. CLECs may request meetings with Verizon to discuss the collocation process.
	Information on available space in Verizon Central Offices will be provided via the TIS web site.
Are there special requirements for virtual collocation?	It is important to identify the type of virtual collocation equipment that will be deployed. This will enable Verizon to plan for any provisioning or training requirements for non-standard equipment. See template instruction #17 and the attached exhibits.
Degree of confidence	The CLEC should strive to provide Verizon with a high degree of accuracy in the timing, location and sizing of collocation projects. Special attention should be paid to the information provided for Year 1, in accordance with a forecasting carrier's current business plan.
Distribution of the official forecast	Forecasts will only be made available to those parties within Verizon with a need to know. For example, Verizon-Telecom Industry Services, Verizon-Network Forecasting and Verizon-Network Provisioning groups will be receiving this forecast information. Individual CLEC forecasts will not be shared with other CLECs or Verizon Retail Marketing organizations.
How should each party provide information to the other regarding an out-of-cycle change in demand that is not	During the time period between forecast cycles, each party will notify the other when they project a significant change in demand that has the potential to impact infrastructure and/or workforce balance. Special attention should be paid to changes in a Year 1 forecast. Notification from CLECs, via E-mail and hard copy, should be directed to the respective Verizon Account Manager and Verizon Collocation Project Manager
forecasted in the current Feb 1 st or Aug 1 st view?	Examples of changes can include: • A new CLEC requirement for physical or virtual collocation. • A change in "Application" or "In Service" month or year • A deletion of previously forecasted demand. • A change in the status of a Verizon Central Office.
What should a CLEC do if there is no change in a forecast provided six months earlier?	The CLEC should always send their most recent forecast to Verizon. If there are no changes, the CLEC should simply re-send the document and provide an affirmative statement that there are no changes to the previously provided forecast. The affirmative statement will eliminate confusion and save time for all parties.
Joint network planning reviews	May be called by either party as required. These meetings will include network operations and/or project management representatives from each party. These reviews may be scheduled to discuss the significant forecast changes cited above.

CLEC Interconnection Collocation Forecast Guide Forecast Template Field Definitions

Header Section (See Exhibits for examples)

1. Company Name:

DEFINITION: This field identifies the Competitive Local Exchange Carrier (CLEC) issuing the collocation forecast.

USAGE: Used by Verizon to identify individual carrier forecasts.

EXAMPLE: ABC Telecom

2. Company Contact Person:

DEFINITION: This field identifies the individual at the CLEC responsible to submit the forecast and act as a contact person for Verizon.

USAGE: This information will be used by Verizon to contact the CLEC if additional information concerning the forecast needs to be communicated.

EXAMPLE: Jane Doe

3. Company Contact Person Telephone Number:

DEFINITION: This field identifies the telephone number of the contact person.

USAGE: This information will be used by Verizon to contact the CLEC if additional information concerning the forecast needs to be communicated.

EXAMPLE: 212-555-1234

4. Verizon Account Manager:

DEFINITION: This field is used to identify the name of the Verizon Account Manager assigned to the CLEC providing the forecast.

USAGE: This information will be used by the CLEC and by Verizon to insure that the forecast is forwarded to the appropriate individual in Verizon.

EXAMPLE: Tom Dreyer

5. Date of This Forecast

DEFINITION: This field is used to identify the date on which the current forecast is being submitted.

USAGE: This information will be used by Verizon to distinguish the current view from previously provided forecast information.

EXAMPLE: August 1, 1999

6. Date of Previous Forecast

DEFINITION: This field is used to identify the most recent CLEC provided forecast date.

USAGE: This information will be used by Verizon to identify Adds, Changes and Deletions to previously forecasted information.

EXAMPLE: August 1, 1998

Collocation Specific Section

7. Request Number:

DEFINITION: This field is used to numerically identify each individual request that appears on the forecast template.

USAGE: This information will be used by Verizon to identify and refer to individual forecast requests.

EXAMPLE: 1, 2, 3 etc.

8. State:

DEFINITION: This field identifies the state for which the forecast is being made.

USAGE: This information will be used by Verizon to sort and to aggregate demand forecast data by state.

EXAMPLE: NY

9. LATA:

DEFINITION: This field identifies the LATA for which the forecast is being made.

USAGE: This information will be used by Verizon to sort and to aggregate demand forecast data by LATA.

EXAMPLE: 132

10. City/County

DEFINITION: This field identifies the city or county for which the forecast is being made.

USAGE: This information will be used by Verizon to sort and to aggregate demand forecast data by city and/or county.

EXAMPLE: Manhattan

11. Central Office CLLI Code

DEFINITION: This field identifies the eight- (8) character CLLI (Common Language Location Identifier) code of the specific central office for which the forecast is being made.

USAGE: This information will be used by Verizon to sort and to aggregate demand forecast data by Verizon central office.

EXAMPLE: NYCMNY42

12. Quantity:

DEFINITION: This field identifies the quantity of offices the CLEC expects to apply for in a specific state, LATA, city or county when the CLEC has not yet determined the specific central offices where they will apply for collocation. If a specific CLLI code is supplied, this field will always be one (1).

USAGE: This information will be used by Verizon to aggregate demand by state, LATA, city/county when the CLEC is unsure of the exact offices that will be applied for.

EXAMPLE: 5

13. Application Month:

DEFINITION: This field identifies the month in which the CLEC plans to submit the application for collocation. The year that the application will be submitted is the forecast year shown at the top of the template, for example "1998". A separate template is required for each forecast year

USAGE: This information will be used by Verizon to sort and aggregate forecast demand data by application month.

EXAMPLE: August 1999

14. Requested In-Service Month

DEFINITION: This field identifies the month in which service is required. Requested In-service month is based upon the appropriate provisioning intervals and/or tariff provisions in specific jurisdictions and is dependent on what type of collocation is being requested.

USAGE: This information will be used by Verizon to sort and aggregate demand forecast data by requested In-Service month. Note: "In Service" month refers to the point in time when the collocation project is completed, turned over to the CLEC and capable of being occupied. For

Year 2 an attempt should be made to provide as much detailed information as possible. General information will be accepted for planning purposes.

EXAMPLE: January 1999

15. Type of Collocation (Physical or Virtual)

DEFINITION: This field identifies the type of collocation the CLEC plans to apply for.

USAGE: This information will be used by Verizon plan collocation space.

EXAMPLE: Physical

16. New Arrangement or Augment to Existing

DEFINITION: This field identifies whether the CLEC will be requesting a new collocation arrangement or is planning to augment an existing arrangement. Augments include expansions of existing cages, additional power requirements or additional cabling (DS1, DS3's, SVGAL etc.)

USAGE: This information will be used by Verizon to account for collocation requirements in planning collocation space, power plant growth, etc.

EXAMPLE: Power Augment

17. Floor Space in Sq. Ft. (Physical only)

DEFINITION: This field identifies the amount of square footage that will be requested for new physical collocation requests or expansion requests to existing arrangements. This field is not applicable when requesting virtual collocation.

USAGE: This information will be used by Verizon to plan collocation space.

EXAMPLE: 100 Sq. Ft.

18. Type of Equipment (Virtual Only)

DEFINITION: This field identifies the high level description of the type of equipment the CLEC will request to have installed in the virtual collocation arrangement. This information may also be supplied for physical collocation requests, but is not mandatory.

USAGE: Verizon will use this information for the planning of virtual collocation space requirements

EXAMPLE: OC48, SLC2000

19. Forecast Update Code

DEFINITION: This field categorizes the entry based on previously forecasted information.

USAGE: Verizon will use this information to synchronize new forecast entries with previously provided forecasts and collocation applications.

EXAMPLE: For an "Add" not previously forecasted enter "A"

For a "Change" to a previous forecast enter "C" For a "Delete" to a previous forecast enter "D"

Statistical Methodologies:

The incumbent LEC <u>Verizon</u> will use statistical methodologies as one means to determine if "parity" exists, or if the performance for CLECs is equivalent to the performance for the incumbent LEC. For performance measures where "parity" is the standard and sufficient sample size exists, the incumbent LEC <u>Verizon</u> will use the "modified Z statistic" proposed by a number of CLECs in LCUG (Local Competitors User Group). The specific formulas are detailed below:

Counted Variables:

$$Z = \frac{P_{INC} - P_{CLEC}}{\sqrt{P_{INC} \left(1 - P_{INC}\right) \left(\frac{1}{n_{INC}} + \frac{1}{n_{CLEC}}\right)}}$$

Measured Variables:

$$t = \frac{\overline{X}_{INC} - \overline{X}_{CLEC}}{\sqrt{S^2_{INC} \left(\frac{1}{n_{INC}} + \frac{1}{n_{CLEC}}\right)}}$$

Note: If the metric is one where a higher mean or higher percentage signifies better performance, the proportions (counted variables) or means (measured variables) in the numerator of the statistical formulas should be reversed.

Definitions:

Measured Variables are metrics of means or averages, such as mean time to repair, or average interval.

<u>Counted Variables</u> are metrics of proportions, such as percent measures.

X is defined as the average performance or mean of the sample

S² is defined as the standard deviation

n is defined as the sample size

p is defined as the proportion, for percentages 90% translates to a 0.90 proportion

A Z or t score of below -1.645 provides a 95% confidence level that the variables are different, or that they come from different processes.

Sample Size Requirements:

The standard \boldsymbol{Z} or \boldsymbol{t} statistic will be used for measures where "parity" is the standard, unless there is insufficient sample size. For measured variables, the minimum sample size for both the incumbent LEC Verizon and CLEC is 30. For counted variables, both $n_{INC}p_{INC}(1-p_{INC})$ and $n_{CLEC}p_{CLEC}(1-p_{CLEC})$ must be greater than or equal to 5. When the sample size requirement is not met, the incumbent LEC Verizon will do the following:

- a.) If the absolute performance for the CLEC is better than the incumbent LEC's Verizon performance, no statistical analysis is required.
- b.) If the performance is worse for the CLEC than for the incumbent LEC <u>Verizon</u>, the incumbent LEC <u>Verizon</u> will use the t distribution or binomial (counted or measured) until such time as a permutation

Appendix K Statistical Methodologies

test can be run in an automated fashion. If the performance is worse for the CLEC than for the incumbent LEC Verizon for a counted variable, the incumbent LEC Verizon will utilize the hypergeometric distribution, where calculable in an automated fashion in a manner that is contained within, or directly linked to the performance reporting spreadsheets, to produce the same result as would be obtained from the permutation test. The incumbent LEC Verizon will provide monthly updates regarding its progress in automating the permutation test for measured variables and for automating the permutation test for counted variables in those instances where the test in not calculable in a manner tied to the performance reporting spreadsheets.

- c.) If the t or binomial distribution show an "out of parity" result, the incumbent LEC Verizon will run the permutation test.
- d.) If the permutation test shows an "out of parity" condition, the incumbent LEC Verizon will perform a root cause analysis to determine cause. If the cause is the result of "clustering" within the data, the incumbent LEC Verizon will provide such documentation. The nature of the variables used in the performance measures is that they do not meet the requirements 100% of the time for any statistical testing. Individual data points are not independent. The primary example of such non-independence is a cable failure. If a particular CLEC has fewer than 30 troubles and all are within the same cable failure with long duration, the performance will appear out of parity. However, for all troubles, including the incumbent LEC's Verizon's troubles, within that individual event, the trouble duration is identical. Another example of clustering is if a CLEC has a small number of orders in a single location, with a facility problem. If this facility problem exists for all customers served by that cable and is longer than the average facility problem, the orders are not independent and clustering occurs. Finally, if root cause shows that the difference in performance is the result of CLEC behavior, the incumbent LEC Verizon will identify such behavior and work with the respective CLEC on corrective action.

INCUMBENT LEC VERIZON

Exceptions:

A key frailty of using statistics to evaluate parity is that a key assumption about the data, necessary to use statistics, is faulty. One such assumption is that the data is independent. Events included in the performance measures of provisioning and maintenance of telecommunication services are not independent. The lack of independence is referred to as "clustering" of data. Clustering occurs when individual items (orders, troubles etc.) are clustered together as one single event. This being the case, the incumbent LEC Verizon will file an exception to the performance scores if the following events occur:

- a.) Event Driven Clustering- Cable Failure: If a significant proportion (more than 30%) of a CLECs troubles are in a single cable failure, the incumbent LEC Verizon will provide the data demonstrating that all troubles within that failure, including the incumbent LEC's Verizon's troubles were resolved in an equivalent manner. Then, the incumbent LEC Verizon will provide the repair performance data with that cable failure performance excluded from the overall performance for both the CLEC and the incumbent LEC Verizon and the remaining troubles compared according to normal statistical methodologies.
- b.) Location Driven Clustering - Facility Problems: If a significant proportion (more than 30%) of a CLECs missed installation orders and resulting delay days were due to an individual location with a significant facility problem, the incumbent LEC Verizon will provide the data demonstrating that the orders were "clustered" in a single facility shortfall. Then, the incumbent LEC Verizon will provide the provisioning performance with that data excluded. Additional location driven clustering may be demonstrated by disaggregating performance into smaller geographic areas.
- c.) Time Driven Clustering - Single Day Events: If significant proportion (more than 30%)of CLEC activity, provisioning or maintenance, occur on a single day within a month, and that day represents an unusual amount of activity is in a single day, the incumbent LEC Verizon will provide the data demonstrating that the activity is on that day. The incumbent LEC Verizon will compare that single day's performance for the CLEC to incumbent LEC's Verizon's own performance. Then, the incumbent LEC Verizon will provide data with that day excluded from overall performance to demonstrate "parity".
- d.) <u>CLEC Actions</u>: If performance for any measure is impacted by unusual CLEC behavior, the incumbent <u>LEC Verizon</u> will bring such behavior to the attention of the CLEC to attempt resolution. Examples of CLEC behavior impacting performance results include order quality, causing excessive missed appointments, incorrect dispatch identification, resulting in excessive multiple dispatch and repeat reports, inappropriate X coding on orders, where extended due dates are desired, and delays in rescheduling appointments, when the incumbent <u>LEC Verizon</u> has missed an appointment. If such action negatively impacts performance, the incumbent <u>LEC Verizon</u> will provide appropriate detail documentation of the events and communication to the individual CLEC and the Commission.

Documentation:

The incumbent LEC <u>Verizon</u> will provide all details, ensuring protection of customer proprietary information to the CLEC and Commission. Details include, individual trouble reports, and orders with analysis of the incumbent LEC's <u>Verizon's</u> and CLEC performance. For cable failures, the incumbent LEC <u>Verizon</u> will provide appropriate documentation detailing all other troubles associated with that cable failure.

Appendix L

Note: Not all products listed in this appendix are offered in all jurisdictions.

Refer to the Verizon web-site:

http://www.bell-atl.com/wholesale

for Product Interval Summary and Product Specifications Information.

Note: Not all products listed in this appendix are offered in all jurisdictions.

Order Accuracy Measures:

In the order processing area two issues of concern are: (1) whether appropriate information is being recorded on the Order Confirmation ("LSRC") that VZ-NY is sending CLECs; and (2) whether the VZ-NY order correctly reflects what is included on the Local Service Request. VZ-NY will separately measure performance for order confirmation and order accuracy.

LSRC Accuracy:

Short Term Solution: (NY, CT, MA, RI, NH, ME, VT)

VZ will manually sample LSR's and compare to their associated LSRC. Eight or Nine (depending on the order type) key fields will be compared to ensure that the correct information is placed on the LSRC. These key fields are information that Verizon must provide. Information already provided by the CLEC, hence already known, is not included in these critical fields. These fields are detailed below according to specific order types.

LSC Confirmation/Order Types:

	Loop			LNP		Platform/PORTS			
	New	Change	Disc.	Port Out	Trigger	Directory List	New	Migrate	Disc
FIELD									
NAME									
PON	X	X	X	X	X	X	X	X	X
VER	X	X	X	X	X	X	X	X	X
ATN	X	X	X	X	X	X	X	X	X
CD/SENT	X	X	X	X	X	X	X	X	X
REP	X	X	X	X	X	X	X	X	X
TELNO	X	X	X	X	X	X	X	X	X
ECCKT	X								
SOID	X	X	X	X	X	X	X	X	X
SOID DD	X	X	X	X	X	X	X	X	X

Sampling methodology:

VZ will sample according to the centers that process CLEC orders, 20 LSRs per center. Samples will be identified using random number generation from DCAS. VZ will then print a copy of the FOC within 24 hours (or later if the standard is later for that service type) for that PON and manually evaluate it to determine if the information included is accurate. These centers are as follows:

Center	Product	State(s) Covered	
New York (West St.)	Resale	NY, CT	
New York (West St.)	UNE Loop/LNP	NY, CT, MA, RI, NH, ME, VT	

Boston (High St.)	UNE-P & Combinations	NY, CT, MA, RI, NH, ME, VT
Boston (Franklin St.)	Resale	MA, RI, NH, ME, VT

Long Term Solution: (NY, CT, MA, RI, NH, ME, VT)

Upon implementation of the "Request Manager" (formerly known as LSRM in the South states), VZ NY will have an automated capability to measure % LSRCs re-sent due to error. This capability currently exists in the Verizon South States.

Order Accuracy:

Permanent Solution:

Order accuracy performance will be completed using a manual sampling process whereby 20 completed Service Orders are selected each day using a random number generator within DCAS Request Manager. Verizon will print a copy of each Service Order and a copy of the last version of the associated LSR. The complexity of each order type precludes a complete list on a field by field basis for inclusion in this filing. However the specific fields to be addressed include:

- Billed Telephone Number
- RSID or AECN
- PON Number
- Telephone Number (if applicable, required for resold POTS, Platform and LNP/INP)
- Ported TN (if applicable, required for LNP/INP)
- Circuit ID (if applicable, required for specials and loops)
- Directory Listing Information (if included)
- E911 Listing Information (if changing and appropriate)
- Features (for Resale, UNE-P and Switching orders)
- Application Date
- Due Date
- Remarks (if applicable)

Includes all fields on service order that impact service. For example "optional fields" such as call forwarding to telephone number would be included as a "feature" field and be subject to review.

Table of Measures, Sub-Metrics and Product Disaggregation

Verizon VA will provide periodic status reports on the metrics to the Commission.



APPENDIX O

TEST DECK

PRE-ORDER AND ORDER WEIGHTS



ADDITIONAL PROVISIONS

- 1. Interpretation. These Carrier-to-Carrier Guidelines ("Guidelines") are intended to implement the order of the Commission, [insert citation], ("Order") (as amended from time-to-time), and other applicable orders of the Commission. The Guidelines shall be construed and implemented so as to be consistent with and implement the Order and other applicable orders of the Commission.
- 2. Changes. The Commission, in accordance with the procedures provided under applicable law, may modify the Guidelines, including, but not limited to, in order to conform the Guidelines to changes in Verizon's systems and processes.
- 3. **Skewed Data.** Verizon shall not be responsible for a failure to meet a performance standard, to the extent such failure was the result of: (a) a Force Majeure event; (b) a statistically invalid measurement; or, (c) Event Driven Clustering, Location Driven Clustering, Time Driven Clustering, or CLEC Actions, as described in Appendix K.

Force Majeure events include the following: (a) events or causes beyond the reasonable control of Verizon; or, (b) unusually severe weather conditions, earthquake, fire, explosion, flood, epidemic, war, revolution, civil disturbances, acts of public enemies, any law, order, regulation, ordinance or requirement of any governmental or legal body, strikes, labor slowdowns, picketing or boycotts, unavailability of equipment, parts or repairs thereof, or any acts of God.

If Verizon claims that it is excused under this Exhibit 1, Section 3 from meeting a performance standard, Verizon will submit notice to the Commission and all affected CLECs at the time that it submits the applicable monthly performance report. If any interested party wishes to dispute Verizon's claim, it must do so within thirty (30) calendar days after the monthly report is submitted to the Commission, by requesting the Commission to institute an appropriate proceeding to resolve the dispute.

4. Confidentiality.

(a) Verizon Information:

- (1) As used in this Section 4(a), the following terms have the meanings stated below:
 - (A) "Verizon Information:" (1) information contained in the report for Verizon Retail performance; (2) information contained in the report for Verizon Affiliate

 Aggregate performance; and, (3) any other information about or related to Verizon retail customers or Verizon Affiliates or service provided to Verizon retail customers or Verizon Affiliates (including, but not limited to, Verizon Advanced Data Inc.), disclosed to a CLEC in conjunction with the Guidelines.
 - (B) "Agent:" (1) an employee, agent, contractor or affiliate of a CLEC; and, (2) an employee of an agent, contractor or affiliate of a CLEC.
- (2) A CLEC may disclose Verizon Information to other persons only as follows: (1) to CLEC Agents who need to receive the Verizon Information for a use permitted by this Section 4(a); (2) to the Commission, the FCC, a court of competent jurisdiction, other governmental entity of competent jurisdiction, or an arbitrator or mediator, under seal or cover of a protective order or agreement, that reasonably protects the confidentiality and limits the use of the information; (3) as required by applicable law, under government seal or cover of a protective order, that reasonably protects the confidentiality and limits the use of the information; or, (4) as required or permitted by an agreement between Verizon and the CLEC. A CLEC may use Verizon Information only for the following purposes: (1) assessment of Verizon's performance in providing service; (2) assessment of Verizon's performance in complying with these Guidelines; (3) enforcement of the CLEC's rights under any performance assurance plan, an applicable agreement or tariff, or applicable law; (4) such other uses as may be required by applicable law or permitted by the Commission, the FCC, a court of competent jurisdiction, other governmental entity of competent jurisdiction, or an arbitrator or mediator, including, but not limited to, reporting to the Commission, the FCC, a court of competent jurisdiction, other governmental entity of competent jurisdiction, or an arbitrator or mediator; and, (5) such other uses as may be required or permitted by an agreement between Verizon and the CLEC. A CLEC's Agents shall be bound by the same restrictions on disclosure and use of Verizon Information as the CLEC is under this Section 4(a) and the CLEC shall require its Agents to comply with these restrictions.

<u>Draft 4/30/01</u> 54

_

¹ As used in this Section 4(a) definition of "Agent," an "affiliate of a CLEC" is a person that (directly or indirectly) controls, is controlled by, or is under common control with, the CLEC.

(3) Except as otherwise expressly required by applicable law, in providing performance reports to a CLEC and otherwise performing its obligations under the Guidelines, Verizon shall not be obligated, and may decline, to disclose to a CLEC any individually identifiable information pertaining to a person other than the CLEC, including, but not limited to, any other carrier customer of Verizon or any retail customer of Verizon.

(b) CLEC Information

- (1) As used in this Section (4)(b), the following terms have the meanings stated below:
 - (A) "CLEC Information:" information disclosed by Verizon to a CLEC in a report for CLEC Specific performance for that CLEC, while such information is in a CLEC individually identifiable form.
 - (B) "Agent:" (1) an employee, agent, contractor or affiliate of Verizon; and, (2) an employee of an agent, contractor or affiliate of Verizon.
- (2) Verizon may disclose CLEC Information to other persons only as follows: (1) to Verizon's Agents who need to receive the CLEC Information for a use permitted by this Section 4(b); (2) to the Commission, the FCC, a court of competent jurisdiction, other governmental entity of competent jurisdiction, or an arbitrator or mediator, under seal or cover of a protective order or agreement, that reasonably protects the confidentiality and limits the use of the information; (3) as required by applicable law, under government seal or cover of a protective order, that reasonably protects the confidentiality and limits the use of the information; or, (4) as required or permitted by an agreement between Verizon and the CLEC. Verizon may use CLEC Information only for the following purposes: (1) performing its obligations under the Guidelines; (2) assessment of Verizon's performance in providing service; (3) assessment of Verizon's performance in complying with these Guidelines; (4) enforcement of Verizon's rights these Guidelines, under any performance assurance plan, an applicable agreement or tariff, or applicable law; (5) provision of service to CLECs; (6) such other uses as may be required by applicable law or permitted by the Commission, the FCC, a court of competent jurisdiction, other governmental entity of competent jurisdiction, or an arbitrator or mediator, including, but not limited to, reporting to the Commission, the FCC, a court of competent jurisdiction, other governmental entity of competent jurisdiction, or an arbitrator or mediator; and, (7) such other uses as may be required or permitted by an agreement between Verizon and the CLEC. Verizon's Agents shall be bound by the same restrictions on disclosure and use of CLEC Information as Verizon is under this Section 4(b) and Verizon shall require its Agents to comply with these restrictions.

² As used in this Section 4(b) definition of "Agent," an "affiliate of Verizon" is a person that (directly or indirectly) controls, is controlled by, or is under common control with, Verizon.

Exceptions

The restrictions on disclosure and use of Verizon Information and CLEC Information stated in Sections 4(a) and 4(b), above shall not apply:

- (1) With regard to Verizon Information, if Verizon makes the Verizon Information publicly available; and,
- (2) With regard to CLEC Information, if the CLEC makes the CLEC Information publicly available.
- (d) This Section 4 is intended to be in addition to and not in derogation of any applicable law protecting the confidentiality of the information of a telecommunications carrier or the customers or users of a telecommunications carrier, including, but not limited to, 47 U.S.C. § 222. This Section 4 shall not be construed as permitting any disclosure or use of information otherwise prohibited by applicable law.
- **5. Reporting Date.** Performance Measurement Reports will be distributed on the 27th day of the month following the reporting month for Aggregate CLEC and Aggregate Affiliate Reports, and the 29th day of the month following the reporting month for CLEC Specific Reports (or, if the 27th or 29th day of the month is a Saturday, Sunday or holiday observed by Verizon, the next Verizon business day).
- **6. CLEC General Obligations.** CLECs shall comply with all of the obligations imposed upon them by the Guidelines, including, but not limited to, the obligation to provide timely, accurate forecasts for interconnection trunks (both "CLEC to Verizon" and "Verizon to CLEC") and collocation.

			Proposed Change to NY C2C Guidelines for VA C2C	
Item#	Metric	Name	Guidelines	Rationale for Change

1	PO-1	Pre-Order	Modify Geography to reflect VA.	Guidelines apply to VA not NY.
	OR-1 thru OR-	Ordering	7 2 1 7	
	9			
	PR-1 thru PR-	Provisioning		
	9			
	MR-1 thru	Maintenance		
	MR-5			
	NP-1, 2	Network Performance		
	BI-1, 2, 3	Billing		
	OD-1	Operator Services/DA		
2	PO-	Pre-Order	Reformat and explicitly state	Clarifies and makes easier to read
	1,2,3,4,6,7,8		Performance Standard for sub-	Performance Standard for sub-metrics.
	OR-1,2,4,6	Ordering	metrics.	
	PR-1,2,3,4,6,8	Provisioning		
	MR-2,3,4	Maintenance		
	NP-1,2	Network Performance		
	BI-1	Billing		
3	PO-1	Response Time OSS	Deleted word "Simulated" from	"Actual" transactions, not "simulated"
			Formula section.	transactions, are measured for CLECs.
4	PO-2	OSS Interface Availability	Modify Geography to reflect	Guidelines apply to VA not NY.
			Potomac states combined	Simulated transactions used to
			reporting, i.e., DC, MD, VA, and	calculate metric result are not state-
			WVA combined data.	specific.
5	PO-3	Contact Center Availability	Modify description of how calls	New description more consistent with
			are answered.	the actual operation of the ordering
				center serving VA.
6	PO-3	Contact Center Availability	Under Performance Standard,	In NY, this metric measures Speed of
			Center Hours of Operation, delete	Answer for Ordering and Repair only.
			Order Entry Assistance, Order	Billing and Collections and System
			Processing Assistance, Billing and	Administration are not pertinent to
			Collections, and System	this metric. The National Market
			Administration. Add National	Center (NMC) serving VA is different
			Market Center hours of operation.	from the NMC serving NY. Order
				Entry Assistance and Order
				Processing Assistance are covered
				under the VA NMC.

			Proposed Change to NY C2C Guidelines for VA C2C	
Item #	Metric	Name	Guidelines	Rationale for Change

7	PO-5	Avg Notification of Interface Outage	Modify Geography to reflect OSS interfaces serving VA combined	The Guidelines apply to VA, not NY. Electronic interfaces serve multiple
8	PO-6 PO-7	Software Validation Software Problem Resolution	Remove NY specific language.	jurisdictions. NY language not appropriate for VA. Clarification change.
9	PO-7	Timeliness	Add language to Exclusions to specify "Failed" pre-order and order transactions.	Clarification change.
10	PO-8	Manual Loop Qualification	Add Exclusion to exclude Weekend and Holiday hours.	This Exclusion was inadvertently omitted from NY C2C Guidelines.
11	PO-8-01 PO-8-02	Manual Loop Qualification Engineering Record Request	Rename sub-metrics from "Average Response Time" to "% On-Time" and modify numerator description accordingly. Add a footnote indicating that implementation of PO-8-01 is tied to development of a separate OSS transaction.	The standards for these sub-metrics are 95% of request responses to be provided within a specified interval (48 or 72 hours). However, the original measurement measured not percentage of requests responded to within the specified interval, but average completion time. The revised numerator measures percentage completed within the specified interval and provides measurement data compatible with the standard. Footnote added for clarification.
12	OR-1	Order Confirmation Timeliness	Delete NY SOP hours and add VA SOP down-time hours.	The SOP (service order processing) system used in NY is different from
	OR-2	Reject Timeliness		the one used in VA.

Item #MetricNameGuidelinesRationale for Cha	nge
Item# Metric Name Guidelines Rationale for Cha	nge

13	OR-1-11	Average FOC Time	Fixed Numerator and Denominator	Correction.
	OR-1-12	% On Time FOC	language to be consistent with	
	OR-1-19	% On Time Response	Products and corresponding	
			intervals.	
14	OR-2	Reject Timeliness	Under Definition, replace "DCAS	DCAS is not used in VA.
	OR-3	Percent Rejects	or Request Manager" with "EDI or	Furthermore, EDI and Web GUI more
			Web GUI".	accurately describe the ordering
				interface.
15	OR-3	Percent Rejects	Change metric title to "%	New title more consistent with
			Resubmission Not Rejected."	Performance Standard.
16	OR-5	Percent Flow-Through	Remove language from Definition	This language should have been
			regarding the non-flow-through of	removed with the NY 12/22/00
			pending orders. Replace "DCAS	compliance filing. DCAS is not used
			or Request Manager" with "EDI or	in VA. Furthermore, EDI and Web
			Web GUI".	GUI more accurately describe the
				ordering interface.
17	OR-6	Order Accuracy	Remove DCAS language from	Clarification change. DCAS is not
			Methodology. Specify "Verizon"	used in VA.
			errors in numerator.	
18	OR-6-03	% Accuracy – LSRC (Interim	Delete sub-metric.	This measure was introduced in NY as
		Measure)		an interim measure because Verizon
				NY did not have an automated
				capability to measure % LSRCs resent
				due to Verizon error. However, in
				VA, Verizon has the capability to
				measure % LSRCs resent due to
				Verizon error and will implement this
				measurement ("OR-6-03 % Accuracy-
				LSRC (Long Term Measure)").
				Therefore, the interim measure is not
				needed.

			Proposed Change to NY C2C Guidelines for VA C2C	
Item #	Metric	Name	Guidelines	Rationale for Change

19	OR-7-01	% Order Confirmation/Rejects Sent within Three (3) Business Days	Add metric name for OR-7-01.	Clarification change.
20	PR-1-01 PR-2-02	Average Interval Offered Average Interval Completed	Correct standard for PR-1-01 and 02, UNE 2 Wire xDSL Line Sharing, to be Parity with Retail (VADI).	Correction. This was a NY consensus item.
21	PR-2	Average Interval Completed	Add Exclusion for 2 Wire Digital Service and 2 Wire xDSL Service orders missed due to facility reasons.	This Exclusion was a NY consensus item and was inadvertently omitted from the NY C2C Guidelines.
22	PR-3	Completed within Specified Number of Days (1-5 Lines)	Clarify Exclusion for orders missed due to facility reasons to apply to 2 Wire Digital Services and 2 Wire xDSL Services only.	Clarification change.
23	PR-3	Completed within Specified Number of Days (1-5 Lines)	Delete Footnotes 23 through 25. Remove 2 Wire xDSL Line Sharing as a Product under PR-3- 07.	These footnotes and this measure are not necessary. Effective May 1, 2001 the standard interval for Line Sharing No Dispatch orders of 1 to 5 lines is 3 business days. Therefore, Line Sharing No Dispatch 1 to 5 lines will be measured under sub-metric PR-3-03.
24	PR-4	% Missed Appointment	Clarify Exclusion for orders missed due to facility reasons for PR-4-04 and 14 to apply to 2 Wire Digital Services and 2 Wire xDSL Services only.	Clarification change.
25	PR-4-02	% Missed Appointment – Verizon-Total	Add Retail DS1 and Retail DS3 products.	Correction to NY Guidelines. Performance Standard specifies Retail compare for UNE IOF is DS3 and for UNE EEL is DS1.

			Proposed Change to NY C2C Guidelines for VA C2C	
Item#	Metric	Name	Guidelines	Rationale for Change

26	PR-4-03	% Missed Appointment – Customer	Add Retail DS1 product.	Correction to NY Guidelines. Performance Standard specifies Retail compare for UNE EEL is DS1.
27	PR-4-01 PR-4-02 PR-4-03	% Missed Appt – TotalAverage Delay Days – Total% Missed Appt – Customer	Add word "trunks" to Description, Numerator, and Denominator.	Clarifies that "trunks," not "trunk orders," are counted.
28	PR-4-05	% Missed Appointment – Verizon-No Dispatch	Delete Retail 2 Wire xDSL Loops product.	Not required since there is no UNE 2 Wire xDSL Loops product. Furthermore, 2 Wire xDSL Loops for the most part require a dispatch.
29	PR-4-14	% Completed On Time	Clarify 2 Wire xDSL pertains to 2 Wire xDSL Loops.	Clarification change.
30	PR-5	Facility Missed Orders	Add word "trunks" to Description, Numerator, and Denominator.	Clarifies that "trunks," not "trunk orders," are counted.
31	PR-6	Installation Quality	Replaced "STARMEM" with "SERVICE".	"SERVICE" not "STARMEM" is used in VA.
32	PR-6	Installation Quality	Specify Exclusion pertaining to CLECs that do not participate in cooperative testing applies to submetric PR-6-01 only.	Clarification change.
33	PR-6	Installation Quality	Under Performance Standard, specify for PR-6-01, UNE 2 Wire xDSL Loops, that the comparison is to Retail POTS-Dispatch. Add POTS-Dispatch under Retail/VADI Products.	Clarification of the retail comparison.
34	PR-8-01 PR-8-02	Open Orders in a Hold Status	List Specials DS0 under Retail/VADI products and remove 2 Wire xDSL Loops.	Change is consistent with Performance Standard, which specifies for UNE 2 Wire xDSL Loops that the Retail comparator is Specials DS0.
35	PR-9	Hot Cut Loops	Remove from Performance Standard reference to sub-metrics that are no longer included under PR-9 (PR-9-02 through 07 and PR- 9-10).	Correction.

			Proposed Change to NY C2C Guidelines for VA C2C	
Item#	Metric	Name	Guidelines	Rationale for Change
36	PR-9-01	% On Time Performance – Hot Cut	Delete second Description.	Except for one sentence, second Description is redundant with first Description and therefore not necessary. The one sentence difference was added to the first Description.
37	PR-9-08	Average Duration of Service Interruption-Hot Cuts	Remove the Specials language from numerator.	Sub-metric measures Hot Cuts which, by definition, are POTS Loops. The reference to Specials is inaccurate.
38	MR-1	Response Time OSS Maintenance Interface	Specify Caseworker R2 under Methodology. Add footnote to Geography section.	Caseworker R2, not Caseworker, is used in Virginia. Clarification of VZ Retail reporting at the Potomac level (VA, MD, DC, and WV states combined). Caseworker R2 is not able to identify transactions by state.
39	MR-3-01,02 MR-4- 02,03,08	% Missed Appts Trouble Duration Intervals	Add to list of Retail/VADI products, POTS-Total.	This product provides a parity comparison for UNE Loop.
40	NP-1	% Final Trunk Group Blockage	Under Performance Standard, delete End User References.	References not applicable to VA and also not relevant to Performance Standard.
41	NP-3	Switching Performance	Modify to reflect that individual state switching performance is provided in accordance with state specific requirements.	Data is state specific.
42	Glossary	Basic Edits	Replace references to DCAS and former BA North states.	DCAS not applicable to VA.
43	Glossary	BFR	Delete.	BFR not pertinent to Guidelines. The Guidelines do not contain BFR related measures.
44	Glossary	Common Trunks	Tailor description to reflect VA and former BA South states.	Clarification change.
45	Glossary	Dedicated Trunks	Tailor description to reflect VA and former BA South states.	Clarification change.
46	Glossary	DCAS	Delete.	DCAS not applicable to VA.
47	Glossary	Dispatched Orders	Remove reference to 10 lines.	Language outdated.

Draft VA Carrier-to-Carrier Guidelines

Item#	Metric	Name	Proposed Change to NY C2C Guidelines for VA C2C Guidelines	Rationale for Change
48	Glossary	Loop Qualification	Add xDSL services	Updated definition to include xDSL services.
49	Glossary	Mechanized Flow-Through	Remove reference to DCAS.	DCAS not applicable to VA.
50	Glossary	Orders>10 Lines	Change 10 Lines to 6 Lines.	Language outdated.
51	Glossary	Retail/VADI	Add Definition for Retail/VADI.	Clarification change.
52	Glossary	Suspend/Restore Orders	Remove references to New York. Add generic definition.	Clarification change.
53	Glossary	Complex	Further describe 2 Wire xDSL Services to be 2 Wire xDSL Loops and 2 Wire xDSL Line Sharing for UNE.	Clarification change.
54	Appendix C	Pre-Ordering Details	Remove DCAS references. Update process and delete file names.	DCAS not used in VA. Process and file names outdated.
55	Appendix D	Bona Fide Request Process	Delete and replace with Holiday Schedule.	BFR not pertinent to Guidelines. The Guidelines do not contain BFR related measures. Unlike NY, where the BFR process is set out in a tariff, in VA the BFR process is set out in interconnection agreements and through negotiation may differ from the NY Appendix D process. Holiday Schedule pertinent to Guidelines.
56	Appendix E	LNP Process	Remove references to Centrex.	Outdated language.
57	Appendix G	Flow-Through Scenarios	Replace with reference to Verizon website for most current information.	Referencing the Verizon website for this information ensures CLEC access to the most current information.
58	Appendix K	Statistical Methodology	Change "incumbent LEC" terminology to "Verizon".	Use of "Verizon" more appropriate for VA.
59	Appendix M	Order Accuracy Details	Delete references to LSRC Accuracy and "Short Term Solution." Also delete NY specific references.	The "Short Term Solution" is not applicable to Verizon VA. Verizon VA will implement the "Long Term Measure" identified in the NY C2C Guidelines.
60	Appendix N	Table of Measures, Sub- Metrics and Product	Replace with note that Verizon VA will submit periodic status reports.	This appendix provides a status of metrics and is a snap-shot which will

Item#	Metric	Name	Proposed Change to NY C2C Guidelines for VA C2C Guidelines	Rationale for Change
Itelli #	MEHIC	Traine	Guidennes	Rationale for Change
		Disaggregation		be out-of-date shortly after it is set out in the Guidelines. Therefore, Verizon VA will submit periodic status reports.
61	Exhibit 1	Additional Provisions	Add to Guidelines.	Provides valuable information including Force Majeure and Confidentiality provisions.